

**BILL OF QUANTITIES / ESTIMATE FOR FURNISHING WORK OF
REGIONAL OFFICE, MATHURA.**

S.NO.	DESCRIPTION	UNIT	QUANTITY	RATE	AMOUNT
1	GLASS BARRIER :- Providing and fixing glass barrier in front of counters made out of 12mm thick float latched glass with polished edge and the champhering of the edges at the distance of 25mm from edges of the glass supported at the end of each counter with teak wood supporters of appropriate size at ends as per design approved by bank.	SQ.FT	100.00		
2	SIDE UNITS/ CREDENZA :- Providing & placing in position box type side units /Credenza (2'-6"/4'-0" ht. & 18" deep) made out of 19mm approved board with 1mm laminate. The sides, partition, top, shelves & bottom shall be made out of 19mm thk. approved board and back made out of 6mm thk. approved ply. Item shall have one 6" deep drawer on top and file drawer below complete with handles etc. The shutters shall be made out of approved board with teak/cedar wood edges. Teak /cedar wood lipping shall be provided on all exposed ends of board. All exposed surfaces of teak/cedar wood lipping shall be finished with melamine polish while inner surfaces shall be finished with approved 1.0 mm thick laminate. A skirting of 3" high finished with approved laminate to be provided. (for the purpose of contractors bill front elevation area is to be measured)	Sq.ft.	1080.00		
3	SUGGESTION BOX :- P/F in position of suggestion box made out of 19mm thick approved board with 1mm thick laminate(as approved) on all exposed surfaces and T.W lipping duly melamine polished etc. complete. The item shall also include locking arrangement and other required hard ware etc.complete internal surfaces of the box shall be finished with 1.00mm thick laminate.	No	2.00		

4	<p>LAMINATED PARTITION :- Providing, fabricating & fixing partly glazed both side laminated partition (low height up to 4'-0"/ full height) made out of 2"x2" kail wood underframing at 2'-0" centre to centre in both directions, fixed rigidly at floor & ceiling, covered with 6mm approved ply & 1mm thk. Laminate in two different shades (as approved by the Architect/ Bank) on both sides. All kail wood shall be treated to resist termite. The glass shall be 6mm th.clear float glass to be fixed at 3' height, complete with itching as per design . All teak /cedar wood work shall have melamine polish.The item shall include making provisions for electrical, computer & other services points / out lets. The partition wood work shall include complete anti termite treatment, door shutters in partition wherever required and complete hardware such as hinges, tower bolts (excluding locks and door closure) etc of approved make. The grooves in the partition shall be @2' C/C vertically /horizontally or as per design / direction of the architect / bank. Low ht. partition shall be 3' high wooden and 1'-0" high 10 mm glass work on top. Item shall also include 3" high skirting finished with 1 mm th. laminate of approved shade.</p>	Sq.ft.	3300.00		
5	<p>NOTICE BOARD :- P/F in position notice board of size 900x1500x150mm. The side shall be made out of 19mm thick approved board with 1mm thick laminate(as approved) on all exposed surfaces. It shall have 12mm thick tack board (cellotex or equivalent) wrapped with streched blazer cloth (raymonds of approx Rs. 200.00 per mtrs.) of approved colour and pattern by Bank. It shall be fixed with the help of dash fasteners of required size.</p>				
	<p>The front shall have 6mm thick float glass sliding shutter in two parts. It shall also have 19mm wide two track aluminium channels for sliding arrangements, all round along with locking arrangements.</p>				

	All the exposed edges of board and ply shall be provided with 6mm thick teak/cedar wood lipping which shall be polished and other internal surfaces to be painted with enamel paint with two or more coat over a coat of primer with the desired shade. The item includes hanging and proper grouting of the notice board in the desired place property as per requirement of the Bank. Complete in all respect.	No.	4.00		
6	A.G.M.'S TABLE :- Providing & fixing in position A.G.M. table of size 6'-6"x 3'-6" by using 19 mm thick approved board for top having double layer of 19.mm board all around the table covered with polished teak wood lipping. All other horizontal and vertical members shall also be of 19mm th. board. Telescopic CPU stand / Keyboard tray and one drawer shall be provided with ball bearing slides etc. Footrest made with T.W. member of size 4"x1.5" finished with polish. All exposed surfaces to be finished with 1mm thick laminate of approved make & shade and all exposed edges of table top & verticals to have T.W. lipping of appropriate/approved size & shape . All exposed T.W. sections to be melamine polish and internal surfaces to be have 1mm thick laminate as directed.The table shall have one cabinet below drawer unit with shutter and necessary hardware etc. complete. The item shall also include 10 mm glass on table top.	Nos.	1.00		
7	D.M'S TABLE :- Providing & fixing in position D.M table of size 5'-6"x 3'-0" by using 19 mm thick approved board for top having double layer of 19.mm board all around the table covered with polished teak wood lipping. All other horizontal and vertical members shall also be of 19mm th. board. Telescopic CPU stand / Keyboard tray and one drawer shall be provided with ball bearing slides etc. Footrest made with T.W. member of size 4"x1.5" finished with polish. All exposed surfaces to be finished with 1mm thick laminate of approved make & shade and all exposed edges of table top & verticals to have T.W. lipping of appropriate/approved size & shape . All exposed T.W. sections to be melamine polish and internal surfaces to have 1.0 mm thick laminate.The table shall have one cabinet below drawer unit with shutter and necessary hardware etc. complete. The item shall also include 10 mm thick glass on table top.	Nos.	3.00		

8	<p>C.M'S TABLE :- Providing & fixing in position CM table of size 5'-0"x 3'-0" by using 19 mm thick approved board for top having double layer of 19.mm board all around the table covered with polished teak wood lipping. All other horizontal and vertical members shall also be of 19mm th. board. Telescopic CPU stand / Keyboard tray and one drawer shall be provided with ball bearing slides etc. Footrest made with T.W. member of size 4"x1.5" finished with polish. All exposed surfaces to be finished with 1mm thick laminate of approved make & shade and all exposed edges of table top & verticals to have T.W. lipping of appropriate/approved size & shape . All exposed T.W. sections to be melamine polish and internal surfaces to have 1.0 mm thick laminate.The table shall have one cabinet below drawer unit with shutter and necessary hardware etc. complete. The item shall also include 10 mm thick glass on table top.</p>	Nos.	9.00		
9	<p>Officer's TABLE :- Providing & fixing in position Officer table of size 5'-0"x 2'-6" by using 19 mm thick approved board for top having double layer of 19.mm board all around the table covered with polished teak wood lipping. All other horizontal and vertical members shall also be of 19mm th. board. Telescopic CPU stand / Keyboard tray and one drawer shall be provided with ball bearing slides etc. Footrest made with T.W. member of size 4"x1.5" finished with polish. All exposed surfaces to be finished with 1mm thick laminate of approved make & shade and all exposed edges of table top & verticals to have T.W. lipping of appropriate/approved size & shape . All exposed T.W. sections to be melamine polish and internal surfaces to have 1.0 mm thick laminate.The table shall have one cabinet below drawer unit with shutter and necessary hardware etc. complete. The item shall also include 10 mm thick glass on table top.</p>	Nos.	24.00		
10	<p>Same as above but reception table as per design provided by bank / architect of size 7'-6" X 2'-0".</p>	Nos.	1.00		

11	VERTICAL BLINDS : Providing and fixing of vertical blinds made out of 100mm wide (Scotch - Guarded) fabric louvers (as per shade approved by the Architect) including Head rail, control unit carriers, Tilter, Traverse cord, Tilt rod bottom Machanism, Installation brackets etc complete.	Sqft	750.00		
12	DOOR CLOSER : P/ F heavy duty Hudraulic wall mounted door closers (UL rated) 68 KG (product code 1938) of Godrej or equivalent).	No	15.00		
13	MORTISE LOCK : P/F SS matt finish NEH 05 - 200 mm door handle set with lock body 2C (Product code 7110) of Godrej or equivalent.	No	15.00		
14	DOOR STOPPER : P/ F door stopper (ISI mark) of brass.	No	25.00		
15	MAIN DOOR : Providing and fixing full Glass door with 12 mm thick toughned glass fixed on top and bottom with patch fittings. The item shall have heavy duty floor spring (80 Kg.) of approved make (Godrej),SS D- type 25 mm dia - 300 long door handles, locking arrangement etc. complete with other necessary hardwares required for proper functioning of the door.	Sq.ft.	65.00		
16	Same as above but full glass fixed partition with SS fittings.	Sq.ft.	100.00		
17	WALL PANELLING : Providing and fabricating wall pannelling 'with 2"x1.5" kail wood framing @ 2'-0"x 2'-0" size in both direction covered with '6mm thk ply & 1mm th laminate of approved shade.	Sq.ft.	3650.00		
18a	FALSE CEILING : Providing and fixing in position Arm strong false ceiling as per design in 600x600 mm x16 mm th. (Dune Micro look) tile with silhouette type frame work in combination with gypboard false ceiling as per design as specified by Armstrong company with suspenders wherever required.Making necessarry frame work for AC ducting, if any, and necessarry cut out for difusers and light fittings, taping & finishing to proper line and level, including making grooves and trap doors for AC units in approved grade 12 mm th. Ply wood with stain less steel hinges & locks with molding 1"x1" for edges including finishing with white plastic emulsion paint etc. complete in all respect.	Sq.ft	4250.00		

18b	Same as above but including Rock-wool 50mm thick with chicken mesh above the grid in conference room.	Sq.ft	750.00		
19	Suplly and fixing of Conference table as per design made out of 19mm BWP board and finished with 1.0mm approved laminate same as specifications but 2'-0" wide provisions for microphone and its wiring etc. complete.	Rft.	64.00		
20	Supplying Planter 15'x15"x15" made of 19mm comm. Ply with 1mm laminate and polished teak wood moulding 25x 8 mm on top & lining of aluminum sheet..	No.s	10.00		
21	Supply & placing of 3 & 2 -seater's soffa in Cabins & waiting area made out of wooden frame, spring, canvas etc in sit & back, 100mm foam in sheet & 75mm in back of 40 density and soffa cloth as approved by bank or architect(cloth should not less than 500/ metre). The item shall also include polishing etc complete.	seat	17.00		
22	Supply & placing of centre table of size 4'-0" X 3'-0" in A.G.M. Cabin made out of teak wood and table top with 10mm glass. The item shall also include polishing etc complete.	NO	1.00		
23	Supply & fixing of pin-up board of size (3'-0" X 1'-6") on front partition of cubical tables.	NO	24.00		
24	Acoustical paneling:- Providing & fixing panelling with G.I. Framework in both direction up to ceiling and 50mm thick rock-wool Of 48kg/m with chicken mesh in between the grid covered with 12mm thick approved ply and 1.0mm thick laminate upto door height. Above the door height finishing will be done with 12 mm thick gypsum tiles including two or more coats of plastic emulsion paint etc complete.	Sqft	1175.00		
			TOTAL (RS.)		
NOTE -: All work should be done as per Bank's Specification					
-: GST shall be paid extra as per Government norms at the time of billing					