संदर्भ सं./Ref.No. CIBM/ADMIN/MPL/395/2021

## **CORRIGENDUM-1**

Corrigendum-1 to Tender Ref. No.CIBM/ADMIN/TENDER/02-2021 dated 10.02.2021 for Design, Supply, Installing, Testing and Commissioning of 8- passenger lift/ elevator at CIBM, Manipal.

It is decided to amend the following in respect of the above tender:

Description	Existing details	Amended details
Notice Inviting Tender (NIT), Page No.3, Point No.2 (Earnest Money Deposit EMD amount), Page No.4, Table Sl. No.A.3 (EMD), Page No.5, Table for Details of the Tender (Earnest Money Deposit) Page No.5, Table for details of the Tender,	1% of tendered amount by way of Demand Draft drawn in favour of "Canara Bank, CIBM, Manipal", payable at Udupi/Manipal obtained from any scheduled Bank  02.03.2021 up to 03.30 pm	Rs.15,000/- by way of Demand Draft drawn in favour of "Canara Bank, CIBM, Manipal", payable at Udupi/Manipal obtained from any scheduled Bank  15.03.2021 up to 03.30pm
Last date and time of submission of the tender, Page No.9, Annexure 2, Point No.5  Page No.5, Table for details of the Tender, date and time of opening of the tender - Technical bids, Page No.9, Annexure 2, Point	O2.03.2021 at 4.00 PM (In case bid opening day happens to be holiday, the bid will be opened on the next working day of the Bank)	
No.6 Page No.55, Point No.5, Guides/ Guides Rails	The guide rails shall be minimum 16mm Tongued & Grooved type.	Carry out the works as per OEM standards
Page No.55, Point No.7 Safety Devices	Terminal Buffers Suitable spring buffers mounted on RCC foundation blocks shall be provided in the pit in compliance with ANSI/ASME/CENEN-81 /JIS codes	Comply as per IS 14665

Contd..2

दिनांक/Date: 25.02.2021

## संदर्भ सं./Ref.No. CIBM/ADMIN/MPL/395/2021

::2::

दिनांक/Date: 25.02.2021

Description	Existing details	Amended details
Page No.57, Point		Comply as per IS -14665
No.10.2, Fire Safety	fire resistance rating of	
Requirements	one hour.	
Page No.59, 5. Lift shaft Drawing	1. Car Size - 1.3m×1.1m 2. FW/FW1 - 0.375m	Car size should be such that it does not hamper the free movement of specially abled persons using the lift car and comply IS standards.
	* 40	The available F-F ht at GF is 2.39 meter as mentioned in the plan, but the required height as per OEM standards will be made available at the time of working in the Ground floor by excavation & other means
Page No.65, Annexure - 5, Sl. No. 10	Pit depth -1600mm	Consider pit depth = 1600mm instead of 1300mm
Page No.65, Annexure -	Door Opening -	Door opening
5, Sl. No. 16	900mm×1200mm	900mm×2000mm
Page No.66, Annexure - 5, Sl. No. 20	VF Regenerative	This feature is removed from technical specifications, hence neglect the condition
Page No.67, Annexure -	Mirror on rear side	Since rear wall is not present
5, Sl. No. 26	of the wall	this feature is removed from the technical specifications
Page No.68, Terms of price bid, Point No.4	Price quoted shall cover the cost of dismantling the existing elevator of OLYMPUS make and removing them from site of work. No extra payment on this amount shall be entertained/ paid. No material of the dismantled elevator shall be used in erection of new elevators.	The condition is removed as there is no existing elevator.

All other instructions and terms and conditions of the above RFP remain unchanged. Please take note of the above Amendments while submitting your response to the subject tender.

(Prakash Pradhan) Asst. General Manager

ولما