CANARA BANK

INVITATION TO TENDER

ONLY FOR EMPANEL CONTRACTORS FOR

COMPOSITE WORKS

(CATEGORY A & B ONLY)

<u>OF</u>

CIRCLE OFFICE KOLKATA

TENDER FROM ANY OTHER CONTRACTOR WILL BE SUMMARILY REJECTED

INSTRUCTION TO BIDERS

AND

GENERAL CONDITIONS OF CONTRACT

FOR

COMPOSITE WORKS (CIVIL, FURNISHING & ELECTRICAL)

AT

CANARA BANK – ENTALLY BRANCH, KOLKATA

,	
NAME OF THE CONTRACTOR:	
	• • • • • • • • • • • • • • • • • • • •
ADDRESS:	

TENDER NO.: 09/23-24/SP

Date: 11-05-2023

NOTICE INVITING THE TENDER

То,	
M/s	
furnishing & electrical Works at ENTALLY Brazelet Documents may be obtained a	invited from panel Contractors for Civil , anch . t free of cost from the Premises & Estate ata during working hours from 11-05-2023
Earnest Money Deposit :	NIL
Period of completion :	30 days
Last date, time and place for : Submission of tender	On or before 4 pm, 19-05-2023 to The Asst. General Manager, Premises & Estate section Canara Bank, Circle Office Kolkata
Time and date of opening of tender :	11 am on 20-05-2023
The Bank will not be bound to accept the accept or reject any or all the tenders with	he lowest tender and reserves the right to hout assigning any reason whatsoever.
	Asst. General Manager Premises & Estate Section Canara Bank, Circle Office Kolkata

GENERAL RULES & INSTRUCTIONS TO TENDERERS

Name of the work: Civil, Furnishing & Electrical Works to be carried out at ENTALLY Branch

The rates quoted shall also be inclusive of materials, labour charges, work contract tax, surcharge and all the taxes except GST.

GST WILL BE PAID EXTRA.

The rates quoted by the tenderer shall hold good till the completion of the work from the date of issue of the "WORK ORDER" and no enhancement in the rates are allowed during the period of execution of the work under any circumstances. The rates quoted shall also cover for the work to be executed before and after office hours and also on holidays.

The time stipulated for the completion of the work is 30 days from the date of issue of the WORK ORDER and the work is to be carried out as per the convenience of occupants without disturbing other occupants of the building.

TENDERS:

The entire set of tender paper issued to the tenderer should be submitted fully priced and also signed on the last page together with initials on every page. Initials / signatures will indicate the acceptance of tender papers by the tenderers.

The schedule of quantities shall be filled in as follows:

- The "rate" column to be legibly filled in ink in both English figures and words.
- 'Amount' column to be filled in for each item and the amount for each sub-head as detailed in the "schedule of quantities".
- All corrections to be initialed.
- o The "Rate" column for all the items shall be filled up.
- The "Amount" column for the items for which the quantities are not mentioned shall not be filled up.
- o In case of any errors / omissions in the quoted rates, the rates mentioned in the tender in words shall be taken as correct rates.

No modifications, over-writings or corrections can be made in the tender papers by the tenderer, but may at his option offer his comment or modifications in a separate sheet of paper attached to the original tender papers.

The Bank reserves the right to reject the lowest or any tender or all of the tenders for each section or to split up and distribute any item of work to any specialist firm or firms, without assigning any reason.

The tenderers should note that tender is strictly on the item rate basis and their attention is drawn to the fact that the rates for each and every item should be correct, workable and self – supporting. If called upon by the bank, detailed analysis of any or all the rates shall be submitted. The architects/bank shall not be bound to accept the contractor's analysis.

The Quantity mentioned in the BOQ is approximate measurements. The works will be paid for as "measured work" on the basis of actual work done and not as "lump sum" contract.

All the items of work described in the schedule of quantities are to be deemed and paid as complete works in all respects and details including preparatory and finishing works involved, directly, related to and reasonably detectable from the drawings, specifications and schedule of quantities and no further extra charges will be allowed in this connection. In the case of lump-sum charges in the tender in respect of an item of works, the payment of such items of work will be made for the actual work done on the basis of lump-sum charges as assessed to be payable by the architects/bank.

The bank has power to add or delete any work or described in specifications or included in schedule of quantities and intimates the same in writing but no addition, omissions or variation shall be made by the contractor without authorization from the bank. No variation shall vitiate the contract. The bank reserves the right to delete any of the items in the tender without assigning any reasons whatsoever.

The tenderer shall note that his tender shall remain open for consideration for a period of 90 days from the date of opening of tender.

AGREEMENT

The successful contractor is required to sign agreement as may be drawn up to suit the local conditions and shall pay for all the stamps and legal expenses incidental thereto. The original will be kept with the Bank and duplicate with contractor.

EARNEST MONEY AND SECURITY DEPOSIT:

There is NO Earnest Money Required to deposite/ submit along with the bids. Retention Money shall be deducted from the final bill at 3% of the gross value of bill. The Retention amount will be refunded to the contractor 15 days after the end of defects liability period provided he has satisfactorily carried out all the work and attended to the entire defect in accordance with the condition of the contract. No interest is allowed on Retention Money.

A part of the Security Deposit if and as decided by the constituent bank can also be furnished in the form of a Bank Guarantee on the bank other than that of the constituent bank.

CONTRACTOR TO PROVIDE EVERYTHING NECESSARY:

The contractor shall provide everything necessary for the proper execution of the work according to the intent and meaning of the drawings, schedule of the quantities and specifications taken together weather the same may or may not be particularly shown or described therein provided that the same can reasonably be inferred there from and if the contractor finds any discrepancies therein he shall immediately and in writing, refer the same to the Architects/Bank whose decision shall be final and binding.

The rates quoted against individual items will be inclusive of everything necessary to complete the said items of works within the contemplation of the contract, and beyond the unit price. No extra payments will be allowed for incidental or contingent labour and/or materials inclusive of all taxes and duties whatsoever except for specific items, if any, stipulated in tender documents

The contractor shall supply, fix and maintain at his own cost, for the execution of any work, all tools, tackles, machineries and equipments and all necessary scaffolding, staging and lighting by night as well as by day required not only for proper execution and protection of the said work.

The contractor shall take down and remove any or all such scaffoldings as occasion shall be required or when ordered to do so, and shall fully reinstate and make good all matters and things disturbed during the execution of work to the satisfaction of architect/bank.

The contractor shall all times give access to workers employed by the bank or any men employed at site and to provide such parties with proper sufficient and if required, special scaffolding and ladder and provide them lighting as may be required to enable such workmen to inspect the work, lay or fix pipes, Civil & furnishing wiring, special fittings etc. The quoted rates of tenderers shall accordingly include all these above-mentioned contingent works.

LIQUIDATED DAMAGES:

Should the work be not completed to the satisfaction of bank within the stipulated period, the contractor shall be bound pay the bank a sum calculated as given below by way of Liquidated Damages after the expiry of completion date

.1.00% of the estimated amount shown in the tender per week subject to a ceiling of 10% of the accepted contract sum.

TIME PERIOD FOR COMPLETION: 30 days from the date of award of work.

FINAL PAYMENTS

The final bill shall be accompanied by a certificate of completion from the Occupant/Bank Officials. Payments of the final bill shall be made after deduction of retention money as specified in clause 9 of these conditions which sums shall be refunded after the completion of the defects liability period after receiving the banks certificate that the contractor has rectified all defects to the satisfaction of the

banks. The acceptance of payments of the final bill by the contractor would indicate that he would have no further claims in respect of the work executed.

ESCALATION:

The rates quoted shall be firm throughout the tenure of the contract [including extension of time, if any granted] and will not be subject to any fluctuation due to increase in cost of materials, labour, sales tax, octroietc, unless specifically provided in these documents.

CONTRACTORS EMPLOYEES:

The contractor shall employ technically qualify and competent supervisors for the work who shall be available [by turn] throughout the working hours to receive and comply with the instructions of the bank officials. The contractor shall engage at least one experienced engineer, as site in-charge for the execution of the work the contractor shall employ in connection with the work persons having appropriate skill or ability to perform their job efficiently. The contractor shall employ local labours on the work as far as possible. No laborers below age of 16 and who is not an Indian national shall be employed on the work. Any laborers supplied by the contractor to be engaged on the work on daywork basis either wholly or partly under the direct order or control of bank or its representative shall be deemed to a person employed by the contractor.

The contractor shall comply with provision of all labour legislation including the requirements of

- a. Payments of minimum wages act
- b. Employers liabilities
- c. Workmen's compensation act
- d. Contract labour (regulation and abolition) act, 1970 and central rules 1971
- e. Apprentices act 1961
- f. Any other act or enactment relating thereto and rules framed there under from time to time

The contractor shall keep the bank saved harmless and indemnified against claims if any of the workmen and all costs and expenses as may be incurred by the bank in connection with any claim that may be made by any workmen.

The contractor shall comply at his own cost with the order of requirement of any health officer of state or any local authority or of the bank regarding the maintenance of proper environmental sanitary condition of the area.

The contractor shall arrange to provide first aid treatment to the laborers engaged on the works. He shall within 24 hrs of occurrence of any accident at or about the site or in connection with execution of work, report such accidents to the bank and also the competent authority where such report is required by law.

The contractor shall obtain all Risk Insurance Policy at their cost within 7 days of commencement of work, for the laborers/workmen working at the site including the work till the work is completed. The policy shall be in the joint name of the Bank and contractor and Bank's name shall appear First.

PAYMENTS:

The contractor, in the form prescribed by the bank shall prepare all the bills and submit the same to Bank with measurement of work. Normally one interim bill shall be prepared each month. Bank may release payment within 15 days of receipt of bills/after check measurement, after deduction of retention money, Income Tax etc. The contractor shall have a competent engineer at site for the supervision of the work.

The contractor shall have to make his own arrangements for watch and ward of the work/building, till the work is handed over to the bank.

The decision of the bank will be final and binding with regard to the quality of work is concerned.

The contractor is responsible for procuring the required materials for the work and stores the same at site at his cost and risk.

The amount stated in the interim certificate shall be the 75% of total value of the work executed up to date of the bill, less the amount to be retained by the bank as retention money. If the bank has supplied any materials or goods to the contractors, the cost of such materials will be progressively deducted from the amount due to the contractor on accordance with the quantities consumed in the

work. All the interim payments shall be regarded as payments by way of advance against the final payment only and not as payments for works actually done and completed and shall not preclude the requiring of bad, unsound or imperfect or unskilled work to be removed and taken away and reconstructed or re-erected or be considered as an admission of the due performance of the contract or any part there of if any respect or accruing of any claim nor shall it conclude, determine of effect in any way the power if the bank under conditions or any of them add to the final settlement and adjustment of the accounts or otherwise or in any other way or affect the contract.

The contractor shall submit the final bill within one month from the date of completion of the work. A certificate of completion from the bank shall accompany the final bill. The payment of the final bill shall be made after deduction of retention money as specified elsewhere in these documents.

ARBITRATION:

All disputes or differences of any kind whatsoever which shall at any time arise between the parties here to touching or concerning the works or the execution or maintenance thereof of this contract or the rights touching or concerning the works or the execution of maintenance thereof of this contractor or the construction remaining operation or effect thereof or to the rights or liabilities of the parties are arising out of or in relation thereto whether during or after determination foreclosure or branch of the contract[other than those in respect of which the decision of any person is by the contract expressed to be final and binding] shall after written notice by either party to the contract to the other of them and to the employer hereinafter mention to deal referred for adjudication to a sour arbitrator to be appointed as hereinafter provided.

For the purpose of appointing the sole arbitrator referred to above, the employer will send within 30 days of receipt of the notice, to the contractor a panel of 3 names of persons who shall be presently unconnected with the organization for which the work is executed.

The contractor shall on receipt of the names as aforesaid, select, anyone of the person's name to be appointed as a sole arbitrator and communicate his name to the employer within 30 days of the receipt of the names. The employer shall thereupon without any delay appoint the person as the sole arbitrator. If the contractor fails to communicate such selection as provided above within the period specified, the competent authority shall make the selection and appoint the selected person as the sole arbitrator.

If the employer fails to send to the contractor the panel of 3 names as a foresaid within the period specified, the contractor shall send to the employer a panel of 3 names of persons who shall be unconnected with either party. The employer shall on receipt of the name as a foresaid select anyone of the person's names and appoint him sole arbitrator. If the employer fails to select the person and appoint him as a sole arbitrator within 30 days of the receipt of the panel and inform the contractor accordingly, the contractor shall be entitled to appoint one of the persons from the panel as the sole arbitrator and communicate his name to the employer.

If the arbitrator as appointed is unable or unwilling to act or resigns his appointment or vacates his office due to any reason whatsoever another sole arbitrator shall be appointed as aforesaid.

The work under contract shall, however, continue during arbitration proceedings and payment due or payable to the contractor shall be withheld on account of such proceedings.

The arbitrator shall be deemed to have entered on the reference the data he issued notice to both the parties fixing the date of the first hearing.

The arbitrator may from time to time, with the consent of parties, enlarge the time or making and publishing the award.

The arbitrator shall give a separate award of each disputes or difference referred to him. The arbitrator shall decide each dispute in accordance with the terms of the contract and give a reasonable award. The venue of arbitration shall be such place as may be fixed by the arbitrator in his sole discretion.

The fee, if any, of the arbitrator shall, if required to be paid before the award is made and published, be half and half by each of the parties. The cost of the reference and of the award including the fees, if

PAGE No. 7

any, of the arbitrator who may direct to and by whom and in what manner, such costs or any part thereof shall be paid and may fix or settle the amount of costs to be so paid.

The award of the arbitrator shall be final and binding on both the parties.

Subject to aforesaid the provision of the arbitration act 1940 or any statutory modification or reenactment thereof and the rules made there under, and for the time being in force, shall apply to the arbitration proceeding under this clause.

The employer and the contractor hereby also agree that arbitration under the clause shall be a condition precedent to action under the contract with regard to the matters hereby expressly agreed to be so referred to arbitration.

Date:	Signature of the Contractor
	With seal and address

CANARA BANK # ENTALLY BRANCH & ATM # KOLKATA CIRCLE

BOQ FOR INTERIOR FURNISHING WORKS

SI No.	Description Of Item	Qnty.	Unit	Rate (Rs.)	Amount (Rs.)
1	Providing and fixing in position full height Glazad				,
	partition 65 mm thk. as indicated in the drawing				
	excluding the door made out of aluminium hollow				
	sections of 50mm x 50mm size 1.5mm thick of JINDAL /				
	INDAL make as internal framed structure placed				
	horizontally & vertically in 550 mm x 550 mm / 600mm x				
	600 mm center to center or as directed by the Architect.				
	The alternate corner vertical members of the partition				
	shall be taken upto the ceiling level (payment shall be				
	made for the partition measured below the false ceiling				
	level) and the same shall be anchored to the ceiling				
	securely with help of suitable cleats. Framework shall be				
	fixed with 6 mm thick marine grade ply (IS - 710) of				
	approved make on both sides finished as per following				
	specifications. The Partition shall be finished with 1.0				
	mm thick laminate of approved shade and make or				
	equivalent on both the sides. The glazing will be of 6				
	mm. thk clear glass fixed within 900 - 2100 mm. level.				
	There will be designed glass film over the glazing area				
	with required design, complete as directed by the				
	Architect. The item does not include the doors.	170.00	sq. ft.		
2	Providing and fixing in position full height solid				
	partition 65 mm thk. as indicated in the drawing				
	excluding the door made out of aluminium hollow				
	sections of 50mm x 50mm size 1.5mm thick of JINDAL /				
	INDAL make as internal framed structure placed				
	horizontally & vertically in 550 mm x 550 mm / 600mm x				
	600 mm center to center or as directed by the Architect.				
	The alternate corner vertical members of the partition				
	shall be taken upto the ceiling level (payment shall be				
	made for the partition measured below the false ceiling				
	level) and the same shall be anchored to the ceiling				
	securely with help of suitable cleats. Framework shall be				
	fixed with 6 mm thick marine grade ply (IS - 710) of				
	approved make on both sides finished as per following				
	specifications. The Partition shall be finished with 1.0				
	mm thick laminate of approved shade and make or				
	equivalent on both the sides. Rate shall be inclusive of				
	provision of pencil groove as directed by the Architect.				
	The item does not include the doors.	930.00	sq. ft.		

3	Providing & Fixing double skin low ht. partition with			
	wicket door (1200 mm. high) with electrical wire			
	management system, 900 mm. solid, then 300 mm.			
	partly glazed (as per drawing), made out of aluminium			
	hollow sections of 50mm x 50mm size 1.5mm thick of			
	JINDAL / INDAL make as internal framed structure			
	spaced not more than 600 mm. c/c bothways, double			
	skin partition fixed to aluminium frame made of 6 mm.			
	thk. approved marine grade ply (IS:710), finished both side with approved laminate with 1.5 mm. groove			
	design, 4" high laminated skirting etc., the vertical			
	support of 50 x 50 mm. frame to be extended upto 1200			
	mm., side & top faces to be covered with 65 x 15 mm.			
	CP teak wood moulding bead (curved at top) with 6 mm.			
	x 6 mm. polished groove. 300 mm. high x 12 mm. thk.			
	glass to be fixed to partition with 30 x 12 mm. teak			
	wooden bead with 6 mm. groove, all exposed teak			
	wood surface to be completed with natural colour high			
	polishing etc. all complete as per design, direction and			
	approval of the Architect.	150.00	sq. ft.	
4	Providing and fixing Solid Core Flush Door Shutter			
	(IS - 2202) of 35 mm thk. finished both side with 1 mm			
	thk. approved colour laminate (IS: 2046) with 1.5 mm.			
	groove design to be fixed to existing Wooden frame. The rate shall be inclusive of fitting and fixing of hinges,			
	1 no. Godrej make door closer, 1 no. CP finsh door			
	stopper, screws, 1 no. Godrej cylindrical lock, tower bolt			
	of approved make. All edges of the door to be covered			
	with necessary lipping with polish finish. The work			
	should be completed as per specification, design and			
	approval of Architect.			
а	Shutter size: 900 mm. x 2100 mm. with glazing size			
	600 x 1800 mm.	21.00	sq. ft.	
b	Shutter size: 900 mm. x 2100 mm. with 250 x 125			
	mm. vision panel of 6 mm. glass	170.00	sq. ft.	
5	Providing and fixing Storage Unit made out of 19 mm			
	block board (IS: 1659) for top, sides & 6 mm. for back			
	finished with 1.0mm laminate. The openable shutters to			
	be made out of 19 mm block board finished outside with			
	1.0 mm laminate (IS: 2046). The cabinet will have			
	shelves of clear ht. approx. 14". The shelves to be made of 19 mm. thk. block board. The necessary godrej			
	multipurpose locks, 4" SS matt finished handles, hinges			
	are to be provided. 4" laminated skirting to be provided.			
	Inside of the unit to be synthetic enamel painted /			
	polished in matching tone. All the exposed edges of the			
	boards/ plywoods to be covered with white beach/ white			
	ceader wooden lippings/ mouldings (6 x 20 mm.) duly			
	natural polished all complete. The work to be completed			
	as per approval and specification of the architect.			
а	Low Height Storage (upto 900 mm. high)	175.00	sq. ft.	
b	Full Height Storage (upto 2400 mm. high)	60.00		
	J	00.00	sq. ft.	

6	Providing & fixing in position 19mm thk. Blockboard			
0				
	structure, Cash Work Station of size W-1500 x D-900 x			
	H-750 mm inclusive of a 1050 mm height front partition,			
	400 mm wide customer writing top, table top,finished			
	with 1mm thk. laminate. Inside of table top finished with			
	painting / polishing. The design in the front apron as per			
	bank's design guidelines. The workstations shall be			
	supported from the partition system at both side. The			
	workstation to be comprised with a Drawer unit of			
	approx. overall size of 400 x 600 x 725 mm. (h) made			
	with 12 / 19 mm. thk. block board with telescopic drawer			
	slides. The drawer unit shall comprise of 3 drawers with			
	inner faces polished with approved shade. The drawer			
	unit shall be finished with 1 mm. laminate. The quoted			
	price should include cost of teak wood moulding to			
	edges, wood lipping, multi locks of Godrej make & other			
	necessary hardware accessories including SS handles,			
	pvc wire manager, keyboard tray, mobile CPU trolley			
	etc. of approved quality all complete as per design &			
	direction.	10.00	rft	
7	Providing & fixing 2100 mm. high Cash Work Station			
	Partition (sides & back of cash cabin) solid upto 1050			
	mm. (with electrical wire management system), above			
	solid part there will be 6 mm. thk. clear glazing upto			
	2100 mm. lev. as per design. Partition to be made of			
	aluminium hollow sections of 50mm x 50mm size 1.5mm			
	thick of JINDAL / INDAL make as internal framed			
	structure placed horizontally & vertically in 550 mm x			
	550 mm / 600mm x 600 mm center to center or as			
	directed by the Architect, double skin partition fixed to			
	aluminium frame made of 6 mm. thk. approved ply as			
	per IS:710, finished both side with approved laminate			
	with groove design complete with polishing, 4" high			
	laminated skirting etc. all complete as per design,			
	direction and approval of the Architect.	220.00	sq. ft.	
8	Providing and fixing 12 mm thk x 1050 mm. high clear		•	
	non-thoughned glass finished with machine polished of			
	all free edges above working top providing a			
	semicircular hole of 150 mm. dia. for operation, the glass			
	to be fixed to side partition using 35 x 10 mm.			
	continuous polished wooden bead at both side of the			
	glass, all complete as per design and drawing by our			
	Architects.	35.00	sq. ft.	

		1		ı	
9	Providing and fixing Gypsum false ceiling which				
	includes G.I perimeter channels of size 0.55mm thk.				
	(having one flange of 20mm and another flange of				
	30mm and a web of 27mm) along with perimeter of				
	ceiling, screw fixed to brick wall/partition with the help of				
	nylon sleeves and screws, at 610mm centres. Then				
	suspending G.I intermediate channels of size 45mm (
	0.9mm thk. with two flanges of 15mm each) from the				
	soffit at 1220mm centres with flanges of 26mm each				
	with lips of 10.5 mm are then fixed to the intermediate				
	channel with the help of connecting clip and in direction				
	perpendicular to the intermediated channel at 457mm				
	centres.12.5mm tapered edge Gypboard (confirming to				
	IS: 2095 - 1982) is then screw fixed to ceiling section				
	with 25mm drywall screws at 230mm centers. Screw				
	fixing is to be done mechanically either with screw driver				
	or drilling machine with suitable attachment. The boards				
	are to be jointed and and finished so as to have a flush				
	look which includes filling and finishing the tapered and				
	square edges of the boards with jointing compound. No				
	extra payment will be made for the cutting of light points				
	, stain glass, cove lighting etc. The measurement will be				
	taken in one level, rate should include the drops also, no				
	extra amount will be paid for the drops. The joints to be				
	properly mended with paper tapes and gypsum				
	compound. The surface to be finished with two coats of				
	distemper paint of approved shade with two coats of				
	good quality drywall primer all complete. The rate				
	should include the full completion of the ceiling. At the				
	time of handing over the site all necessary repairing				
	work to be considered if required. The work to be				
	completed as per specification, drawing and approval of				
	the Architect. No Drop or design (if any) will be				
	considered as extra measurement it will be considered		4.		
	flat ceiling.	850.00	sq. ft.		
10	Providing, fabricating and erecting lay in type tegular				
	or drop type Modular False Ceiling (ARMSTRONG				
	make - 12 mm. thk) of 600 x 600 mm. grid. The rate				
	shall include the additional cost of Tee and L supports				
	and other accessories near the ends/ odd size				
	edges/corners. Provide additional length support from				
	the ceiling to the false ceiling grid wherever necessary,				
	making necessary openings for electrical light fittings,				
	alarm detectors and any other fixtures. No extra				
	payment for making openings in the panel/grids for the				
	purpose of light fittings. Item rate shall include all the				
	taxes, transportation, erection, loading and unloading				
	and any other incidental expenditure for completing the				
	· · · · · · · · · · · · · · · · · · ·				
	work.	1300.00	sq. ft.		
10	Providing and fixing soft board/ notice board		·		
	fabricated out of 12mm BWR ply covered with 12mm				
	soft board padding and upholsply propylene fabric @80/				
	mtr. Edges of the soft board should have white				
	beach/white ceader moulding with natural polished. NB				
	: where pin up board is in a panelled area, the top of the				
	pin up board should be flushed with the panel, kepping				
	the same level. The work should be completed as per				
	design specification & approval of the architect.	24	ca ft		
	uesign specification & approval of the architect.	24	sq. ft.		l .

				<u> </u>
11	Providing & fixing synthetic door mats of approved			
	shade from Birla 3M (6mm thk). The work to be			
	completed as per approval of the Architect. (1.5 m. x			
10	0.75 m.)	2	unit	
12	Providing & erecting in position free standing table			
	made of 19 mm. thk. BWP grade block board for sides,			
	top & panel, finished with 1 mm. thk. laminate of			
	approved shade & make in outer faces. Inside of the			
	table to be finished with synthetic enamel paint / polish			
	as per matching tone. Drawer cum cabinet unit of			
	approx. overall size of 400 x 600 x 725 mm. (h) of 19			
	mm. thk. block board. The drawer unit shall comprise of			
	1 tea tray, 1 drawer, 1 cabinet with inner faces polished			
	with approved shade with telescopic drawer slides. the			
	drawer unit shall be finished with 1 mm. laminate			
	including inner faces of cabinet shutter. The quoted price			
	should include cost of teak wood moulding to edges,			
	wood lipping, multi locks of Godrej make & other			
	necessary hardware accessories including SS handles,			
	pvc wire manager, keyboard tray, mobile CPU trolley,			
	foot rest etc. of approved quality. All table should have a			
	side credenza which shall be 900 mm. long., 400 mm.			
	wide & 750 mm. high with intermidiate 1 no. shelf of 19 mm. BB. The side credenza have sliding shutters of 12			
	mm. thk. ply with 1 mm. thk. laminate finish on visible			
	side. Inside of the unit to be synthetic enamel painted /			
	polished in matching tone. All the ply edges should be			
	lipped & finished with prescribed shade of polish. The			
	rate also include the cost of hardwares like hinges, tower			
	bolts, handles, magnets, wire manager etc.			
а	size: 1800 mm. x 900 mm. x 750 mm.(h) including			
	side credenza and 10 mm. thk. Clear Float Glass at Top	1	no.	
b	size : 1500 mm. x 750 mm. x 750 mm.(h) including		110.	
b	side credenza & 10 mm. thk. Clear Float Glass at Top	_		
		5	no.	
С	size: 1500 mm. x 750 mm. x 750 mm.(h) excluding			
	side credenza & including 10 mm. thk. Clear Float Glass	0		
	at Top	2	no.	
d	size: 1200 mm. x 750 mm. x 750 mm.(h) excluding			
	side credenza & including 10 mm. thk. Clear Float Glass	2	20	
40	at Top Providing 8 Fixing fully glozed 12 mm, thk, 450 mm	3	no.	<u> </u>
13	Providing & Fixing fully glazed 12 mm. thk., 450 mm.			
	high, clear float Glass , with polished edge as directed			
	fitted in front of table top vertically with polished teak			
	wooden post (@ 1200 mm. c/c) and beading, complete	<i>1</i> 5.00	r. ft.	
14	as per design & direction. Providing & Fixing fully glazed 12 mm. clear	45.00	1.11.	
14	Toughened Glass Door with floor mounted pivotted			
	door spring hinges to shutters fitted with patch fittings &			
	floors with plate & screws including cutting holes &			
	mending good with cement mortar, with sticker design			
	bank's name, logo, bands etc. (polished edge as			
	directed) fitted with 30 mm. dia. 100 mm. X 500 mm.			
	long stainless pair of 'C' handles (both inside & outside)			
	with all accessories, floor spring complete as per design			
	& direction.	56.00	sq. ft.	
15	Providing & Fixing fully glazed 12 mm. clear Fixed	33.00	J 94. 1t.	
	Toughened Glass fixed with patch fittings & floors with			
	plate & screws including cutting holes & mending good			
	with cement mortar, with sticker design bank's name,			
	logo, bands etc. complete as per design & direction.	45.00		
	1 1 1 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	45.00	sq. ft.	<u> </u>

	T				
16	Providing & Fixing 1200 mm. x 1500 mm. high x 12				
	mm. clear Toughened Glass partition fitted to floor				
	with ss patch fittings with sticker design, bands etc. in				
	ATM (polished edge as directed) complete as per				
	design & direction.	100.00	sq.ft.		
17	Providing & fixing in position wall / column panelling		•		
	consisting of 6.0 mm thk. marine grade ply IS:710 with				
	aluminium hat furring channel 22-25 @ 500 mm. both				
	direction. The face of the cladding is to be laminated				
	with 1.0 mm. thk. laminate of approved shade & groove				
	design. The ply surface of the groove is to be melamine				
	polish finished of approved colour. The item is to be				
	completed in all respects as per design & approval of the				
	architect.	600.00	sq. ft.		
18	Providing and fixing Main Panel Encasement in				
	position fabricated out of marine grade ply (IS-710) with				
	1 mm laminate finished for top, both sides and front with				
	necessary hardware including locks, hinges and				
	handles. Encasement will be having louver and 6mm				
	thk. Glass for seeing the indicator in both shutters. The				
	exposed sorface of 19mm block board will be finished				
	with TW / white ceader lipping with natural polish and				
	inside of the encasement shall be finished with enamel				
	paint. The item is to be completed in all respect as per				
	design, specification and approval of the Architect.	50.00	sq. ft.		
19	Providing & fixing Rolling Shutters Encasement with				
	3mm thick (0.5mm + 2 mm + 0.5mm) ACP in approved				
	colours all complete with approved aluminium sub				
	structure, aluminium brackets, silicon sealants, gaskets,				
	PVDF coating in approved colour etc. all complete				
	including bird/ vermin proof closer at the bottom and				
	flashing at top, complete as per instructions & drawings.	400.00	· · ·		
		100.00	sq. ft.		
20	Providing & fixing writing ledge 900 mm. long x 300				
	mm. wide x 150 mm. deep, as per design made out of				
	19mm BWP block board with necessary groove patterns				
	1.0mm laminate. A divider made of 19mm block board to				
	be provided. White beach / white ceader lipping with				
	natural polish to be used in all exposed areas, inside of				
	writing ledge to be enamel painted. Top of ledge will be				
	of 12 mm. thk. float glass. The work to be completed as				
	per design and approval of the architect.	1	unit		
21	Providing and fixing vertical blinds of 100 mm wide		-		
	(Mac/Annums) of approved shade and pattern having				
	handail made of high strength alluminium alloyed wll				
	thickness of 1.2 mm thk handrail to have 25mm				
	decorative insert. Control unit shall be of derlin. The				
	runners are also to be a derlin withantiflixtion adeshive.				
	Spacers should be made of stainless steel. Febric				
	should be polyester viscosted/polyester yarn having				
	protective coating with chemicals for stain resistance &				
	soilrepalancy. The rate shall include necessary scoch				
	gurd treatment on both sides. The overlaping should be				
	uniform and adequate. Necessary operative				
	arrangements frames to be provided. The work to be				
	completed asper specification and approval of the				
	Architect.	200.00	sq. ft.		
	/ Horitoot.	200.00	34. 11.	l .	l

22	Providing and fixing Drop / Suggestion Box (400 x			
	600 x 150 mm.) made out of 19mm BWR Ply and			
	finished with 1 mm. laminate and enamel painted insde.			
	A 6" long slit is to be made in the front for inserting			
	letters etc. The shutter with necessary locking			
	arrangement & should have a glass panel at bottom.			
	The work should be completed in all respects as per			
	design specification & approval of the architect.	2	unit	
23	Dismantling existing partition / ceiling / table /			
	counter, any types of wooden work etc. and removing			
	the rubbish outside the compound for auctioning			
	complying local municipal rules as per direction of Bank			
	/ Architect.	1.00	unit	
	TOTAL		•	
				1

1	False Ceiling / Channels	India Gypsum / Armstrong / Saint Gobain		
2	Wood Frame Work / Wood Section : All Wood, Must be well seasoned, free from knots, other defects decay and defects due to handling and Transportation. Wherever necessary, provide with anti – termite Treatment.	Malaysian Sal / Kapoor		
3	Wood Skirting / Moulding / Lipping / Bidding	White Beach / White Ceader / CP Teak		
4	Wood Preservative	STP Pentaphene Pale / Termiseal by PCI / Bison by British Paint		
5	Fire Reterdant Paint	Industrial grads of Noble / Viper		
6	BWR Ply (IS: 710)	Century / Green /Kitply/Austin		
7	Flush Door / BWP Block board (IS : 1659)	Century / Green / Kitply/ Austin		
8	Laminate (1.0 mm thk.) (IS: 2046)	Green lam / Century / Sunmica / Airolam		
9	Door Closure (Heavy Duty)	Godrej / Archi / Sterling (DC 2000)		
10	Floor Spring (Heavy Duty)	Godrej / Archi / Sterling (FS 3000)		
11	Door Lock (Dead)	Godrej / Hafele /Hettich / Kich / Doorset / Yale		
12	Door Handles	Godrej / Hafele /Hettich / Kich / Doorset		
13	Drawer / Storage Handle	Godrej / Hafele /Hettich / Kich / Doorset		
14	Drawer / Storage Lock (Multipurpose)	Ebco / Hafele /Hettich /Doorset		
15	Night latch	Godrej / 4C Acme		
16	Screws	GKW / Nettle fold		
17	Hinges	CIEF		
18	Sliding Telescopic Drawer Channel	Ebco / Earl Behari / Efficient Gadjets		
19	Cable Organizer	Ebco / Innofitt Systems (CM 63.C)		
20	Adhesive	Fevicol SH / Fevimate TL		
21	Soft Board	Jolly Board		
22	Vertical Blinds	Mac / Annums / Window Fashion		
23	Glass	Modi /AIS / Saint Gobain		
24	Paints (Synthetic Enamel / Acrylic Emulsion)	Asain Paints / Berger / ICI		
25	PVC Flooring	Krishna Vinyl / Armstrong / Birla		
26	Texture Paint	Spectrum		
27	Glass	Modi / AIS / Saint Gobain		
28	European WC / Washbasin	Hindware /Parryware		
29	Sanitary Fittings	Jaquar / Essco Delux		
30	G.I. Pipe	Tata (Medium)		
31	Cement	Ultratech / Laferge / ACC		
32	Footmat	Birla 3M / Approved Equivalent		
33	Vitrified Tiles	Johnson / Nitco / Kajaria		
34	Ceramic Tiles	Johnson / Nitco / Kajaria		
36	All other items not covered above	As per sample approved by Employer/Consultant		

CANARA BANK # ENTALLY BRANCH & ATM # KOLKATA CIRCLE B O Q FOR CIVIL WORKS

Description Of Item	Qnty.	Unit	Rate (Rs.)	Amount (Rs.)
Dismantling existing Wall/Floor Tiles, any types of massonary work, wooden door & windows, cooking counter, sanitary fittings, water line etc. and removing the rubbish outside the compound complying local municipal rules as per direction of Bank / Architect.				
floor tiles/stone	265	sq. ft.		
wall tiles	580			
existing plaster	750			
door (toilet, pantry)	5.00	unit		
existing ALL bathroom fittings	2.00	unit		
existing ALL water supply lines & fittings	2.00			
15 mm. thk. Plastering with sand and cement mortar including rounding off or chamfering corners as directed and raking out joints or roughening of concrete surface, including throating, noising and drip course where necessary. With 6:1 sand-cement mortar. including cost of scaffolding etc.	750			
Applying white cement based wall putty (1.5 mm. thk.)				
Priming two coats on plastered surface with acrylic oil bound primer of approved quality including smoothening surfaces by sand papering etc.				
Wall painting with Plastic Emulsion Paint , having VOC (Volatile Organic Compound) content less than 50 grams/litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour.	3333.53	94		
Two coats	9000.00	sa. ft.		
Priming two coats on timber, steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. complete as directed.	1200.00			
Painting on all types of Metal surface with Synthetic Enamel Paint of approved brand and manufacture of required colour to give an even shade		·		
Two or more coats	1200.00	sq. ft.		
Supplying and laying true to line and level double charge Vitrified Tiles of approved brand conforming to IS 15622: 2006 (Group B I a) and tested as per IS 13630:2006 (relevant parts) [Non-modular sizes for tiles with Water absorption (av.) ≤ 0.08 %] in floor, skirting etc. using polymerised adhesive of 6mm thick layer applied directly over finished artificial stone floor/Mosaic etc. without any backing course and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials,labour and all other incidental charges complete as per direction of Architect. (Base price for Tile : Rs. 55.00-60.00 per sq.ft.)				
	massonary work, wooden door & windows, cooking counter, sanitary fittings, water line etc. and removing the rubbish outside the compound complying local municipal rules as per direction of Bank / Architect. floor tiles/stone wall tiles existing plaster door (toilet, pantry) existing ALL bathroom fittings existing ALL water supply lines & fittings 15 mm. thk. Plastering with sand and cement mortar including rounding off or chamfering corners as directed and raking out joints or roughening of concrete surface, including throating, noising and drip course where necessary. With 6:1 sand-cement mortar. including cost of scaffolding etc. Applying white cement based wall putty (1.5 mm. thk.) to new plastered surface. Priming two coats on plastered surface with acrylic oil bound primer of approved quality including smoothening surfaces by sand papering etc. Wall painting with Plastic Emulsion Paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. Two coats Priming two coats on timber, steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. complete as directed. Painting on all types of Metal surface with Synthetic Enamel Paint of approved brand and manufacture of required colour to give an even shade Two or more coats Supplying and laying true to line and level double charge Vitrified Tiles of approved brand conforming to IS 15622: 2006 (Group B I a) and tested as per IS 13630:2006 (relevant parts) [Non-modular sizes for tiles with Water absorption (av.) ≤ 0.08 %] in floor, skirting etc. using polymerised adhesive of 6mm thick layer applied directly over finished artificial stone floor/Mosaic etc. without any backing course and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and all other incidental charges complete	massonary work, wooden door & windows, cooking counter, sanitary fittings, water line etc. and removing the rubbish outside the compound complying local municipal rules as per direction of Bank / Architect. floor tiles/stone 265 wall tiles existing plaster door (toilet, pantry) existing ALL bathroom fittings existing ALL bathroom fittings existing ALL water supply lines & fittings 15 mm. thk. Plastering with sand and cement mortar including rounding off or chamfering corners as directed and raking out joints or roughening of concrete surface, including throating, noising and drip course where necessary. With 6:1 sand-cement mortar. including cost of scaffolding etc. Applying white cement based wall putty (1.5 mm. thk.) to new plastered surface. Priming two coats on plastered surface with acrylic oil bound primer of approved quality including smoothening surfaces by sand papering etc. Wall painting with Plastic Emulsion Paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. Two coats Priming two coats on timber, steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. complete as directed. Painting on all types of Metal surface with Synthetic Enamel Paint of approved brand and manufacture of required colour to give an even shade Two or more coats Supplying and laying true to line and level double charge Vitrified Tiles of approved brand conforming to IS 15622: 2006 (Group B I a) and tested as per IS 13630:2006 (relevant parts) [Non-modular sizes for tiles with Water absorption (av.) ≤ 0.08 %] in floor, skirting etc. using polymerised adhesive of 6mm thick layer applied directly over finished artificial stone floor/Mosaic etc. without any backing course and polishing the tiles using soft and dry cloth upto mirror finish complete including the cost of materials, labour and	massonary work, wooden door & windows, cooking counter, sanitary fittings, water line etc. and removing the rubbish outside the compound complying local municipal rules as per direction of Bank / Architect. floor tiles/stone ### wall tiles ### sanitary ### cook (toilet, pantry) ### existing plaster ### door (toilet, pantry) ### existing ALL bathroom fittings ### existing ALL water supply lines & fittings ### fittings ### 15 mm. thk. Plastering with sand and cement mortar including rounding off or chamfering corners as directed and raking out joints or roughening of concrete surface, including throating, noising and drip course where necessary. With 6:1 sand-cement mortar. including cost of scaffolding etc. #### Applying white cement based wall putty (1.5 mm. thk.) to new plastered surface. #### priming two coats on plastered surface with acrylic oil bound primer of approved quality including smoothening surfaces by sand papering etc. #### Wall painting with Plastic Emulsion Paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. ##### Priming two coats on timber, steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. #### Priming two coats on timber, steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. ##### Priming two coats on timber, steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. #### Priming two coats on timber, steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. #### Priming two coats on timber, steel or other metal #### Priming two coats on timber, steel or other metal #### Priming two coats on timber, steel or oth	Dismantling existing Wall/Floor Tiles, any types of massonary work, wooden door & windows, cooking counter, sanitary fittings, water line etc. and removing the rubbish outside the compound complying local municipal rules as per direction of Bank / Architect. floor tiles/stone wall tiles existing plaster door (toilet, pantry) existing ALL bathroom fittings existing ALL bathroom fittings existing ALL water supply lines & fittings 15 mm, thk, Plastering with sand and cement mortar including rounding off or chamfering corners as directed and raking out joints or roughening of concrete surface, including throating, noising and drip course where necessary. With 6:1 sand-cement mortar, including cost of scaffolding etc. Applying white cement based wall putty (1.5 mm, thk.) to new plastered surface. Priming two coats on plastered surface with acrylic oil bound primer of approved quality including smoothening surfaces by sand papering etc. Wall painting with Plastic Emulsion Paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. Two coats Priming two coats on timber, steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. Two coats Priming two coats on timber, steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. Two coats Priming two coats on timber, steel or other metal surface with synthetic oil bound primer of approved quality including smoothening surfaces by sand papering etc. Troo or more coats Supplying and laying true to line and level double charge Vitrified Tiles of approved brand conforming to IS 15622: 2006 (Group B I) and tested as per IS 1200.00 sq. ft. Painting on all types of Metal surface with Synthetic enamel Paint of approved brand conforming to IS 15622: 2006 (Group B I) and t

9	Providing and fixing Ist quality Ceramic Glazed / matt Wall/ floor tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. (Location: Toilet)			
а	Wall tiles: 450 x 300 mm.	580	sq.ft	
b	floor Tiles: 300 x 300 mm	265	sq.ft	
10	Black Stone Slabs 20 mm thick in structure of cooking platform laid on 12 mm (average) thick cement mortar 1: 4 (1 cement: 4 coarse sand) and jointed with grey cement slurry/adhesive mixed with pigment to match the shade of the slabs, including rubbing and polishing complete. (Location: Kitchen)	60.00	sq.ft	
11	Granite slabs (Sadar Ali / Galaxy) 15-18 mm thick in	50.00	54.11	
	cooking platform laid on 12 mm (average) thick cement mortar 1:3 (1 cement: 3 coarse sand) and jointed with grey cement slurry mixed with pigment to match the shade of the slabs, including rubbing, moulding and polishing complete. (Location: Kitchen)	40.00	og ft	
12	Marble slabs (Doongri) 15-18 mm thick in stair case (40.00	sq.ft	
	lobby, landing, trades, riser, skirting etc.) laid on 12 mm (average) thick cement mortar 1:3 (1 cement: 3 coarse sand) and jointed with grey cement slurry mixed with pigment to match the shade of the slabs, including moulding, rubbing and polishing complete. (Location: Stair) All tread should have 3 nos. anti-slippery groove along the width of the stair with 15 mm. nosing			
	along the width of the stall with 13 mm. hosing	225.00	sq.ft	
13	Supplying, fitting, fixing 40 mm. dia. SS (grade 304) handrail for staircase fixed to side walls	45.00		
14	30 mm thick factory made Poly Vinyl Chloride (PVC)	45.00	r.ft.	
	door shutter made of styles and rails of a UPVC hollow section of size 60 x 30 mm and wall thickness 2 mm (± 0.2 mm), with inbuilt decorative moulding edging on one side. The styles and rails mitred and joint at the corners by means of M.S. galvanised/ plastic brackets of size 75 x 220 mm having wall thickness 1.0 mm and stainless steel screws. The styles of the shutter reinforced by inserting galvanised M.S. tube of size 25x20 mm and 1 mm (± 0.1 mm) wall thickness. The lock rail made up of 'H' section, a uPVC hollow section of size 100x30 mm and 2 mm (± 0.2 mm) wall thickness fixed to the shutter styles by means of plastic/galvanised M.S. 'U' cleats. The shutter frame filled with a uPVC multi-chambered single panel of size not less than 620 mm, having over all thickness of 20 mm and 1 mm (± 0.1 mm) wall thickness. The panels filled vertically and tie bar at two places by inserting horizontally 6 mm galvanised M.S. rod and fastened with nuts and washers, complete as per manufacturer's specification and direction of Engineer-in-charge.	400.000		
		120.000	sq.ft	

15	Providing and fixing Wash Basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require			
а	White Vitreous China Wash basin size 630 x 450 mm	2	Nos.	
16	Supplying, fitting and fixing Flat back urinal (half stall urinal) in white vitreous chinaware of approved make in position with c.p. stop cock, connecting pipe, pvc waste and outlet pipe, brass screws on 75 mm X 75 mm wooden blocks complete as directed by Architect.	2	each	
17	Supplying, fitting and fixing Squating plate with integral flushing in white vitreous chinaware of approved make in cement concrete (6:3:1) with jhama chips complete. (size: 450 x 350 mm.).	1	Nos.	
18	Providing and fixing Stainless Steel A ISI 304 (18/8) Kitchen Sink as per IS: 13983 with C.I. brackets and stainless steel plug 40 mm, including painting of fittings and brackets, cutting and making good the walls wherever required			
а	610 x 510 mm bowl depth 200 mm	1	Nos.	
19	Providing and fixing white vitreous china pedestal type (European type) Water Closet . [Base Price : 1050.00 - 1100.00]	2	Nos.	
20	Providing and fixing P.V.C. low Level Flushing Cistern with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete. [<i>Base Price: 850.00 - 900.00</i>]			
а	10 litre (full flush) capacity-white	2	Nos.	
21	Providing and fixing Solid Plastic Seat with lid for pedestal type W.C. complete. [<i>Base Price : 400.00 - 450.00</i>]			
а	White solid plastic seat with lid	2	Nos.	
22	Providing and fixing P.V.C. Waste Pipe for sink or wash basin including P.V.C. waste fittings complete.			
а	32 mm dia	3	Nos.	
23	Providing and fixing Mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing. [Base Price: 450.00 - 500.00]			
а	Rectangular shape 453 x 357 mm	2	Nos.	
24	Providing and fixing Chlorinated Poly Vinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge.			
	Concealed work, including cutting chases and making good the walls etc.			
а	20 mm nominal outer dia Pipes	100.00	r.ft.	
b	40 mm nominal outer dia Pipes	35.00	r.ft.	

25	Supplying, fitting & fixing new PVC pipes (110 mm. dia.) including all specials (bend, tee, etc.) in wall by PVC clamp using rawl plug and screw in wall etc. complete in all respect.	15.00	r.ft.	
26	Providing and fixing unplasticised P.V.C. connection pipe with PTMT Nuts, collar and bush of approved quality and colour.			
а	15 mm nominal bore with 45 cm length	6	Nos.	
27	Supplying, Fittings & fixing different size high/low pressure CPVC Ball Valve of approve quality.			
а	20 mm.	3	Nos.	
28	Providing and fixing C.P. Angle Stop Cock of approved quality.			
	15 mm nominal bore	6	Nos.	
29	Providing and fixing C.P. Bib Cock of approved quality.			
	15 mm nominal bore	4	Nos.	
30	Providing and fixing C.P. Long Body Bib Cock of approved quality.			
	15 mm nominal bore	2	Nos.	
31	Providing and fixing C.P. Sink Cock of approved quality.			
	15 mm nominal bore	1	Nos.	
32	Providing and fixing 2 in 1 bib Cock including commode shower of approved quality.			
	15 mm nominal bore	2	Nos.	
33	Providing and fixing SS Liquid Soap Container 109 mm wide, 125 mm high and 112 mm distance from wall of standard shape with bracket of the same materials with snap fittings of approved quality and colour, weighing not less than 105 gms.	2	Nos.	
34	Providing and fixing SS Towel Ring trapezoidal shape 215 mm long, 200 mm wide with minimum distances of 37 mm from wall face with concealed fittings arrangement of approved quality and colour, weighing not less than 88 gms.	2	Nos.	
	yınə.		1105.	
	TOTAL			

APPROVED MAKE OF MATERIALS			
1	Paints (Synthetic Enamel / Acrylic Emulsion)	Asain Paints / Berger / Dulux	
2	Cement	Ultratech / Laferge / ACC	
3	MS ANGLE / FLAT / SQ. BAR	TATA / JINDAL / RINL	
4	Reinforcement Bar	SAIL/ TATA/ RINL	
5	Construction Chemicals	Sika / Pidilite	
6	UPVC / CPVC Pipes	Supreme / Astral	
7	Vitrified Tiles	Johnson / Kajaria	
8	Ceramic Tiles	Johnson / Kajaria	

CANARA BANK # ENTALLY BRANCH & ATM # KOLKATA CIRCLE B O Q FOR ELECTRICAL WORKS

SI No.	Description Of Item	Qnty.	Unit	Rate (Rs.)	Amount (Rs.)
1	MAIN INCOMING SFU	•	•	• •	
	S/I/T/Commissioning of 125 Amp. TPN Main Switch (HRC type SFU) at main incoming from CESC / SEB to be fixed on MS angle framework & 2 nos. cable end box including necessary interconnections	1	unit		
2	MAIN PANEL BOARD		3 1111		
	S/I/T/Commissioning of Main Distribution Panel as per given below: - 440 Volts AC, 3 Phase, 50 Hz with 50 KA fault level for 1 second, Floor / Wall mounted, 7 tank cleaning process with duly powder coated with copper bus bar. 125 Amps 4P MCCB of 35 KA breaking capacity - 1 nos., 63 Amps 4P MCCB - 1 no. (interlocking for DG supply) with LED type phase indicating lamp, Digital voltmeter, Ammeter with selector switch with required CT unit, Danger Notice Board indicating sign (DANGER) in English, Hindi, Bengali. Outgoing: 63/40 Amps TPN MCB - 3 Nos., 40 Amps DP MCB - 4 Nos., 63 Amp TPN Changeover-1 No., 125 Amp TPN Bus bar Chamber-1 No.	1	unit		
3	UPS INPUT/ OUTPUT	'	dilit		
	63 Amps/40 Amps 4P MCB in MS enclosure box	6.00	unit		
4	DISTRIBUTION BOARDS (All MCBs to be "C" series) (All connections to be through Cu socket)				
а	Providing and fixing 12 way SPN double door UPS DB with incomer 1 no. 40 Amps DP MCB controlling 10 nos. 16/10 Amp SP MCB Complete.	3.00	unit		
b	Providing and fixing 12 way SPN double door LIGHT DB for LIGHT POINTS with incomer 1 no. 25 Amps DP RCBO controlling 10 Nos. 6/10 Amp SPMCB Complete.	3.00	unit		
С	Providing and fixing 4 way TPN double door AC DB for A.C. POINTS with incomer 1 no. 63 Amps 4P MCB controlling 12 no. 10/16 Amp SPMCB, keeping other space as spare Complete.	1.00	unit		
d	Providing and fixing 4 way TPN double door POWER DB for RAW POWER POINTS with incomer 1 no. 40 Amps 4P MCB controlling 12 no. 16/10 Amp SPMCB Complete.	2.00	unit		
е	Providing and fixing 63 Amps TPN Isolator with Cut Out DB (For Master Switch controlling light, AC, power point etc. excluding UPS distribution) near Branch entrance location.	1	unit		
5	CABLES	•	dint		
а	Providing and placing in position, testing and connecting 1.1 KV grade XLPE Al armoured cable 3.5-C x 50 sq. mm. with 2 Nos 10 swg GI ECC by GI bar and saddles on wall/floorpass. Cable to be for Main switch to Main Panel Including all necessary terminals etc. complete.	30.00	r. m.		

		,		T	1
b	Providing and placing in position, testing and connecting 1.1 KV grade Cu cable 4-C x 25 sq. mm. with 2 Nos 10 swg GI ECC by GI bar and saddles on wall/floorpass. Cable to be for DG to Main Panel Including all necessary terminals etc. complete.				
	oto. complete.	30.00	r. m.		
С	Providing and laying 4 x 6 sq. mm. & 2 x 4 sq. mm. FR PVC coated copper conductors (1.1 KV grade) in pvc rigid pipe/capping-casing on surface of wall duly clamping with necessary fittings and accessories from Main DB to AC DB. Including all necessary terminals etc. complete.	25.00	r. m.		
4		20.00	1. 111.		
d	Providing and laying 4 x 6 sq. mm. & 2 x 4 sq. mm. FR PVC coated copper conductors (1.1 KV grade) in pvc rigid pipe/capping-casing on surface of wall duly clamping with necessary fittings and accessories from Main DB to UPS Input and UPS Output to UPS DB. Including all necessary terminals etc. complete.	80.00	r. m.		
е	Providing and laying 4 x 6 sq. mm. & 2 x 2.5 sq. mm. FR PVC coated copper conductors (1.1 KV grade) in pvc rigid pipe/capping-casing on surface of wall duly clamping with necessary fittings and accessories from Main DB to POWER DB. Including all necessary terminals etc. complete.	60.00			
	Don't in a self in O. O. a. a. a. O. A. A. F. a. a. a. FD.	60.00	r. m.		
f	Providing and laying 2 x 6 sq. mm. & 1 x 1.5 sq. mm. FR PVC coated copper conductors (1.1 KV grade) in pvc rigid pipe/capping-casing on surface of wall duly clamping with necessary fittings and accessories from Main DB to LIGHT DB. Including all necessary terminals etc. complete.	75.00	r. m.		
g	Providing and laying 2 x 2.5 sq. mm. & 1 x 1.5 sq. mm. FR PVC coated copper conductors (1.1 KV grade) in pvc rigid pipe/capping-casing on surface of wall duly clamping with necessary fittings and accessories from <u>LIGHT DB to SWITCH BOARDS</u> . Including all necessary terminals etc. complete.				
	Complete.	150.00	r. m.		
h	Providing and laying 2 x 2.5 Sq mm. & 1 x 1.5 sq. mm. FR PVC insulated multi stranded copper wire in suitable size pvc rigid pipe/capping-casing on surface of wall duly clamping with necessary fittings and accessories for UPS DB To Computers . Including all necessary terminals etc. complete.	300.00	r. m.		
i	Providing and laying 2 x 4 Sq mm. & 1 x 1.5 sq. mm. FR PVC insulated multi stranded copper wire in suitable size pvc rigid pipe/capping-casing on surface of wall duly clamping with necessary fittings and accessories for AC DB To Starters/Outdoor Units & DB To Glow Sign Board.				
	Including all necessary terminals etc. complete.	225.00	r. m.		
6	POINT WIRING				
a	Providing & fixing POINT WIRING for Ceiling and wall lights. Point wiring to be laid with 2 x 1.5 sq. mm. + 1 x 1.0 sq.mm. PVC insulated copper conductor with all necessary accessories, such as saddles etc. on surface or embedded in wall, chasing the walls and making the surface neat afterwards. The item includes modular switch 6 Amp with all base plates & cover plates, M.S. box of same make etc. 3 plate ceiling rose to be provided for Exhaust fans complete. (one point to be controlled by one switch)	80.00	unit		
	<u> </u>	- 0.00	<i>~</i> ····•	l .	L

b	Same as above But 2 points to be controlled by 1	1		[
	switch	30.00	unit		
С	Providing and fixing power point for Wall / Exhaust Fan				
	points with 1 x 2 pin 6 Amp socket outlet to be provided at the location of fan	25.00	umit		
d	Providing & fixing Raw Power Point Includes 1 nos. 5 pin	25.00	unit		
	6 AMP socket and 1 no 6 Amp switch etc. complete.	30.00	unit		
е	Providing & fixing Raw Power Point Includes 1 nos. 5 pin	30.00	unit		
	5/15 AMP socket and 1 no 15 Amp switch etc. complete.	4.00	unit		
f	Providing & fixing Computer Plug Points with 3 Nos 5 pin	4.00	dille		
	6 Amp sockets,1 Nos 6 amp switch & one indicator lamp, complete with all necessary accessories. The switch and				
	indicator to be located above the counter while sockets to				
	be fixed below the counter.	20.00	unit		
g	Providing and fixing BELL POINTS on wall / partition with	20.00	dille		
	2 x1.0 sq. mm. copper conductor with call bell switch (Push				
	Type) including ANCHOR call bell TRESSA Multi Tune Bell complete.	4.00			
h	Providing and fixing Starter for AC consisting of 15 Amp.	1.00	unit		
	Socket for plug, 12-18 Amp. Starter (socket to provide near				
	indoor unit)	12.00	unit		
i	Providing and fixing AC timer controlling thro. separate 16 Amp. DP MCB with metal enclosure complete.	1.00	unit		
j	Providing and fixing Glow Sign Board point with timer	1.00	unit		
	controlling thro. separate 16 Amp. DP MCB with metal				
	enclosure complete.	2.00	unit		
_	EARTHING				
7	EARTHING Farthing installations as par I F, rules by making earth				
7 a	EARTHING Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement.				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation should be provided with 300 mm x 300 mm and 300 mm				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation should be provided with 300 mm x 300 mm and 300 mm depth inside dimension masonry inspection pit with C.I. hinged cover having locking arrangements, test link of size				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation should be provided with 300 mm x 300 mm and 300 mm depth inside dimension masonry inspection pit with C.I. hinged cover having locking arrangements, test link of size 150 mm length x 25 mm x 6 mm copper flat connected to				
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation should be provided with 300 mm x 300 mm and 300 mm depth inside dimension masonry inspection pit with C.I. hinged cover having locking arrangements, test link of size	1.00	unit		
-	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation should be provided with 300 mm x 300 mm and 300 mm depth inside dimension masonry inspection pit with C.I. hinged cover having locking arrangements, test link of size 150 mm length x 25 mm x 6 mm copper flat connected to copper earth lead-in-strip and restoring the surfaces duly rammed. Providing and fixing Pipe Earthing (IS 3043 Code) 3.0m.	1.00	unit		
a	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation should be provided with 300 mm x 300 mm and 300 mm depth inside dimension masonry inspection pit with C.I. hinged cover having locking arrangements, test link of size 150 mm length x 25 mm x 6 mm copper flat connected to copper earth lead-in-strip and restoring the surfaces duly rammed. Providing and fixing Pipe Earthing (IS 3043 Code) 3.0m. deep with 40 mm. dia. GI pipe With perforations filled with	1.00	unit		
a	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation should be provided with 300 mm x 300 mm and 300 mm depth inside dimension masonry inspection pit with C.I. hinged cover having locking arrangements, test link of size 150 mm length x 25 mm x 6 mm copper flat connected to copper earth lead-in-strip and restoring the surfaces duly rammed. Providing and fixing Pipe Earthing (IS 3043 Code) 3.0m. deep with 40 mm. dia. GI pipe With perforations filled with alternate layers of Charcoal and salt. The item includes Funnel on top in brick masonary chamber with CI cover for	1.00	unit		
a	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation should be provided with 300 mm x 300 mm and 300 mm depth inside dimension masonry inspection pit with C.I. hinged cover having locking arrangements, test link of size 150 mm length x 25 mm x 6 mm copper flat connected to copper earth lead-in-strip and restoring the surfaces duly rammed. Providing and fixing Pipe Earthing (IS 3043 Code) 3.0m. deep with 40 mm. dia. GI pipe With perforations filled with alternate layers of Charcoal and salt. The item includes	1.00	unit		
a	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation should be provided with 300 mm x 300 mm and 300 mm depth inside dimension masonry inspection pit with C.I. hinged cover having locking arrangements, test link of size 150 mm length x 25 mm x 6 mm copper flat connected to copper earth lead-in-strip and restoring the surfaces duly rammed. Providing and fixing Pipe Earthing (IS 3043 Code) 3.0m. deep with 40 mm. dia. GI pipe With perforations filled with alternate layers of Charcoal and salt. The item includes Funnel on top in brick masonary chamber with CI cover for watering purpose complete.				
b	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation should be provided with 300 mm x 300 mm and 300 mm depth inside dimension masonry inspection pit with C.I. hinged cover having locking arrangements, test link of size 150 mm length x 25 mm x 6 mm copper flat connected to copper earth lead-in-strip and restoring the surfaces duly rammed. Providing and fixing Pipe Earthing (IS 3043 Code) 3.0m. deep with 40 mm. dia. GI pipe With perforations filled with alternate layers of Charcoal and salt. The item includes Funnel on top in brick masonary chamber with CI cover for watering purpose complete. Providing and fixing Copper Earth Wire 8 guage in pvc conduit in Floor / walls From earth pit to earthing station &	2.00	unit		
b	Earthing installations as per I.E. rules by making earth stations with 600 mm x 600 mm x 6.0 mm. thick copper plate electrode to be installed such that its top edge shall be at a minimum depth. of 3.0 meter below ground level after preparation of ground with charcoal and salt and connecting the MIP with 25 mm x 6 mm G.I. earth lead-in-strip directly in ground by bolting and then brazing to the copper Plate complete with G.I. bolts of suitable length double nuts and washers including supply and fixing of 50 mm dia. partly perforated G.I. pipe with funnel for watering arrangement. 3.0 m. long with 300 x 300 mm. casting plate connection to be fitted with bitumen, the electrode to be driven under G. L. to an av. depth of 3.15 m. The earthing installation should be provided with 300 mm x 300 mm and 300 mm depth inside dimension masonry inspection pit with C.I. hinged cover having locking arrangements, test link of size 150 mm length x 25 mm x 6 mm copper flat connected to copper earth lead-in-strip and restoring the surfaces duly rammed. Providing and fixing Pipe Earthing (IS 3043 Code) 3.0m. deep with 40 mm. dia. GI pipe With perforations filled with alternate layers of Charcoal and salt. The item includes Funnel on top in brick masonary chamber with CI cover for watering purpose complete.				

а	Supplying, Installation, Testing & Commissioning of 10 pair 0.51 sq. mm. telephone unarmoured cable in 20 mm PVC pipe. (Make - Finolex / Havells / Polycab)	60.00	r. m.	
b	S/I/T/Commissioning of Telephone point with 1 No. of RJ- 11 socket, 1 Module Plate & Modular Box as per instructions of the Architect.	4.00	unit	
С	S/I/T/Commissioning of telephone Junction box 10 pair krone type housed in MS box with Lock & key.	1.00	unit	
9	ELECTRICAL FIXTURES			
	Item includes supplying, assembling, fixing, testing & commissioning Following Fixtures including all accessories, lamps & extension chords as maybe necessary complete. All LED / Flurescent fixtures (except down lighters) to be hung from the RCC ceiling by 20 KG grade adjustable GI chain & in NON False ceiling area they are to be hung by appropriate Down Rods.			
а	Providing and Fixing Recessed mounted diffused optics high performance 2' X 2' LED luminaire with necessary LED lamp (34W LED 6000K) or similar	35.00	unit	
b	Providing and Fixing Recessed mounted LED spot light with necessary LED lamp (15W LED 6000K) or similar. (Ceiling cutout ø 155 mm.)	60.00	unit	
С	Providing and Fixing Surface mounted 4' long luminaire suitable for Lamp type 18W LED (T5) or similar	38.00	unit	
d	Providing and Fixing wall mounted fans 400 mm. sweep	18.00	unit	
е	Providing and Fixing ceiling fans 1200 mm. sweep including 600 v electronic regulator	7.00	unit	
f	Supplying & Fixing of exhaust fan heavy duty industrial type 225 mm sweep with 1400 RPM.	4.00	unit	
10	Dismantling existing wiring / DB / light fittings / fan, any types of electrical work etc. and removing the rubbish outside the compound for auctioning complying local municipal rules as per direction of Bank / Architect.	1.00	unit	
	TOTAL (C)			

APPROVED MA	AKE OF MATERIALS	
1	Switch fuse units (HRC)	LEGRAND / INDO-ASIAN / HAVELLS
2	Timer (TSQ 100)	L & T / HAVELLS
3	Voltmeter & Ammeter	A. E. / IMP
4	Voltmeter & Ammeter selector switches	KAYCEE / L & T
5	Phase indicating lamp	Vaishno / SIEMENS / ROSS controls
6	Capacitor	CROMPTON/SIEMENS
7	HRC fuses	GE power / SIEMENS / L & T / SCHNEIDER
8	Power Cable : XLPE	GLOSTER/POLYCAB/HAVELLS / NICCO
9	HRC fuse base & carriers.	GE power / SIEMENS / L & T / SCHNEIDER
10	1.1 KV grade PVC insulated armoured aluminium cable (ISI marked)	GLOSTER / NATIONAL / NICCO / HAVELLS
11	1.1KV / 600V grade PVC insulated & sheathed / insulated copper wire & flexible cords (ISI marked).	FINOLEX / HAVELLS
12	RCCB / ELCB / MCCB	LEGRAND / INDO-ASIAN / HAVELLS

13	Moulded case circuit breaker	LEGRAND / INDO-ASIAN / HAVELLS
14	RCCB / ELCB	LEGRAND / INDO-ASIAN / HAVELLS
15	Switch fuse with rewirable fuses. (6A & 32A TPN)	LEGRAND / INDO-ASIAN / HAVELLS
16	Isolator	LEGRAND / INDO-ASIAN / HAVELLS
17	Changeover switch (on load type)	LEGRAND / INDO-ASIAN / HAVELLS
18	MCB distribution board	LEGRAND / INDO-ASIAN / HAVELLS
19	6/16 Amp modular type switch / flushed type plug socket	ANCHOR (Roma) / CRABTREE / INDO- ASIAN
20	6/16 Amp modular switch / socket, module plate & mounting M.S. / PVC box.	ANCHOR (Roma) / CRABTREE / INDO- ASIAN
21	16/25 Amp., 2 module electronic regulator	ANCHOR (Roma) / CRABTREE / INDO- ASIAN
22	Ceiling rose	KAY / EPP / ANCHOR / JJ
23	Holder	KAY / EPP / ANCHOR / JJ
24	Alarm bell	KHERAJ / GETCO
25	Black enamelled Steel conduits (conforming to IS in all respects)	BEC / SUPREME / AKG
26	Compression type brass gland	DOWELLS / JOHNSON / COMET
27	Cable termination socket	DOWELL'S
28	Light fitting & lamps	PHILLIPS / HAVELLS
29	Ceiling / Wall Mounted Fan	CROMPTON / POLAR / KHAITAN / HAVELL'S
30	Exhaust fan	CROMPTON / POLAR / KHAITAN / HAVELL'S
31	Industrial type socket & top	HAVELL'S / CROMPTON / LEGRAND
32	Telephone wire	FINOLEX / RRK/NATIONAL
33	Starters	NORTH WEST / CABTREE
34	All other items not covered above	As per sample approved by Employer/Consultant

SI. No.	Description	Amount Quoted
1	Furnishing Work (A)	
2	Civil Work (B)	
3	Electrical Work(C)	
4	Net Total (A+B+C)	
5	Discount if any	
6	Net Total After Discount	
7	GST	
8	Total inclusive of GST	

Note: Lowest Bidder will be the lowest of SI No. 6 i.e. Net Total After Discount