

FURNITURE & FURNISHING WORK OF CANARA BANK, EXTENSION OF CIRCLE OFFICE, JAIPUR

ANNEXURE 1(A) : Furnishing work

S.No	ITEM	QTY.	UNIT	RATE	AMOUNT Excluding GST
1	<u>LOW HEIGHT PARTITION (1350 mm high)</u>				
	Providing & fixing partition, made of 50 x 50mm kailwood frame @ 600mm c/c both ways at floor level with anti-termite paint, fixed rigidly to floor 9 mm thick Comm. Ply of approved make & shade with 1mm thick laminate of approved quality and shade shall be fixed on both faces of partition as per design with groove with necessary openings for glass at 900 mm ht. These openings shall be covered by 12 mm thick etched Toughened glass fixed with wooden beading. All exposed edge of the glass shall be ground polished. Skirting shall be 100 mm high with 1mm laminate. All exposed teak surfaces shall be finished with wood polish.	76	sqm.		
2	<u>LAMINATED / GLAZED PARTITION</u>				
	providing & fixing of partly glazed partition made of 50x50mm kailwood frame @ 600mm c/c both ways with anti-termite paint, fixed rigidly at floor level as well as ceiling bottom, 9 mm thick Comm. Ply of approved make with 1mm laminate of approved quality and shade shall be fixed on both faces of partition with necessary openings for the glass as per design with groove. Skirting of teak wood shall be 100 mm high and finished with 1mm approved make laminate. The grooves are to be filled with matching polish. The item includes door shutter of size 900 x 2100 mm made of 75x25mm kail wood frame @ 300-4--mm c/c both ways painted with anti-termite paint with 9 mm thick comm. ply on both faces finished with 1mm thick laminate of approved quality and shade with necessary openings for glass. There shall be TW edging with 40x20mm TW section on all edges of shutter (all around) with TW door frame (chowkhat) out of 75x50 mm section. The partition & door to be provided with 1200 mm high 12mm thick toughened etched glass of approved make & shall be fixed at 900mm height from FF level fixed with 20x35 mm TW beading in place of commercial plywood & laminate. All exposed teak wood surfaces shall be finished with approved colour polish. The Item includes necessary hardware such as powder coated hinges, door closer tower bolts, door stopper, 2 lever (godrej) lock with 1 nos 6" long powder coated. All handle of approved quality and design. All exposed teak wood surfaces shall be finished with approved colour polish. The rate includes making provision for electrical conduits, switch and junction boxes.	118	sqm.		
3	<u>CUPBOARD (low Height /full height)</u>				
	Providing & fixing 450 mm deep cupboards/ storage units with sides, Top, bottom, shutters, partitions & shelves made of 19mm thick commercial board of approved quality and make. The partitions shall be spaced at a maximum spacing of 810 mm C/C and shelves shall be spaced at 450mm C/C The width of each shutter shall not exceed 450mm. The back shall be made of 6mm comm. ply duly painted with anti-termite paint (on outer face). The front shutter and exposed sides shall be finished with TW laminate (in two shades) of approved quality & shade as per design with groove. The exposed edges of the board shall have teak wood liping. Skirting shall be 100mm high & made of 19mm thick commercial board finished with 1mm laminate. top of cupboard will finished with 1mm thk laminate The rate includes necessary powder coated hardware such as piano hinges, tower bolts, brass dead locks, magnet catchers, 4" long aluminium handle of approved design. All fixtures shall be powder coated. All inner surfaces shall be painted with two or more coats of enamel paint over a coat of primer including sand papering, filling and preparation of surface. All exposed teak surfaces shall be finished with wood polish.	37	sqm		
4	<u>FALSE CEILING (Gypsum Board)</u>				
	Providing & fixing false ceiling as per design consist of GI frame, which includes perimeter channels alongwith the parameter of ceiling, with intermediate channel of size 45mmx0.9mm thick with two flange of 15mm each @ 1220mm c/c with ceiling angle of size 25x10x0.5mm fixed to the bottom of the ceiling with GI cleat & steel expansion fastener, ceiling section of 0.55mm thick with knurled web of 51.5mm & two flanges of 26mm each with lips of 10.5mm are then fixed to the intermediate channel with connecting clips and direction perpendicular to the intermediate channel at 457mm c/c, 12.5mm thick gypsum board shall be fixed with screw with filling & finishing the tapered edge with jointing compound, paper tape and painted with two or more coats of plastic emulsion paint over a coat of primer. The item includes P/F perimeter channel of size 20x27x30mm and 0.55mm thick for light fittings, AC grills, diffusers & for light fixtures, A.C. etc. with 40x40mm teak with 40x40mm TW moulding all around, around the walls / pillars All complete as per design. (The finished surface area shall be measured) height of ceiling is 20' approx. it will use 1" x 2" holo iron section in both ways @ 10' c/c welded frame for supporting the false ceiling structure.	190	sqm		
5	<u>FALSE CEILING -GRID</u>				

	Providing & fixing Grid false ceiling (armstrong or equalvent company product) with 12mm thick mineral fibre acoustic tiles with crisp finely granulated surface in bright colour Prima regular Fine Fissured RH 99 with Arm strong TL 24mm exposed grid Tee section, exposed face shall be powder coated (white), main runner shall be Tee-shape section with single rotary stitching of size 24x38mm , 3.6m long with cross runner of tee shape section with single rotary stitching of size 24x30mm @1.2m with 24x25mm runner @ 0.60m c/c, with Armstornng suspenders, perimeter channel of size 22x22mm (white) all complete in all respect as per manufacturer's specifications.	166	sqm		
6	<u>12 MM TH. TOUGHENED GLASS Door</u>				
	12 MM TH. TOUGHENED GLASS Cabin door providing & fixing main doors/cabin made out of/cabin door made out of HNG/ Asahi India MAKE 12 MM TH.toughened EATCHED glass in single piece with computrised diamond cut & diamond edge polish including making required cutout holes for lock , handles , pivot patch fitting , corner fitting hinges etc. the rate is inclusive of patch fitting of dorma make floor spring ,pivot patch fitting with cover plate locks handles , singsges with necessary hardware rtc. as per intructions of Architect/Engineer.	3	sqm		
7	<u>12 MM TH. TOUGHENED GLASS PARTITION</u>				
	FULLY GLAZED 12 MM TH. TOUGHENED GLASS PARTITIONAs above item no 1 Aa (both side gyp.board finished partition but partition shall have 12 mm th. Toughened plane glass fixed with 1 1/2" x 1" teak wood moulding finished with white high gloss laminate 4mm teak wood veneer finished with stainless steel "D" Brackets etc . Complete as per detailed drawing & innstuction of Architect /Engineer .	6	sqm		
8	<u>TABLE (Laminated Top)</u>				
	Providing TABLES in position with Writing top, sides & front apron all be made of 19mm thick commercial board approved make with TW lipping on all exposed ends of commercial board. The front apron & sides shall be finished with 1mm thick laminate of approved shade. The writing top shall be provided with 1mm thick laminate of approved quality and shade with teak / rubber wood edging all around.The skirting shall be 100mm high with There shall be wooden foot rest made of hollock wood There shall be key board tray made of 19mm commercial block board with teakwood lipping and ebco make sliding fittings. All the non laminated surfaces shall be finished with wood polish.				
A	1800mm x900mmx 750mm high with drawer unit consists of 3 drawers, mounted on sliding channels (Ebco) All made of 19 mm commercial block board and 1 mm. lamination finish.	4	nos		
B	1500mm x 750mmx 750mm high with drawer unit consists of 3 drawers, mounted on sliding channels (Ebco) All made of 19 mm commercial block board and 1 mm. lamination finish.	11	nos		
C	1200mm x600mmx 750mm high with drawer unit consists of 3 drawers, mounted on sliding channels (Ebco) All made of 19 mm commercial block board and 1 mm. lamination finish.	30	nos		
9	<u>Wall Paneling:-</u>				
	Providing & fixing wall paneling consisting of 19 mm board with 1.0 mm high gloss two or more shades laminate of approved shade. The top of paneling to have 60 X 25 mm teak wood moulding and polished complete. Complete in all respects as per direction of Bank Engineer / Architect	210	sqft		
10	<u>RESHIFTING OF EXISTING TABLES:-</u>				
	Reshifting of existing tables 1200mm x600mmx 750mm existing circle office to new circle office as per new layout plan. It included all labour charges & material part of changes channel , lock , mica, board etc. no extra will pay	10	nos		
		Total			