

- 1. SUPPLY, INSTALLATION AND COMMISIONING OF 35 KWp ON-GRID SOLAR ROOFTOP POWER SYSTEM AT CIRCLE OFFICE KARNAL, BAY SITE 17-18, SECTOR 12, KARNAL 132001, HARYANA
- 2. SUPPLY, INSTALLATION AND COMMISIONING OF 25KWp ON-GRID SOLAR ROOFTOP POWER SYSTEM AT REGIONAL OFFICE PANCHKULA, SCO 904, NAC, MANIMAJRA, CHANDIGARH- 160101

NOTICE TYPE : DOMESTIC TENDER NOTICE

AUTHORITY TYPE : PUBLIC SECTOR BANK

\_\_\_\_\_\_

ISSUED BY
PREMISES AND ESTATE SECTION, CIRCLE OFFICE
BAY SITE 17-18, SECTOR 12, KARNAL – 132001,
HARYANA

Tel: 0184-4063657, 8572800777 e-mail: <a href="mailto:pecokar@canarabank.com">pecokar@canarabank.com</a>



	TABLE OF CONTENTS			
S.No	DETAILS			
	TECHNICAL BID			
1.	Notice Inviting Tender			
2.	Eligibility Criteria			
3.	Checklist for Enclosures			
4.	General rules and instructions for the guidance of bidders			
5.	Tender Offer			
6.	General Conditions of contract			
7.	Safety Code			
8.	Form of Agreement			
9.	Format of Indemnity Bond			
10.	Bank Guarantee Format for Earnest Money Deposit			
11.	Bank Guarantee Format for Security Deposit			
12.	Schedule A			
13.	Schedule B			
14.	Schedule C			
15.	Profile of the Bidder			
16.	Technical Data Sheet			
17.	Checklist for meeting Eligibility Criteria			
18.	Scope of Comprehensive Annual Maintenance Contract			
19.	Price Bid – Karnal			
20.	Price Bid - Panchkula			

# **NOTICE INVITING TENDERS**

Canara Bank, Premises and Estate Section, Circle Office Karnal invites item rate sealed tenders from eligible & experienced Firms / Companies in "TWO BID CONCEPT" for Supply, Installation, Commissioning & Maintenance of ON-GRID Rooftop Solar PhotoVoltaic Power Plant with Net metering:

- 1. 35 kWp at Canara Bank, Circle Office Karnal, Bay Site 17-18, Sector 12, Karnal 132001, Haryana.
- 2. 25kWp at Canara Bank, Regional Office Panchkula, SCO 904, NAC, Manimajra, Chandigarh- 160101.

# 1) Details of the Tender:

1) Details of the Tender:		
Name of the Work	Supply, Installation, Commissioning & Maintenance of ON-GRID Rooftop Solar Photo Voltaic Power Plant with Net Metering	
	Place	Capacity
	Circle Office Karnal, Bay Site 17-18, Sector 12, Karnal – 132001, Haryana	35kWp
	Regional Office Panchkula, SCO 904, NAC, Manimajra, Chandigarh- 160101	25kWp
Nature of Work	Solar Roof Top Power Plant with net	metering
Earnest Money deposit	Rs.26,000/- by way of Demand Scheduled Bank drawn in favour of	
	Circle Office, Karnal payable at	
	-	
	has to be submitted in a sealed	•
	scribing 'EMD for Tender for Supply	y, Installation,
	Commissioning & Maintenance o	f35 KWp ON-
	GRID Rooftop Solar Photo Voltaic	Power Plant
	with net metering at Circle Office	
	_	
	Site 17-18, Sector 12, Karnal	- 132001,
	Haryana.	
	Rs.19,000/- by way of Demand	
	Scheduled Bank drawn in favour of	Canara Bank
	Circle Office, Karnal payable at	Karnal. EMD
	has to be submitted in a sealed	cover, super-
	scribing 'EMD for Tender for Supply	·
	Commissioning & Maintenance o	•
	GRID Rooftop Solar Photo Voltaic	
	with net metering at Regional Office I	Panchkula, SCO
	904, NAC, Manimajra, Chandigarh- 1603	101.

PANCHKULA RESPECTIVELY	
	Both the above mentioned DDs should be submitted along with Technical & PRICE bid.
	However, those who have exemption certificate from NSIC/Similar Government authorities as per provision of MSME Act will be exempted from submission of EMD subject to the submission of valid document/certificate to that effect.
Issue of tender document	06 April 2022
Last date of submission of pre-bid queries	11 April 2022 till 3.00pm
Pre-bid meeting	12th April 2022 at 11:30AM
Concept of tender	Two Bid system
Last date and time for submission of the tender	27 <sup>th</sup> April 2022 on or before 3.00 pm. The bids should be submitted in separate sealed envelopes on the same date & time .The name of the work and bid to be super-scribed on the envelope.
	Offers shall be submitted to the office of: The Assistant General Manager, Premises and Estate Section, Circle Office Bay Site 17-18, Sector 12, Karnal - 132001, Haryana Tel: 0184-4063657, 8572800777 e-mail: pecokar@canarabank.com
Opening of Technical bids	27 <sup>rd</sup> April y 2022 at 3.30 pm
Opening of Financial bids	Date & time will be informed to the qualified bidders through e-mail/ letter.
Commencement of work	7 <sup>th</sup> day from the date of issuing of Work Order
Period of completion	60 days from the date of issue of work order(including mobilization period)
Tender documents ( soft copy )	Can be downloaded free of cost from Canara Bank's web site from 06 April 2022 till last date of submission https://canarabank.com/tenders.aspx

PANCHKULA RESPECTIVELT	
Payment Terms	As per the Clause 30 of General Conditions of Contract (Page No. 38)
Initial Security Deposit (ISD)	2% Of the Contract Amount Including EMD
Defects Liability Period (DLP)	12 Months from the date of Virtual Completion of Work
Retention Money	As per the "Clause 12 of General Conditions of Contract" (Page No. 27)
Liquidated Damages for Delay in work	As per the "Clause 15 of General Conditions of Contract" (Page No. 30)
For any clarification , please contact	The Manager, Premises and Estate Section, Circle Office Bay Site 17-18, Sector 12, Karnal - 132001, Haryana Tel: 0184-4063657, 8572800777 e-mail: pecokar@canarabank.com

# **ELIGIBILITY CRITERIA**

S.No	<u>Criteria</u>	Papers to be submitted
1	Bidder should be MNRE / SECI registered vendor.  (MNRE registration prior to discontinuation of empanelment of solar vendors by MNRE will be considered.)	Copy of the letter issued by MNRE / SECI regarding registration with them to confirm about the category of their registration.
2	The tenderer should have minimum 5 years experience in the field of solar power plants in Government / Semi Government / PSUs / office buildings / commercial premises/ industrial houses as system integrator prior to 31.12.2021.	Valid certificates, Order copies and satisfactory completion certificates prior to 31.12.2021 (Need to submit all the above mentioned documents)
3	Minimum yearly turnover of Rs 20 Lakhs during last 3 financial years.	Certificate issued by Chartered Accountant indicating turnover for the last three years i.e. 2018-19,2019-20and 2020-21 along with audited financial statement for the sameperiods.
4	The firm should have carried out the works as follows:  1) At least two (2) completed similar works each of Capacity more than 25 KWp during the last 3 (Three) years ending with 31.12.2021.  OR	Copies of detailed work order clearly indicating nature and scope and value of works. Completion certificate for the qualifying works to be submitted. Written information with full details such as names, postal address, e-mail IDs, contact details (Landline and Mobile Nos.) to be furnished so that they can be contacted by the Bank if needed.
	2) At least one (1) completed similar works each of Capacity more than 35 KWp during the last 3 (Three) years ending with 31.12.2021.	
	Similar work means supply and installation of solar power plants	

AINCHKUL/	CHKULA RESPECTIVELY					
5	The firm should have Service setup in Haryana/Delhi/Chandigarh/Punjab.	Address and contact details of the office and Service setup, is to be furnished. Copy of document proof of local address i.e lease agreement of the firm entered with landlord, tax paid receipt or GST registration has to be submitted. The same may be inspected by Bank officials.				
6	The firm must have Goods & Service tax registration number and PAN number.	Copies of the GST registration certificate and PAN card copy shall be enclosed.				

Only the Bidders who are found to meet the Eligibility Criteria detailed aboveshall be considered for Price bid evaluation.

# Checklist for Enclosures (Bidder should fill up YES or NO without fail)

SNo	Bid Enclosures	YES or NO				
1.	Whether the Tender is submitted in sealed covers					
	separately for Technical Bid and Price Bid?					
2.	Whether Technical Bid contains the following					
2.1	Checklist for meeting Eligibility Criteria with all documentation as detailed					
2.2	"Tender Offer" as per this Tender document in Bidder's Letter Head shall be signed by the authority, stamped and					
	submitted.					
2.3	"Profile of the Bidder" as per this Tender Document to be filled up, signed and stamped					
2.4	Signed and stamped Letter of Authorization or Power of Attorney for signing the Tender document shall be submitted.					
2.5	All sections covered in the Tender document in full shall be signed by the authority, stamped and submitted					
2.6	Whether Earnest Money Deposit (EMD) amount as specified in the Tender shall be submitted					
2.7	In case of claiming exemption from EMD, valid document/ certificate for exemption of EMD from NSIC/Similar Government authorities shall be submitted					
2.8	Declaration in Letterhead that all items used shall be as permitted under "Approved list of Makes and Materials" issued by Ministry of New and Renewable Energy vide latest notification.					
2.9	Following Test Certificates & Reports as per' Technical Specificates	cations'				
	i. SPV Modules					
	a) IEC 61215 / IS 14286 for Crystalline Silicon					
	Terrestrial PV Modules					
	b) IEC 61730 Part 1 & 2					
	c) IEC 61701					
	d) STC performance certificate					
	ii. System Components (for PV Power Plants)					
	a) Power Conditioners/Inverters –IEC 61683 & IEC 60083-					
	2(1,2,14,30),IEC62116,IEC62109/Equivalent standards					
	b) Cables- IS: 1554/IEC 60502 AND IS 694/IEC 60227 or Equivalent IS standard					
	Equivalent 10 Standard					

S.No	Bid Enclosures	YES or NO		
	c) Switches/Circuit Breakers/ Connectors – IS/IEC 60947 Part I,II,III & EN 50521			
	d) Junction Boxes / Enclosures of Inverters- IP 65 & IEC 62208			
2.10	2.10 Technical Data Sheets as per this Tender Document are fully filled up and enclosed			
3.	. Whether Price Bid contains the following			
3.1	Whether submitted in a separate sealed envelope with name of the works and bidder's details super scribed on the envelope?			
3.2	Whether corrections or overwriting if any is attested?			
3.3	Whether write up on present Tax structure applicable is enclosed? (refer to Clause 8 of General Conditions of Contract)			

SIGNATURE OF THE CONTRACTOR WITH SEAL

#### GENERAL RULES AND INSTRUCTIONS FOR THE GUIDANCE OF BIDDERS

- 1. Sealed tenders on item rate basis are invited from the competent contractors with sound technical and financial capacity for the subject work, by Canara Bank Premises and Estate Section hereinafter known as the Employer and also as Bank, for the Supply, Installation, Commissioning & Maintenance of 35 KWp and 25 KWp ON-GRID Rooftop Solar Photo Voltaic Power Plant at Circle Office Karnal, Bay Site 17-18, Sector 12, Karnal 132001, Haryana and Regional Office Panchkula, SCO 904, NAC, Manimajra, Chandigarh- 160101 respectively.
- 2. Scope of work covers the Supply, Installation, Commissioning & Maintenance of ON-Grid Rooftop Solar Power System with Net metering as under:-

Place	Capacity
Circle Office Karnal, Bay Site 17-18,	35kWp
Sector 12, Karnal – 132001, Haryana	
Regional Office Panchkula, SCO 904,	25kWp
NAC, Manimajra, Chandigarh- 160101	

The Contractor has to take all permits, No Objection Certificates (NOC), approvals and other liaison works with all concerned Non-statutory and statutory agencies like State Electricity boards /DISCOM (Karnal and Panchkula) for satisfactory completion and integration with the grid. Any deviation will not be accepted under any circumstance. Insuring the goods in transit as well as the commissioned system during 5years comprehensive maintenance period is the responsibility of the bidders. The comprehensive maintenance shall include preventive maintenance service visits monthly till the completion period of comprehensive maintenance. The maintenance shall include replacement of all parts or components found defective due to manufacturing defect or because of wear and tear. If the SPV Power Plants are not functional, the same should be repaired or restored or replaced within 2 days.

**3.** The tender concept is "TWO BID SYSTEM". The bids should be placed in sealed cover, with the name of the project written on the envelopes mentioning "Technical Bid" and "Price Bid" respectively latest by 3PM on 27/04/2022 to **THE ASSISTANT GENERAL MANAGER, PREMISES AND ESTATE SECTION, KARNAL-132001.** 

The sealed envelopes super-scribed as "Technical Bid for Supply, Installation, Commissioning & Maintenance of 35KWp & 25KWp ON-GRID Rooftop Solar Photo Voltaic Power Plant at Circle Office, Karnal and Regional Office Panchkula respectively " & " Price Bid for Supply, Installation, Commissioning & Maintenance of 35KWp & 25KWp ON-GRID Rooftop Solar Photo Voltaic Power Plant at Circle Office, Karnal and Regional Office Panchkula respectively " should contain all the following details:

i). All the schedules of the tender document, technical & Price details of the proposed system equipment with its components & all other attachments and Price Bid separate.

The tender (EMD should in separate envelope) shall be accompanied by earnest money of Rs 26,000/- (Rupees Thirty Five Thousand only) for work at Circle office Karnal and Rs 19,000/- (Rupees Nineteen Thousand only) for work at Regional Office Panchkula , by way of Demand Draft issued in favour of "Canara Bank Circle office" payable at Karnal, Scheduled Commercial Bank other than Canara Bank valid up to validity period of the tender in the Bank's approved format. However, those who have exemption certificate from NSIC/Similar Government authorities as per provision of MSME Actwill be from submission **EMD** subject to the submission exempted of document/certificate to that effect.

# No interest shall be allowed on the Earnest Money. Tenders without Earnest Money shall be rejected.

# 4. PRE BID QUERIES AND CLARIFICATION TO THE TENDER:

The Vendor should inspect both the site, carefully examine and understand the specifications, terms and conditions of the Tender and may seek clarifications, if required. The Vendor in all such cases seek clarification in writing in a word document (.doc) in the same serial order of that of the Tender by mentioning the relevant page number and clause number of the Tender. The soft copy of the prebid queries should be send by email to <a href="mailto:pecokar@canarabank.com">pecokar@canarabank.com</a> and the pre-bid query should be in the following format.

	S.No	Page No	Tender Clause No	Tender Clause	Query
ſ					

All communications regarding points requiring clarifications and any doubts shall be sent by E-mail to <a href="mailto:pecokar@canarabank.com">pecokar@canarabank.com</a> on or before 3:00 PM on 11/04/2022. No oral or individual consultation shall be entertained. No queries will be entertained from the Vendors after the pre-bid meeting.

# Pre-Bid meeting:

A pre-bid meeting of the intending Vendor will be held as scheduled below to clarify any point /doubt raised by them in respect of this Tender document:

Date	Time	Venue
12.04.2022	11.30 AM	Canara Bank Circle Office Karnal, Bay Site 17- 18, Sector 12, Karnal – 132001, Haryana

No separate communication will be sent for this meeting. If the meeting date is declared as a holiday under NI Act by the Government subsequent to issuance of RFP, the next working day will be deemed to be the pre-bid meeting day. Authorized representatives of interested Vendors shall be present during the scheduled time.

The Bank will consolidate all the queries and discussions during the pre-bid meeting and the consolidated replies for the queries shall be made available in the Bank's website and no individual correspondence shall be made. The replies/clarification of the Bank in response to the queries raised by the bidder/s, and any other clarification / amendments / corrigendum furnished hereof will become part and parcel of the Tender document and it will be binding on the Vendors.

Non-reply to the queries raised by any of the Vendor shall not be accepted as a valid reason for non-submission of the Tender. In addition, non-reply to any query may not be deemed the version of the Vendor as reflected in the query has been accepted by the Bank.

#### 6.3 Amendment to Tender Document:

At any time prior to deadline for submission of Tender, the Bank, for any reason, whether, at its own initiative or in response to a clarification requested by prospective bidder may modify the Tender document by amendment.

Notification of amendments will be made available on the Bank's website (www.canarabank.com) and will be binding on all Vendors and no separate communication will be issued in this regard.

In order to allow prospective Vendors reasonable time in which to take the amendment into account in preparing their tender, the Bank, at its discretion, may extend the deadline for a reasonable period as decided by the Bank for the submission of tender.

#### 5. OFFER VALIDITY PERIOD:

The Offer submitted and the Price quoted therein shall be valid for 90 days from the date of opening of tender document i.e. Technical bid and for such further period as may be requested for by the bank, and agreed to in writing by the bidder.

6. The time allowed for carrying out of the work will be not exceeding the period specified in the NIT.

- 7. The contractors should quote in figures as well as in words the rate, and amount tendered by them. The amount for each item should be worked out and the requisite totals given. The rates quoted shall be all inclusive rates for the item of work described, including materials, labour, tools & plant, carriage & transport, supervision, overheads & profits, mobilizing and other charges whatsoever including any anticipated or un-anticipated difficulties etc. complete for proper execution of the work as per drawings and specifications and no claim whatsoever for any extra payment shall be maintainable.
- 8. The rates quoted by the Contractors shall inclusive of obtaining No Objection Certificates (NOC) and other liaison works with all concerned Non- statutory and statutory agencies like State electricity Board / DESCOM.
- 9. When a contractor signs a tender in an Indian language, the percentage above or below and the tendered amount and the total amount tendered should also be written in the same language. In the case of illiterate contractors the rates or the amounts tendered should be attested by a witness.
- 10. Issue of tender form / documents is as per the NIT.
- 11. The acceptance of a tender will rest with the Employer which does not bind itself to accept the lowest tender, and reserves to itself the authority to reject any or all of the tenders received without assigning any reason. All tenders in which any of the prescribed conditions are not fulfilled or are incomplete in any respect are liable to be rejected.

# 12. THE EMPLOYER RESERVES THE RIGHT TO ACCEPT THE TENDER IN FULL OR IN PART AND THE CONTRACTOR SHALL HAVE NO CLAIM FOR REVISION OF RATES/OTHER CONDITIONS IF HIS TENDER IS ACCEPTED IN PART.

- 13. Canvassing in connection with tenders is strictly prohibited and the tenders submitted by the contractors who resort to canvassing will be liable for rejection.
- 14. All rates shall be quoted on the proper form of the tender alone. Quoted rates and units different from prescribed in the tender schedule will be liable for rejection.

Special care should be taken to write the rates in figures as well as in words and the amounts in figures only, in such a way that interpolation is not possible. The total amount should be written both in figures and in words. In case of figures, the words `Rs.' should be written before the figure of rupees and words `P' after the decimal figures, e.g. Rs.2.15 "P" and in case of words, the word `Rupees' should precede and the word `Paise' should be written at the end,

unless the rate is in whole rupees and followed by the words `only' it should be invariably be up to two decimal places. While quoting the rate is in schedule of quantities, the word `only' should be written closely following the amount and it should not be written in the next line. However, if a discrepancy is found;

- i). the rates which correspond with the amount worked out by the Contractor shall unless otherwise proved be taken as correct. (OR)
- ii). if the amount of an item is not worked out by the Contractor or it does not correspond with the rates written either in figures or in words then the rate quoted by the Contractor in words shall be taken as correct. (OR)
- iii)where the rates quoted by the Contractor in figures and in words tally but the amount is not worked out correctly, the rates quoted by the Contractor will unless otherwise prove be taken as correct and not the amount.

In the case of any errors or omissions in the quoted rates, and if the tender is issued in duplicate, the rates quoted in the tender marked "Original" shall be taken as correct rates.

All corrections such as cuttings, interpolations, omissions and over-writings shall be number as `c', `i', `o' and `ow' and initialed and total of such c, i, o and ow on each page certified at the end of the page with grand total at the end of the bill/schedule of quantities.

- 15. An item rate tender containing percentage below / above will be summarily rejected. However, where a Contractor voluntarily offers a rebate for payment within a stipulated period, this may be considered.
- 16. Goods & Service Tax (GST) is payable extra by Bank. Sales tax, service tax, work contract tax, or any other tax, any royalties, import duty, other duties if any, levies, cess, entry tax, Octroi, profession tax, Sales Tax, purchase tax, turnover tax, or any other tax on material or finished work in respect of this contract shall be payable by the Contractor and the Employer will not entertain any claim whatsoever in respect of the same, and nothing extra shall be paid/reimbursed for the same subsequently with exception specified in the clause 8 of the General Conditions of the contract of this tender.
- 17. The contractor shall give a list of his relatives, if any, working with the Employer along with their designations and addresses.
- 18. No employee of the employer is allowed to work as a contractor for a period of 2 years of his/her retirement from the employer services, without the previous permission of the employer. This contract is liable to be cancelled if either the

contractor or any of his employees is found at any time to be such a person who had not obtained the permission of the employer as aforesaid before submission of the tender or engagement in the contractor's service.

- 19. The tender for the works shall remain open for acceptance for a period of 90 days from the date of opening of tenders. If any Contractor withdraws his tender before the said period or makes any modifications in the terms and conditions of the tender which are not acceptable to the Employer, then the Employer shall, without prejudice to any other right or remedy, be at liberty to forfeit full value of the earnest money as aforesaid.
- 20. The tender for the work shall not be witnessed by a contractor or contractors who himself / themselves has / have tendered or who may and had/have tendered for the same work. Failure to observe this condition would render tenders of the contractors tendering as well as witnessing the tender liable to summary rejection.
- 21. It will be obligatory on the part of the Contractor to tender and sign the tendered documents for all the component parts and that, after the work is awarded, he / they will have to enter into an agreement for each component with the competent authority of the Employer.
- 22. Further the Contractor shall agree that until a formal agreement is executed and signed, this tender shall constitute a binding contract between the Contractor and the Employer. The stamp paper of requisite value as per State Governments should be borne by the Contractor.
- 23. The Contractor, apart from being a competent contractor must associate himself with agencies of appropriate class who are eligible to tender for other related works connected directly or indirectly with the contract and employed by the employer.

The Employer does not bind itself to accept the lowest or any tender and reserves to itself the right of accepting the whole or any part of the tender and the Contractor shall be bound to perform the same at the rate quoted.

Contractor are advised to inspect and examine both the site and its surroundings and satisfy themselves before submitting their tenders as to the nature of the site and dimensions, the means of access to the site, and obtain all necessary information as to risks, contingencies and other circumstances which may influence or affect their tender.

A Contractor shall be deemed to have full knowledge of the site whether he inspects it or not and no extra charges consequent on any misunderstanding or otherwise shall be allowed. Submission of a tender by a Contractor implies that

he has read this notice and all other contract documents and has made himself aware of the scope and specifications of the work to be done and local conditions and other factors bearing on the execution of the work.

- 24. On acceptance of the tender, the name of the accredited representative(s) of the contractor who would be responsible for taking instructions from the Employer shall be communicated to the Employer.
- 25. **Method of Evaluation of tender:** All the competitive tenders will be received on the specified date and time. On the same day or on specified date & time in event of any compelling circumstances, the tender will opened in the presence of the available Contractors.

The "Technical Bid" will be opened and details of EMD etc., shall be recorded. Incomplete offers and offers not accompanied by the mandatory documents and EMD shall be rejected. The date of Price bid opening shall be subsequently intimated to the bidders who are provisionally shortlisted after Technical Bid evaluation.

Voluntary submission of the supplementary Price bid by the contractor / Contractor shall not be accepted and supplementary bids shall be limited to the details sought for by the Employer only. Any other un-related Price variations furnished in supplementary Price bids shall not be recognized and might be liable for rejections if undue information are furnished.

In case of other un-successful Contractors, the EMD shall be returned treating it individually after finalizing the L1 vendor.

The Employer reserves the right to accept or reject any of the offer's without assigning any reason and no dispute or negotiation will be entertained in this regard. The Employer's decision will be final in the matter.

# **Techno Economic evaluations:**

Being a techno - economical project, besides the capital cost, the present value of Comprehensive AMC charges for 4 years after completion of defect liability period will also be evaluated. The present value of the AMC component per year will be calculated as per the following formula:

Present Value =  $c / (1+r)^n$ 

Where 'c' is the annual AMC of each year

'r' is REPO LINKED Lending Rate(RLLR) which is at present 6.9%

'n' is number of years, i.e. n is 1 for 1st year and 2 for 2nd year etc.

The above mentioned calculation is for Price comparison purpose only.

Therefore, the Contractors / contractors shall furnish the AMC charges in the Price bid for 5 years. Terms of AMC including details regarding the scope of AMC, detail of spares, consumables & equipments covered and also details of exclusions are as detailed in the tender.

In case of quoting for very low abnormal AMC rates, Bank reserves the right to seek for the Performance Guarantee to the extent of 10% of the project cost throughout the 5 year period (1year Defect Liability period and 4 years under CMC)

- 26. The minimum annual generation guarantee of solar power should be as per the clause 19 of "Technical Specifications of SPV Power Plant".
- 27. The successful Contractor/contractor, on acceptance of his tender by the Accepting Authority, shall, within 7 days from the stipulated date of start of the work sign on a stamp paper the contract consisting of :-
- (a) Standard form of Agreement & Indemnity Bond on stamp paper.
- (b) Notice inviting tender, all the documents including tender, forming the tender as issued at the time of invitation of tender and acceptance thereof together with any correspondence leading thereto. General Conditions, Schedules leading to Technical Specification, Special Conditions, Technical Brochures in schedules submitted by the Contractor etc.,
- (c) Price Bid / Schedule Bill of Quantities.

#### **TENDER-OFFER**

I/We have read and examined the Notice Inviting Tender, prequalification criterion, proforma filled in by the successful Contractor, Schedules, Specifications Applicable, Drawings and Designs, General Rules and Instructions, General Conditions of Contract, Special conditions, Schedule (Bill) of quantities in Price Bid, and all other documents referred to in the conditions of contract and all other contents in the tender document for the work.

I/We hereby tender for the execution of the work specified for the Employer within the time specified at the rates specified in the attached Price Bid viz., schedule of quantities and in accordance in all respects with the specifications, designs drawings and instructions in writing referred to in the General Rules and Instructions, General Conditions of Contract and in all respects in accordance with, such conditions so far as applicable.

In the event of my / our failure to commence the work on the specified date after award I/We agree that the Bank shall without prejudice to any other right or remedy, be at liberty to forfeit the said earnest money absolutely otherwise the said earnest money shall be retained by it towards security deposit to execute all the works referred to in the tender documents upon the terms and conditions contained or referred to therein.

I/We hereby declare that I/We treat the tender documents, drawings and other records connected with the work as secret/confidential documents and shall not communicate information/derived there from to any persons other than a person to whom I/We am /are authorized to communicate the same or use the information in any manner prejudiced to the safety of the State / the Employer.

I/We agree that until a formal agreement on stamp paper is prepared and signed, this tender with your written acceptance thereof shall constitute a binding contract between us.

Dated the: ...... 2022

Witness,

Signature of Contractor
Name & address:
Full Postal Address including
Pin Code NO. & Telephone no

1).

2).

#### **GENERAL CONDITIONS OF CONTRACT**

Except where provided for in the description of the individual items in the schedule of quantities and in the specifications and conditions laid down hereinafter and in the Drawings, the work shall be carried out as per standard specifications and under the direction of the Employer.

# 1. DEFINITIONS / INTERPRETATIONS:

- i). The `Contract' means the documents forming the tender and acceptance thereof and the agreement duly executed between the Employer and the Contractor, together with the documents referred to therein including those conditions, the specifications, schedule of quantities, tender agreement, designs, drawings and instructions issued from time to time by the Engineer-in-Charge. All these documents taken together, shall be deemed to formone contract and shall be complementary to one another.
- ii). In the contract, the following expressions shall, unless the context otherwise requires, have the meanings, hereby respectively assigned to them:-
- a) The 'Firm', 'Contractor' or 'Supplier' or 'Contractor' or 'Contractor' shall mean the individual Kartha, or Manager of HUF, firm or Company, whether incorporated or not, undertaking the works and shall include the legal heirs/representatives of such individual or the partners composing firm and theirs legal heirs and successors, or company's authorized and constituted attorneys/agents and permitted assignees of such firm or company.
- b) The `Employer' or `Bank' or 'Purchaser' means any officer of the Canara Bank, who is specifically authorized to enter into contracts in respect of the above works.
- a) The 'Consultant' means the specialized Consultant/agency appointed by the Bank. The 'Engineer-in-Charge 'means the Senior Manager, or Officer, / Engineer and/or Site Engineer who shall supervise and be in-charge of the work or any other authorized representative or person specifically deputed by the Employer wherever they are employed from time to time by the Employer.
- d) "Contract Value" shall mean the final accepted rates in the Price Bid excluding AMC charges.
- e) `Date of Contract' means the `Calendar date on which the Employer and Contractor have signed the Agreement on the Stamp Paper.

f) "Accepting Authority" shall mean the Divisional Manager/Assistant General Manager, Canara Bank, P&E Section, Circle office.

'Approval' wherever used in the specifications or schedule of Quantities shall mean, respectively, approved by or approval of the `Accepting Authority' in writing.

- g) `Appellant Authority' shall mean The Deputy General Manager, Canara Bank Circle Office (the Employer). Who shall also be the authority to consider any extension of time or compensation as defined in clause hereunder.
- h) `Notice in writing' or `written notice' shall mean a notice in writing typed or printed characters delivered to or sent by registered post to the last known address private or business address or registered office address, and shall be deemed to have been received when in ordinary course of post it would have been delivered, and/or delivered personally, or otherwise proved to have been received.
- i) `virtual completion' shall mean that the work/installation is complete in all respects in the opinion of the Employer and for which the completion/clearance certificate has been issued by the Engineer -in-charge and the installation is fit for usage.
- i) `Drawings' shall mean all drawings and/or design drawings furnished by the Contractor / sketches duly signed by the authorized Engineer-in-charge on behalf of the Employer before commencement or during the progress of the work.
- k) `Work Order/Letter of Acceptance' shall mean an intimation by a letter issued by the Accepting Authority of the Employer to Contractors that his tender has been accepted in accordance with the provisions in the said letter.
- I) "Warranty period" or "Defect Liability period (DLP)" shall mean a period of 1 year from the certified date of virtual completion issued by the Engineer-in-charge and accepted by the Employer.
- m) "Site" shall mean the

Site	Capacity
Circle Office Karnal, Bay Site 17-18,	35kWp
Sector 12, Karnal – 132001, Haryana	_
Regional Office Panchkula, SCO 904,	25kWp
NAC, Manimajra, Chandigarh- 160101	

where the solar power plant is to installed and commissioned as per tender schedule of quantities allotted by the employer for the firm's use.

#### 2. SCOPE OF WORKS TO BE CARRIED OUT:

The work consists of the contractor's own design based on technical specifications furnished. The contractor / supplier shall be responsible for its functioning according to the design criteria and its parameters. Notwithstanding the details furnished, any discrepancies shall be brought out in the technical bid highlighting the shortcomings and suggest modifications.

The work to be carried out under the contract shall, except as otherwise provided in these conditions, include all labour, materials, tools, plants, equipment and transport which may be required in preparation of and for and in the full and entire execution and completion of the works.

The descriptions given in the Price Bid/ Schedule of Quantities shall, unless otherwise stated, be held to include wastage on material, carriage and cartage, carrying and return of empties, hoisting, setting, fitting and fixing in position and all other labour necessary and for the full and entire execution and completion as aforesaid in accordance with good engineering practice and recognized principles.

The several documents forming the Contract are to be taken as mutually explanatory of one another, detailed drawing being followed in preference to small scale drawing and figured dimensions in preference to scale and special conditions in preference to General Conditions.

In the case of discrepancy between the schedule of quantities, the specifications and/or the Drawings, the following order of preference be observed:-

- a) Description in Schedule of Quantities/ Price Bid.
- b) Particular Specifications and Special condition, if any
- c) Drawings prepared for the design.
- d) BIS Specifications.

If there are varying or conflicting provisions made in any one or more document(s) forming part of the contract, the Accepting Authority shall be the deciding authority with regard to the intention of the document and his decision shall be final and binding on contractor.

Any error in description or quantity or rate in Schedule of Quantities or any omission there from shall not vitiate the Contract or release the contractor from the execution of the whole or any part of the works comprised therein according to drawings and specifications or from any of his obligations under the Contract.

The contractor shall forthwith comply with and duly execute any work comprised in such Employer's instruction, provided always that verbal instructions, directions and explanations given to the contractor's or his representative upon the works by the Employer shall if involving a variation be confirmed in writing to the contractor/s within 7 days.

No work for which rates are not specifically mentioned in the Priced schedule of quantities, shall be taken up without written permission of the Employer. Rates of items not mentioned in the Priced schedule of quantities shall be fixed by the Employer as provided in clause "Variation".

Regarding all factory made products, they shall be manufactured as per their respective IS code updated and all tests undertaken at factory. The standards and approved makes as notified by the Ministry of New and Renewable Energy from time to time shall be strictly adhered to.

# 3. The work shall be carried out at Bank's building:

Place	Capacity
Circle Office Karnal, Bay Site 17-18,	35kWp
Sector 12, Karnal – 132001, Haryana	
Regional Office Panchkula, SCO 904,	25kWp
NAC, Manimajra, Chandigarh- 160101	•

The bidder shall visit the sites and make himself thoroughly acquainted with the local site conditions, nature and requirements of works, facilities of transport condition, effective labour and materials, access and storage for materials and removal of rubbish. Thebidder shall provide in his tender cost of carriage, freight and other charges as also for any special difficulties and including police restriction for transport etc. for proper execution of work as indicated. The successful bidder will not be entitled to any claim of compensation for difficulties faced or losses incurred on account of any site condition which existed before the commencement of the work or which in the opinion of the Employer might be deemed to have reasonably been inferred to be so existing before commencement of work. Work shall be carried out through qualified engineer/supervisor with appropriate license as per statutory rules.

#### 4. TENDERS::

The entire set of tender paper issued to the bidder should be submitted with price details filled up in full, and also signed on the last page of respective chapter (this shall be acceptance of all the pages of the tender and its stipulations) together with initials on every page. Notwithstanding this, Initials / signature in every page will indicate the acceptance of the tender papers by the Contractor.

No modifications, writing or corrections can be made in the tender papers by the Contractor, but he may at his option offer his comments or modifications in a separate sheet of paper attached to original tender papers.

The Contractors should note that the tender is strictly on item rate basis and their attention is drawn to the fact that the rates for each and every item shouldbe correct, workable and self-supporting.

If called upon by the Employer, detailed analysis of any or all the rates shall be submitted. The Employer shall not be bound to recognize the contractor's analysis.

All items of work described in the schedule of quantities and technical specifications are to be deemed and paid as complete works in all respects and details including preparatory and finishing works involved, directly, related to and reasonably detectable from the drawings, specifications and schedule of quantities and no further extra charges will be allowed in this connection. In the case of lump-sum contracts, the payment of such items of work will be made for the actual work done on the basis of lump-sum charges as will be assessed to be payable by the Employer.

The Employer has power to add to, omit from any work as shown in the drawings or described in the specifications or included in schedule of quantities and intimate the same in writing but no addition, omission or variation shall be made by the contractor without authorization from the Employer. No variation shall vitiate the contract.

The Contractor shall be deemed to have satisfied himself before tendering as to the correctness and sufficiency of his tender for the works and of the rates and Prices quoted in the Schedule of Quantities, which rates and Prices shall, except as otherwise provided, cover all his obligations under the Contract and all matters and things necessary for the proper completion and maintenance of the works.

#### 5. SIGNING OF CONTRACT & AGREEMENT::

The successful Contractor/contractor, on acceptance of his tender by the Accepting Authority, shall, within 7 days from the stipulated date of start of the work sign the contract consisting of :-

- a) Standard form of Agreement & Indemnity Bond on stamp paper.
- b) Standard tender Form consisting of::
  - i) Notice inviting tender, eligibility criteria, General Rules and Instructions.
  - ii) General Conditions of contract and clauses of contract along with Annexures thereto, like specification, special conditions etc.

- iii) Bill of Quantity and Price Bid.
- iv) List of Approved Brands/manufacturers appended, if any.

Contractor shall sign an Indemnity Bond in Bank's approved format (FORMAT ATTACHED) before starting the work, indemnifying the Bank from any damages, prosecution, other legal suits and claims arising out of any mishaps occurring at the site due to faulty work, non fulfilling safety precautions, faulty construction and for violating any statutory rules and regulations for which the contractor shall be solely responsible.

The contractor shall pay for all stamps and legal expenses, incidental thereto.

# **6. PERMITS AND LICENCES::**

Permits and licenses for the release of materials or its purchases which are under Government control will be arranged by the successful bidder. It may be clearly understood that no compensation or additional charges can be claimed by the contractor for non-availability of such materials in due time on this account or according to his own requirements.

The successful bidder may, however, be eligible to a proportionate extension of time on this account which in the opinion of the Employer is reasonable.

#### 7. GOVERNMENT AND LOCAL RULES::

The contractor shall conform to the provisions of all local bye-laws and acts relating to the work and to the regulations etc. of the Government and Local Authorities and of any Company whose system and design is proposed to be connected / utilized. The cost, if any, shall be deemed to have been included in his quoted rates, taking into account all liabilities and shall indemnify the Employer against such liabilities and shall defend all actions arising from such claims or liabilities.

#### 8. TAXES AND DUTIES ::

Goods & Service Tax (GST) shall be payable extra by Bank. The tendered cost must include all duties royalties, cess and or any other taxes or local charges if applicable. No extra claim will be entertained with exception herein specified below.

The bidders must include in their tendered cost all duties, royalties, cess, Work contract tax and sales tax or any other taxes or local charges like octroi etc. if applicable except in the AMC cost which is exclusive of goods & service tax and inclusive of all other taxes. No extra claim on this account will in any case be entertained. However, pursuant to the Constitution (Forty Sixth Amendment) Act, 1982, if any further new tax, royalties cess or levy is imposed by Statute, and any Central Excise Duty by the Central Government on the Main Equipment and

not on any type of sub-components or material involved in its manufacture or on installation materials like piping or electrical cabling, its switch gears etc., after the date of receipt of tenders, and the contractor there upon necessarily and properly pays such taxes / levies the contractor shall be reimbursed the amount so paid, provided such payments, if any, is not, in the opinion of the Employer ( whose decision shall be final and binding on the contractor) attributable to delay in execution of work within the control of the contractor. On account of any downward revision of such taxes / levies, the benefit shall be passed on to the Employer and shall be binding on the contractor even without the claim by the Employer.

- ii). The contractor shall keep necessary books of accounts and other documents for the purpose of this condition as may be necessary and shall allow inspection of the same by a duly authorized representative of the Employer and / or the Engineer-in-charge and further shall furnish such other information / document as the Employer may require from time to time.
- iii). The contactor shall, within a period of 30 days of the imposition of any such further tax / levies, described above, give a written notice to the Employer that the same is given to pursuant to this condition, together with all necessary information relating thereto.

For this purpose the Contractors are requested to furnish the present tax structures separately with the PRICE bid.

**9.** No optional items should be quoted in the tender.

# **10. QUANTITY OF WORK TO BE EXECUTED:**

The quantities shown in the schedule of quantities are intended to cover the entire works as per the drawings / scope of work, and therefore the contractor is bound to complete the works at the same quoted rates in the event of quantity exceeding the specified bill of quantity, but the Employer reserves the right to execute only a part or the whole or any excess thereof without assigning any reason therefore.

#### 11. OTHER PERSONS OR AGENCIES ENGAGED BY THE EMPLOYER::

The Employer reserves the right to execute any part of the work included in this contract by other agency or persons and contractor shall allow reasonable facilities and use of his facilities for the execution of such work. The main contractor shall extend all co-operation in this regard.

Wherever the work is proposed in co-ordination with other agencies, the contractor shall co-operate with the schedule of works in such a manner as

worked out by the Architect / Engineer-in-charge of the Employer.

# 12. EARNEST MONEY, RETENTION MONEY & TOTAL SECURITY DEPOSIT::

Earnest Money Deposit: The Contractor will have to deposit the specified amount of earnest money as detailed in the notice inviting tender at the time of submission of tender. However, those who have exemption certificate from NSIC/Similar Government authorities as per provision of MSME Act will be exempted from submission of EMD subject to the submission of valid document/certificate to that extent.

No interest will be paid on the earnest money. The earnest money of unsuccessful Contractors will be refunded without any interest soon after the decision to award the work is taken or after the expiry of the validity period of the tender.

The successful Contractor to whom the contract is awarded will have to deposit as initial security deposit (including the Earnest Money) a further sum to make up 2% of the value of the accepted tender. The initial Security Deposit will have to be made within 14 days from the date of acceptance of tender, failing which the Employer at his discretion, without prejudice to any other rights/remedies available under the terms of this Contract may revoke the letter of acceptance and forfeit the Earnest money deposit furnished along with the tender. The initial Security Deposit will not yield any interest & shall be held at Bank's end for the duration of the contract period. It shall be refunded to the contractor without any interest within fourteen days after the issue of certificates of virtual completion, after deducting any sum due from the contractor on any account under this contract.

Apart from the initial security deposit made as above, retention money shall be deducted from progressive running bills @ 8% of the gross value of each running bill until the total security deposit, i.e., the initial Security Deposit plus the retention money equals:

- a) 10% on the first rupees one lakh of the tendered cost of work.
- b) 7.5% on the next rupees one lakh of the tendered cost of work.
- c) 5% on the remaining amount of the tendered cost of work.

50% of the retention amount is refunded to the contractor on completion subject to the following.

- (i) Issue of virtual completion certificate by the Bank's Premises Department/ Architect
- (ii) Contractor's removal of his materials, equipment, labour force, temporary sheds/ stores etc, from the site (excepting for a small presence required if any for the defect liability period and approved by the Bank).

The remaining 50% of the retention amount will be refunded to the contractor, after deducting any sum due from the contractor on any account under this contract, 14 (fourteen) days after the end of Defect Liability period provided, the contractor has satisfactorily carried out all the work and attended to all defects in accordance with the conditions of the contract. The Security Deposit shall be by way of Demand Draft drawn in favour of Canara Bank, payable at Karnal or by way of Bank Guarantee obtained from any Scheduled Commercial Bank other than Canara Bank.

No interest is allowed on retention money.

A part of the Security Deposit if and as decided by the bank can also be furnished in the form of a bank guarantee from a Bank other than Canara Bank.

#### CONTRACTOR TO PROVIDE EVERY THING NECESSARY::

- i). The contractor shall provide everything necessary for the proper execution of the work according to the intent and meaning of the design parameters, technical specifications, drawings and Price Bid/ schedule of quantities, based on the details furnished in the Notice Inviting Tender. The contractors should undertake their own assessment and design the plant and system required. If the contractor finds any discrepancies furnished it shall immediately brought to the notice of the Employer.
- ii). The Contractor shall take full responsibility for adequacy, suitability and safety of all the design, works and methods of design / installation.
- iii). The employer shall on no account be responsible for the expenses incurred by the contractor during the progress of work at site, towards any incidental expenditure like medical amenities to the workers at site, security arrangement etc. The employer shall not be responsible for the safety of the workers at site either on account of the works executed by the contractor or on account of the works executed by any other agency involved at that time.
- iv). The Employer on no account shall be responsible for storage of materials or loss or pilferage or theft either in respect of the material stored or material already built and paid for by the Employer.
- v). The contractor shall at all times give access to workers employed by the Employer.
- vi). All tools, equipments and other required facilities for execution of work shall be provided by the contractor.

vii). Any facilities available at site shall be utilized only with prior permission of the Employer or the in-charge of the site / building owner and cannot be taken as granted and for such services utilized the Employer is entitled to chargeat his discretion.

No extra charges shall be paid over and above what has been quoted for any of the above or for similar such services.

# 14. TIME OF COMPLETION, EXTENSION OF TIME & PROGRESS CHART::

i). Time of Completion: 60 days from the date of work order acceptance by the Vendor including Mobilization period.

The entire work is to be completed in all respects within the stipulated period. The work shall be deemed to commence from the date of issue of work order from the date of acceptance letter or date of handing over site, whichever is earlier. Time is the essence of the contract and shall be strictly observed by the contractor.

The work shall not be considered as complete until the Employer have certified in writing that the work has been virtually completed and defect liability period shall commence from the date of such certificate.

# ii). EXTENSION OF TIME::

- (a) The time allowed for execution of the Works by the Contractor as specified or the extended time in accordance with these conditions shall be the essence of the Contract. If the contractor commits default in the execution of the work as aforesaid, the Employer shall without prejudice to any other right or remedy available in law be at liberty to forfeit the earnest money absolutely.
- (b) Request for extension of time, to be eligible for consideration, shall be made by the contractor to the accepting authority in writing within fourteen days of the happening of the event causing delay. The contractor shall also, if practicable, indicate in such a request the total period for which extension is desired, overlapping period, if any, with earlier events causing delays.
- (c) In such case the authority may give a fair and reasonable extension of time for completion of work. Such extension shall be communicated to the contractor by the Employer in writing, within 3 weeks of the date of receipt of such request. Non application by the contractor for extension of time shall not be a bar for giving a fair and reasonable extension by the Employer and this shall be binding on the contractor.
- (d) The decision of the Employer for an extension of time for completion hereunder ( which decision shall be final and binding on the contractor) shall be

promulgated on completion of the work or at the conclusion of such events based on which the extension of time was sought by the contractor, and the Employer shall then, in the event of an extension being granted, determine and declare the final completion date. The provision in clause with respect to payment of Liquidated Damages shall, in such case, be read and construed as if the extended ate fixed by the Employer were substituted for and the damage shall be deducted accordingly.

# iii). Progress of Work:

During the period of work, the contractor shall maintain proportionate progress on the basis of a programme chart submitted by the contractor or prepared by the Engineer in charge whoever is responsible for such programme of work. Contractor shall plan for procurement of materials, equipments well in advance and reflect the same in a progress chart so that there is no delay on the part of the contractor in completion of the project. Maintenance and production of such records as and when required shall be the responsibilities of the contractor.

# **15. LIQUIDATED DAMAGES::**

Time is the essence of the contract. Thus the Contractor shall be aware and take note that non-supply or commissioning of the equipment / system will affect the Banks committed programs and thus the loss by way delayed services /completion of related works etc, are invaluable and cannot be easily assessed. Therefore, it is part of the agreed terms that in the event of any delay in completion of the work, the Bank is liable to charge the Contractor without the necessity of providing for any details of such losses suffered by the Bank.

If the contractor fails to maintain the required progress in terms of the contract or to complete the work and clear the site on or before the contract or approved extended date of completion, he shall, without prejudice to any other right or remedy of the Employer on account of such breach, pay as agreed compensation the amount calculated at the rates stipulated below or such smaller amount as may be fixed by the employer on the contract value of the work for every completed week that the progress remains incomplete.

For this purpose the term `Contract Value' shall be value at the contract rates of the work as ordered / accepted and the Contract value does not include the AMC cost.

If the Contractor fails to complete the works within the time for completion stated in the tender or within any extended time under Clause 14.ii hereof, the Contractor shall pay the Employer the sum at the rate of 0.5 % of the Contract Value per week of delay subject to a maximum limit of 5 % of the Contract Value as "Liquidated damages" for the period during which the said works shall so remain incomplete or the Employer may deduct aforesaid sum towards such damages from any monies due to the Contractor.

The Employer shall have the right to adjust, / set-off against any sum payable to the contractor under this or any other contract with the Employer anywhere in India/outside India.

# TOOLS, STORAGE OF MATERIALS, PROTECTIVE WORKS AND SITE OFFICE REQUIREMENTS::

The contractor shall provide, fix up and maintain his establishment in an approved position at site and clear away on completion of the works and make good all works disturbed. The contractor shall not fix or place any placards or advertisement of any description or permit the same to be fixed or placed in or upon any hoarding, gantry, building structure other than those approved by the Employer. No fixtures or materials to be placed in such a manner that can be considered dangerous to the installation and to the persons working or passing by or visiting the site.

<u>Storage of materials</u>: The contractors shall make use of existing facilities with due permission of the Employer for storage of materials at site, but watch & ward arrangements for the safety of materials shall be the responsibility of the contractor. Additional covered space required if any, shall be arranged at the Contractor's own cost in the open space identified/ear marked by the Bank.

#### 17. NOTICE AND PATENTS OF APPROPRIATE AUTHORITY AND OWNERS::

The contractor shall conform to the provisions of any Acts of the Legislature relating to the work, and to the regulations and bye-laws of any authorities, and or other Companies (Indian or International), and / or Statutory Authorities, with whose system and design or technical know-how are/were proposed to have connection with this work. So also the contractor shall before making any variations from the drawings or specification that may be associated to so conform, give the Employer written notices specifying the variations proposed to be made and the reasons for making them and apply for instruction thereon. The Employer on receipt of such intimation shall give a decision within a reasonable time.

The contractor shall arrange to give all notices required for by the said Acts, regulations or Bye-laws to be given to any authority, and to pay to such authority or to any public officer all fees that may be properly chargeable in respect of the work and lodge the receipts with the Employer.

The contractor shall indemnify the Employer against all claims in respect of patent rights, royalties, damages to buildings, roads or members of public in course of execution of work and shall defend all actions arising from such claims

and shall keep the Employer aloof and indemnified in all respects from such actions, cost and expenses.

# 18. CLEARING SITE AND SETTING OUT WORKS::

The site of work shown shall be cleared of all obstructions, waste materials, rubbish of all kinds. All material damages on the place of work on the walls, ceiling or flooring or any other connected equipments, materials or installations shall be re-done to maintain the originality and leveled at the contractors own cost.

The contractors shall set out the works and shall be responsible for the true and perfect setting out the works and for the correctness of the positions, levels, dimensions and alignment of all parts thereof. If at any time, any error shall appear during the progress of any part of the work, the contractor shall at his own expenses rectify such error, if called upon to the satisfaction of the Employer.

# 19. FIXING, FASTENING OF EQUIPMENTS::

The contractor is to fix the equipments on the floor by means of appropriate method so that such equipments fixed on to the floor shall not fall by its own or by natural movements of wind, air normal human operations and shall adopt the best engineering traditions and use appropriate tools in such operations.

The contractor while fixing any material or equipment to be suspended from the ceiling, shall use fasteners of suitable strength to hold the weight of the suspended system/equipment or material and such fasteners shall be fixed by means of power drills. The contractor shall not chip the ceiling unless ordered & approved by the Engineer- in-charge.

The contractor shall not puncture the existing civil structures like beams, columns and shall not undertake any type of activity which could affect the structural stability. He shall be responsible for any damages and costs in its rectification.

#### 20. CONTRACTOR IMMEDIATELY TO REMOVE ALL OFFENSIVE MATTERS ::

All waste materials and other matters of any offensive nature shall be taken out once the works are completed. The contractor shall keep the works free from dangerous materials like industrial gases, welding machines and any such devices or material of toxic and poisonous nature shall not carry within the site or building any material which are explosive in nature. Any such offensive materials which are essentially required in course of work shall be undertaken with due written permission of the Employer provided such materials are permissible under Law.

#### 21. ACCESS ::

Any authorized representatives of the Employer shall at all reasonable times have free access to the works and / or to the workshops, factories or other places where materials or equipments are being prepared or constructed for the work and also to any place where the materials are lying or from where they are being obtained, and the contractor shall extend necessary facility to the Employer or their representatives for inspection examination and testing of the quality & workmanship of the materials.

# 22. MATERIALS, WORKMANSHIP, SAMPLES, TESTING OF MATERIALS::

All the works specified and provided for in the specifications or which may be required to be done in order to perform and complete any part thereof shall be executed in the best and most workmanlike manner with materials of the best and approved quality of the respective kinds in accordance with the particulars contained in and implied by the specifications and as represented by the drawings or according to such other additional particulars, and instructions as may from time to time be given by the Employer during the execution of the work, and to his entire satisfaction. The works shall be executed with best workmanlike manner confirming to MNRE Guidelines, BIS Specifications, Indian Electricity Act & Rules, Statutory norms prescribed by local bodies like UHBVN/HAREDA / Electrical Inspectorate, Govt. of Haryana /Chandhigarh etc.

If required by the Employer, the contractor shall have to carry out tests on materials and workmanship in approved material testing laboratories or as prescribed by the Employer at his own cost to prove that the materials etc. under test conform to relevant I.S. Standards or as specified in the specifications. The necessary charges for sample material, transporting, testing etc. shall have to be borne by the contractor.

All materials must be the best of their kind available and the contractors must be entirely responsible for the proper and efficient carrying out of the work. Samples of all the materials to be used must be submitted to the Employer when so directed by the Employer.

Should the work be suspended by any reason, the contractor shall take all precautions necessary for the protection of work and at his own expenses shall make good any damages arising from any of these causes.

#### 23. REMOVAL OF IMPROPER WORK::

The Employer shall during the progress of the work have power to order in writing from time to time the removal from the work within such reasonable time or times as may be specified in the order of any materials which in the opinion of the Employer are not in accordance with specification or instructions, the

substitution or proper re-execution of any work executed with materials or workmanships not in accordance with drawings and specifications or instructions.

In case the contractor refuses to comply with the order the Employer shall have the power to employ and pay other agencies to carry out the work and all expenses consequent thereon or incidental thereto as certified by the Employer shall be borne by the contractor or may be deducted from any money due to or that may become due to the contractor.

#### 24. CONTRACTOR'S EMPLOYEES::

The contractor shall employ technically qualified and competent supervisors for the work who shall be available (By turn) throughout the work and shall participate during site meetings and be available to take and comply with instructions of the Employer. In case of electrical works as per statutory Acts & Rules of Electricity Board and Electrical Inspectorate, the persons so employed shall have the requisite supervisory permit or wireman permit for appropriate nature of work undertaken.

#### No Child Labour:

No labour below the age of eighteen years shall be employed on the work. In case of electrical works, the labour employed by the Contractor or their sub-contractor should be authorized person as permitted by the Chief Electrical Inspectorate office of the respective state Government. The Employer shall not be responsible for any deviation and the Contractors shall indemnify the Employer from any legal action or in any way directly or indirectly.

# **Labour Legislation::**

The Contractor shall comply with the provisions of the payment of Wages Act, 1936, Minimum Wages Act, 1948, Employees Liability Act, 1938, Workmen's Compensation Act, 1923, Industrial Disputes Act, 1947, Maternity Benefits Act, 1961, and the Contractors Labour (Regulation and Abolition) Act 1970, or the modifications thereof or any other laws relating thereto and the rules made there under from time to time.

The Contractor shall, notwithstanding the provisions of any contract to the contrary, cause to be paid fair wage to labour indirectly engaged on the work, including any labour engaged by his sub-contractors in connection with the said work, as if the labour had been immediately employed by him.

The Contractor shall indemnify and keep indemnified the Employer against payments to be made under and for the observance of the laws aforesaid and the Contractors' Labour Regulations without prejudice to his right to claim indemnify

from his sub-contractors. The laws aforesaid shall be deemed to be a part of this contract and any breach thereof shall be deemed to be a breach of this contract.

# **COMPLIANCE OF LABOUR REGULATIONS:**

- i) The Contractor shall at his own expense arrange for all the safety provisions for the safety of all workers and employees directly or indirectly employed on the work by the Contractor or his sub-contractors as mentioned in the Safety Code of this tender.
- ii) The Contractor shall be fully responsible for compliance at his own expense all the labour regulations and rules to be observed by him and his sub-contractors and by the Employer as Principal Employer of workers. The Contractor shall fully indemnify the Employer against any action by the state and/or Central Government for any default or alleged default by the Contractor, Sub-contractor of any of such rules and regulations. If, due to any default of the Contractor or his sub-contractors, the Employer has to incur any expenditure for compliance of the rules and regulations or for any other reason connected with such default, the Employer shall be entitled to recover from the Contractor all such expenditure in full from any payment due to the Contractor.

# 25. DISMISSAL OF WORKMEN::

The contractor shall on request of the Employer immediately dismiss or take of from the works any person employed thereon by him, who may in the opinion of the Employer be unsuitable or incompetent or who may misconduct himself. Such discharge shall not be the basis of any claim for compensation or damages against the Employer or any of their officers or employee.

#### **26. ASSIGNMENT ::**

The whole of the works included in the contract shall be executed by the contractor and the contractor shall not directly or indirectly transfer, assign or underlet the contract or any part, share or interest therein nor, change in constitution and no subletting shall relieve the contractor from the full and entire responsibility of the contract or from active superintendence of the work during their progress.

#### 27. DAMAGE TO PERSONS AND PROPERTY INSURANCE ETC ::

Damages to persons: The Contractor shall be responsible for all injury to the work or workmen to persons, animals or things and for all damages to the structural and/or decorative part of property which may arise from the operations or neglect of himself or of any sub-contractor or of any of his or a sub-contractors employees, whether such injury or damage arise from carelessness, accident or any other cause whatsoever in any way connected with the carrying out of this contract.

The clause shall be held to include inter-alia, any damages to buildings whether immediately adjacent or otherwise, and any damage to roads, streets, footpaths or ways as well as damages caused to the buildings and the works forming the subject of this contract by rain, wind or other inclemency of the weather.

The Contractor shall indemnify the employer and hold harmless in respect of all and any expenses arising from such injury or damages to persons or property as aforesaid and also in respect of any claim made in respect of injury or damage under any acts of compensation or damage consequent upon such claim.

Damages to property: The Contractor shall reinstate all damage of every sort mentioned in this clause, so as to deliver the whole of the contract works complete and perfect in every respect and so as to make good or otherwise satisfy all claims for damages to the property or third parties.

The Contractor shall effect the insurance necessary and indemnify the employer entirely from all responsibility in this respect. The insurance must be placed with a company approved by the employer and must be effected jointly in the name of the contractor and the employer and the policy lodged with the latter. The scope of insurance is to include loss or damage to the work and workmen due to carelessness, accident including fire, earthquake, floods, etc., damage or loss to the contract itself till this is made over a complete state. Insurance is compulsory and must be effected from the very initial stage. The contractor shall also be responsible for anything which may be excluded from damage to any property arising out of incidents, negligence or defective carrying out of this contract.

The employer shall be at liberty and is hereby empowered to deduct theamount of any damages, compensations, costs, charges and expenses arising or occurring from or in respect of any such claim or damages from any sums due or to become due to the contractor.

If the Contractor or his working people or servants shall break, deface, injure or destroy any part of building in which they may be working, or any building, road, road curb, fence, enclosure, water pipe, cables, drains, electrical cables or telephone post or wires, trees, grass or grass land, or cultivated ground contiguous to the premises on which the work or any part is being executed, or if any damage shall happen to the work while in progress, from any cause whatever or if any defect, or other faults appear in the work within twelve months after a certificate final or otherwise or its virtual

completion shall have been given by the Employer as aforesaid arising out of defect or improper materials or workmanship the Contractor shall upon receipt of a notice in writing on that behalf make the same good at his own expense or in default the Employer/Engineer-in-Charge cause the same to be made good by other workmen and deduct the expense from any sums that may be then or at any time thereafter may become due to the Contractor, or from his security deposit, or the proceeds of sale thereof or of a sufficient portion thereof.

## i) TRANSIT INSURANCE ::

Wherever specifically agreed to, the firm will insure at his cost the goods for all transit risks including 60 days storage risk from the date of the delivery of the goods at the final destination.

#### **INSURANCE:**

In his own interest the contractor shall insure the works and keep them insured until the virtual completion of the contract against loss or damages by fire and/or earthquake, flood. The insurance must be placed with a company approved by the Employer, in the joint names of the employer and the contractor for such amount and for any further sum if called to do so by the employer and lodge receipts of premiums paid with the employer within 21 days from the date of issue of letter of acceptance unless otherwise instructed.

Contractor shall strictly follow labour laws in force and obtain the necessary license for doing the work. He will be required to take care of the safety & security of the personnel employed and occupants of the flats, third parties, office equipments, building and other loose furniture's within the working area, during execution of the works. Contractor will be required to obtain Insurance policy "Erection All Risk Policy (EAR)" for the entire duration of the works till settlement of final bills as per clause 27 of this contract document. Any damage to the articles, building shall be made good by the contractor at his cost.

The contractor in case of rebuilding or reinstatement after fire shall be entitled to extension of time for completion as the employer may deem fit.

#### 28. ACCOUNTS RECEIPTS & VOUCHERS::

The contractor shall, upon the request of the Employer furnish them with all the invoices, accounts, receipts and other vouchers that they may require in connection with the works under this contract. If the contractor shall use materials less than what is required under the contract, the value of the difference in the quantity of the materials that was required to use and that actually used shall be deducted from his dues. The decision of the Employer shall be final and binding on the contractor as to the amount of materials the contractor is required to use for any work under this contract.

#### 29. MEASUREMENT::

Before taking any measurement of any work the contractor shall give reasonable notice to the representatives of the Employer or the site engineer if any, and measurements particularly concealable in nature shall be jointly taken and recorded and such statement of measurement shall be enclosed along with the bill or running bills. In the event of such measurement taken directly by the contractor the details shall be recorded and routes be marked for inspection of the engineer-in-charge.

Any deviation or discrepancies observed by the engineer-in-charge shall be brought to the notice of the contractor or their representatives and during such inspection and measurement if the contractor fails to be present the certification of the engineer-in-charge shall be final and binding on the contractor and the contractor shall have no right to dispute the same.

## **30. PAYMENT TERMS, ADVANCE PAYMENT & ITS RECOVERY::**

Payment Terms:

- i). All bills shall be prepared by the contractor in the form agreed or furnished by the Employer.
- ii). No mobilization advance amount will be paid to the firms. Payments to the contractor will be regulated as below:
- a) 65 % of the cost of equipments against supply / delivery of equipments at site, duly unpacked and supported by necessary documents / test certificates etc, and certification of Engineer in charge.
- b) 35 % upon installation, commissioning, testing, successful trial run including grid synchronization along with supply and installation of net metering, generation meter and approvals from Electrical Inspectorate and M/s UHBVN/HAREDA as required.
- (iii) All such interim payments accepted by the Contractor shall be regarded as payments by way of advances against final payment only. These shall not preclude bad, unsound and imperfect or unskilled work to be rejected, removed, taken away and reconstructed or re-erected.
- (iv)All such payments are subject to deductions of security deposit/retention money as detailed in the tender elsewhere.

Any certificate given by the Engineer-in-charge relating to the work done or materials delivered forming part of such payment, may be modified or corrected by any subsequent such certificate(s) or by the final certificate and

shall not by itself be conclusive evidence that any work or materials to which it relates is/are in accordance with the contract and specifications.

Any such interim payment, or any part thereof shall not in any respect conclude, determine or affect in any way powers of the Engineer-in-charge/employer under the contract or any of such payments be treated as final settlement and adjustment of accounts or in any way vary or affect the contract.

Pending consideration of extension of date of completion interim payments shall continue to be made as herein provided.

All the payments, interim or otherwise other than the initial advance, are subject to statutory deductions of Income Tax & its Surcharge, Sales tax deductions as notified by respective Local State Government/Authority and any such instructions conveyed from time to time. From the interim bills, the retention money as detailed elsewhere in this tender shall also be deducted.

The final bill shall be submitted by the contractor within 1 (one) month from the date of completion of work or from the date of certification of virtual completion certified by the branch-in-charge.

#### FINAL PAYMENT::

- (1) The Contractor shall submit the final bill in the same manner as specified in interim bills within one month of physical completion of the work or within 15 days of the date of the final certificate of completion furnished by the Engineer-in-Charge whichever is earlier. No further claims shall be made by the Contractor after submission of the final bill or on acceptance of the final payment and these shall be deemed to have been waived and extinguished.
- (2) In the event of any dispute, payments of those items of the bill in respect of which there is no dispute and of items in dispute, for quantities and rates as approved by Engineer-in-Charge, shall be made by the employer within the period specified herein under, the period being reckoned from the date of receipt of the bill by the Engineer-in-Charge.
  - a) If the gross amount of the work done under the contract items, plus that of additional deviated items is upto Rs. 2 lakhs 30 days.
  - b) do exceeds Rs. 2 lakhs & is upto Rs.20 lakhs 45 days
  - c) do exceeds Rs.20 lakhs /- 60 days

#### 31. VARIATION / DEVIATION::

The Engineer-in-Charge with the specific approval of the Employer shall have power to make alteration in, omissions from, additions to or substitutions for

the original specifications, drawings, designs and instructions that may appear to him to be necessary or advisable during the progress of the work, and the Contractor shall be bound to carry out the works in accordance with any instructions given to him in writing signed by the Engineer-in-Charge. Such alterations, omissions, additions or substitution shall form part of the contract as if originally provided therein and any altered, additional or substituted work which the Contractor may be directed to do in the manner specified above as part of the works, shall be carried out by the Contractor on the same conditions in all respects including Price on which he agreed to do the main work except as hereafter provided.

- (a) No work which radically changes the original nature of the contract shall be ordered by the Engineer-in-Charge as a deviation.
- (b) In the event of any deviation being ordered which in the opinion of the Contractor changes the original nature of the Contract, he shall within fifteen days of having been so ordered bring this to the notice of the Employer with the reasons but nevertheless carry it out and the disagreement as to the nature of work and the rate to be paid therefore shall be resolved in accordance with Clause under caption "SETTLEMENT OF DISPUTES AND ARBITRATION".
- c). The tendered rates, shall hold good for any increase or decrease in the tendered quantities up to variation of 15 % and as stipulated elsewhere for legitimate completion of works as per original design or scope of work and on account of any modification or alteration suggested and where the variation is for the respective item is beyond 15 %, the rate for the respective item may be reviewed on mutually agreed terms.

## 32. SUBSTITUTION::

Should the contractor desire to substitute any materials and workmanship, He must obtain the approval of the Employer in writing for any such substitution well in advance. In respect of Materials whose makes are not specified in the tender, specific approval of the Employer has to be obtained in writing before their usage.

## 33. PREPARATORY WORK FOR UTILISATION OF THE FACILITY AFTER COMPLETION:

The whole of the work will be thoroughly inspected by the contractor and deficiencies and defects set right. On completion of such inspection the contractor shall inform the Employer that they have completed the work and it is ready for inspection.

On completion the contractor shall clean all the area and its surroundings, equipments etc. and will leave the entire area clean and ready for immediate usage to the satisfaction of the Employer.

#### **34. CLEARING SITE ON COMPLETION::**

On completion of the works the contractor shall clear away and remove from the site all constructional materials, plant & equipments, tools, surplus materials, scraps, rubbish and temporary works of every kind and leave the whole of the site and the works clean and in a workmanlike condition to the satisfaction of the Employer.

In the event of failure to clear the site as required the Employer have the right to undertake the same engaging other agency and the same shall be at the cost of the contractor and liable for deductions in the payments due to the contractor and the contractor shall not dispute such payments.

#### 35. CONCEALED WORKS ::

The contractor shall give due notice to the Employer wherever any work is to be buried or concealed in the building in the earth, flooring, walls or otherwise becoming inaccessible later on, in order that the work may be inspected and correct dimensions or measurements taken before such burial. In default whereof the same shall, in the opinion of the Employer be either opened up for measurement at the contractors expenses or no payment may be made for such materials. Should any dispute or difference arise after the execution of any work as to measurements etc. or other matter which cannot be conveniently tested or checked, the notes / certification of the Engineer-in-charge shall be accepted as correct and binding on the contractor.

#### 36. ESCALATION ::

The rate quoted shall be firm throughout the tenure of the contract (including extension of time, if any granted) and will not be subject to any fluctuation due to increase in cost of materials, labour, sales tax, octri etc. unless specifically provided in these documents.

## 37. IDLE LABOUR::

Whatever the reasons may be, no claim for idle labour, additional establishment cost of hire and labour charges of tools and plants would be entertained under any circumstances.

#### 38. SUSPENSION OF WORKS::

Subject to other provisions contained, the Employer may without prejudice to his any other rights or remedy against the Contractor in respect of any delay

- in commencing, completing or during the progress of work or inferior workmanship, may serve notice in writing absolutely determine and cancel the contract in any of the following cases;
- i) If the contractor having been given by the Employer a notice in writing to rectify, reconstruct or replace any defective work or that the work is being performed in any inefficient or otherwise improper or un-workman like manner shall comply with the requirement of such notice for a period of seven days thereafter.
- ii) If the contractor being a company shall pass a resolution or the court shall make an order that the company shall be wound up or if a receiver or a manager on behalf of a creditor shall be appointed or if circumstances shall arise which entitle the court or the creditor to appoint a receiver or a manager or which entitle the court to make a winding up order.
- iii) If the contractor has without reasonable cause failed to commence the work or has suspended the progress of the work or has failed to proceed with the work with due diligence so that in the opinion of the Employer (which shall be final and binding) he will be unable to secure completion of the work by the date for completion and continues to do so after a notice in writing of seven days from Employer.
- iv) If the contractor fails to complete the work within the stipulated date or items of work with individual date of completion, if any stipulated, on or before such date (s) of completion and does not complete them within the period specified in a notice given in writing in that behalf by the Engineer-in-charge.
- v) If the contractor persistently neglects to carry out his obligations under the contract and/or commits default in complying with any of the terms and conditions of the contract and does not remedy it or take effective steps to remedy it within 7 days after a notice in writing is given to him in that behalf by the Engineer-in-charge.
- vi) If the contractor commits any acts mentioned in terms of tender hereof: And when the contractor has made himself liable for action under any of the cases aforesaid, the Employer shall have powers ::
- a) To determine or rescind the contract of which termination or rescission notice in writing to the contractor under the hand of the Employer shall be conclusive evidence. Upon such determination or rescission, the security deposit

of the contractor shall be liable to be forfeited and shall be absolutely at the disposal of Employer.

b) In any such event the contractor shall have no claim to compensation for any loss sustained by him by reason of his having purchased or procured any materials or entered into any engagements or made any advances on account or with a view to the execution of the work or the performance of the contract. And in case action is taken under any of the provisions aforesaid, the contractor shall not be entitled to recover or be paid any sum for any work thereto or actually performed under this contract unless and until the Engineer-in-charge has certified in writing the performance of such work and the value payable in respect thereof and he shall only be entitled to be paid the value so certified; Provided further that any of the recoveries to be made when the excess cost incurred by the Employer is more than the Security Deposit to be forfeited, such recoveries shall be limited to the amount by which the excess cost incurred exceeds the Security deposit so forfeited.

In any case in which any of the powers conferred upon the Employer hereof, shall have become exercisable &the same shall not be exercised, the non-exercise thereof shall not constitute a waiver of any of the conditions hereof and such powers shall notwithstanding be exercisable in the event of any future case of default by the contractor and the liability of the contractor for compensation shall remain unaffected.

#### 39. TERMINATION OF CONTRACT BY EMPLOYER ::

If the contractor::

- (a) at any time makes default in proceeding with the works or any part of the work with due diligence and continues to do so after a notice in writing of 7 days from the Engineer-in-Charge; or
- (b) commits default in complying with any of the terms and conditions of the Contract and does not remedy it or take effective steps to remedy it within 7 days after a notice in writing is given to him in that behalf by the Engineer-in-Charge; or
- (c) fails to complete the works or items of work with individual dates of completion, on or before the date(s) of completion, and does not complete them within the period specified in a notice in writing is given to him in that behalf by the Engineer-in-Charge; or
- (d) shall offer or give or agree to give to any person in Bank service or to any other person on his behalf any gift or consideration as an inducement or

reward for favoring him in relation to the obtaining or execution of this or any other Contract for the Employer or;

- (e) shall enter into a Contract with the Bank in connection with which commission has been paid or agreed to be paid by him or his knowledge, unless the particulars of any such commission and the terms of payment thereof have been previously disclosed in writing to the Accepting Authority/Engineer-in-Charge; or
- (f) shall obtain a Contract with the Employer as a result of wrong tendering or other unethical methods of competitive tendering; or
- (g) being an individual, or in a firm, any partner thereof shall at any time be adjudged insolvent or have a receiving order or order for administration of his estate made against him or shall take any proceedings for liquidation or composition (other than a voluntary liquidation for the purpose or amalgamation or reconstruction) under any Insolvency Act for the time being in force or make any conveyance or assignment of his effects or composition or arrangement for the benefit of his creditors or purport so to do, or if any application be made under any Insolvency Act for the time being in force for the sequestration of his estate or if a trust deed be executed by him for benefit of his creditors; or
- (h) being a company, shall pass a resolution or the Court shall make an order for the winding up of the company or a receiver or manager on behalf of the debenture holders or others shall be appointed or circumstances shall arise which entitle the Court or debenture holders to appoint a receiver or manager; or
- (i) shall suffer an execution being levied on his goods and allow it to be continued for a period of 21 days; or
- (j) assigns, transfers, sublets (engagement of labour on a piece-work basis or of labour with materials not to be incorporated in the work, shall not be deemed to be subletting) or otherwise parts with or attempts to assign, transfer sublet or otherwise parts with the entire works or any portion thereof without the prior written approval of the Accepting Authority;

The Accepting Authority may, without prejudice to any other right or remedy which shall have accrued or shall accrue thereafter to the Employer, by a notice in writing cancel the contract as a whole or only such of items in default from the Contractor.

The Engineer-in-Charge shall on such cancellation by the accepting authority have powers to, for which the contractor shall hereby unconditionally agree ::

- (a) to take possession of the Site and any materials, constructional plant, implements, stores, etc., thereon; and/or
- (b) to carryout the incomplete work by any means at the risk and cost of the Contractor.

On cancellation of the Contract in full or in part, the Engineer-in-Charge shall determine what amount, if any, is recoverable from the contractor for completion of the works or part of the Works or in case the Works or part of the Works is not to be completed, the loss or damage suffered by the Employer. In determining the amount, credit shall be given to the contractor for the value of the work executed by him up to the time of cancellation, the value of contractor's materials taken over and incorporated in the work.

Any excess expenditure incurred or to be incurred by the Employer in completing the Works or part of the Work or the excess, loss or damages suffered or may be suffered by the Employer as aforesaid after allowing such credit shall without prejudice to any other right or remedy available to Employer in law be recovered from any money due to the Contractor on any account, and if such moneys are not sufficient the Contractor shall be called upon in writing and shall be liable to pay the same within 30 days.

If the Contractor shall fail to pay the required sum within the aforesaid period of 30 days, the Engineer-in-Charge with the approval of the Employer shall have the right to sell any or all of the Contractor's unused materials, constructional plant, implements, temporary buildings, etc. and apply the proceeds of sale hereof towards the satisfaction of any sums due from the Contractor under the Contract and if thereafter there be any balance outstanding from the Contractor, it shall be recovered in accordance with the provisions of the Contract.

Any sums in excess of the amounts due to the Employer and unsold materials, constructional plant, etc., shall be returned to the Contractor, provided always that if cost or anticipated cost of completion by the Employer of the Works or part of the Works is less than the amount which the Contractor would have been paid had he completed the Works or part of the Works, such benefit shall not accrue to the Contractor.

#### **40. SETTLEMENT OF DISPUTES AND ARBITRATION ::**

It shall be an inseparable part of the contract that in matters regarding quality of materials, workmanship, removal or rejection of improper work, interpretation of the drawings and specifications, measurements of materials and/or items of work, mode of procedure and carrying out of the work, the decision of the Engineer-in-Charge which shall be given in writing, shall be final, conclusive and binding on the Contractor.

- 40.1(A). If the Contractor considers any work demanded of him to be outside the requirements of the contract, or considers any drawings record or decision given in writing by the Engineer-in-Charge on any matter in connection with or arising out of the contract or carrying out of work, to be unacceptable, he shall promptly within 15 days request the Employer in writing for written instruction or decision. Thereon, the Employer shall give his written instructions or decision within a period of two months from the receipt of the Contractor's letter.
- (B) Upon receipt of such written instructions or decision the Contractor shall promptly proceed without delay to comply with such instructions or decisions. If the Employer fails to give his instructions or decision in writing within a period of two months after being requested or if the Contractor is dissatisfied with the instructions or decision of the Employer, the Contractor may within 30 days appeal to the designated Appellant Authority of the Employer who shall afford an opportunity to the Contractor to be heard and to offer evidence in support of his appeal. If he is dissatisfied with this decision, the Contractor shall within a period of thirty days from receipt of the Appellant Authority of the decision shall indicate his intention to refer the dispute to Arbitration, failing which the said decision shall be final and conclusive and not referable to adjudication by the Arbitrator.

All disputes or differences in respect of which decisions have not been final, binding and conclusive as above shall be referred for adjudication by the arbitration by a Sole Arbitrator appointed as follows:

Within one month of receipt of notice from any party to the contract for appointment of the Arbitrator the Appellant Authority, in charge of the work at the time of such appointment shall send to the Contractor a panel of three names of persons who shall not presently be connected with the work. The Contractor shall within fifteen days of receipt of this list select and communicate to the Appellant Authority the name of one person from the list who shall then be appointed as the sole arbitrator by the Appellant Authority.

If Contractor fails to communicate his selection of name, within the stipulated period, the Appellant Authority shall without delay select one person from the list

and appoint him as Sole Arbitrator. If the Appellant Authority fails to send such a list within one month as stipulated, the Contractor shall send a similar list to the Appellant Authority within 15 days. The Appellant Authority shall then select one person from the list and appoint him as the Sole Arbitrator within 30 days of the receipt of the list. If the Appellant Authority fails to do so the Contractor shall communicate to the Appellant Authority the name of one officer from the list who shall then be the Sole Arbitrator.

If the Arbitrator so appointed is unable or unwilling to act or resigns his appointment or vacates his office due to any reason whatsoever another sole Arbitrator shall be appointed in the manner aforesaid. Such person shall be entitled to proceed with the reference from the stage at which it was left by his predecessor.

It is term of this contract that the party invoking arbitration shall give a list of disputes with amounts claimed in respect of each such dispute along with the notice for appointment of arbitrator and giving reference to the rejection by the Appellant Authority of the appeal and a copy of his notice(s) of intention to refer the dispute to arbitration of such disputes as mentioned in Part (ii) above failing which the notice for appointment of the Arbitrator shall not be treated as notice for appointing the arbitrator.

It is also a term of this contract that no person other than a person appointed by Appellant Authority, in charge of the work as aforesaid should act as arbitrator and if for any reason that is not possible, the matter shall not be referred to arbitration at all.

It is also a term of the contract that if the Contractor does not make any demand for appointment of arbitration in respect of any claims in writing as aforesaid within 90 days of receiving the intimation from the Employer that the final bill is ready for payment, the claim of the contractor shall be deemed to have been waived and absolutely barred and the Employer shall be discharged and released of all liabilities under the contact in respect of these claims. No party shall be entitled to bring any claim to arbitration if the arbitrator has not been appointed before the expiry of sixty days after defect liability period.

The arbitration shall be conducted in accordance with the provisions of the Indian Arbitration Act, 1996, or any statutory modification or re-enactment thereof and the rules made there under and for the time being in force shall apply to the arbitration proceeding under this clause.

The arbitrator may from time to time with the consent of the parties enlarge the time for making and publishing the award.

It is also a term of the contract that any fees TA, DA and other charges are payable to the Arbitrator shall be paid by both the parties equally.

It is also a term of the contract that the Arbitrator shall be deemed to have entered on the reference on the date of first hearing. The venue of the arbitration shall be such a place as may be fixed by the Arbitrator in his sole discretion. The fees, and charges of the Arbitrator shall, if required to be paid before the award is made and published, be paid half and half by each of the parties. The cost of the reference and of the award (including the fees, if any, of the Arbitrator) shall be in the discretion of the Arbitrator who may direct to and by whom and in what manner, such costs or any part thereof shall be paid and fix or settle the amount of costs to be so paid.

The award of the Arbitrator shall be final and binding on both the parties

## 41. RIGHT TO AUDIT/TECHNICAL EXAMINATION::

The Employer shall have the right to cause an audit and technical examination of the works and the final bills of the contractor including all supporting vouchers, abstract, etc., to be made even after payment of the final bill and if as a result of such audit and technical examination any sum is found to have been overpaid in respect of any work done by the Contractor under the contract or any work claimed to have been done by him under the contract and found not to have been executed, the Contractor shall be liable to refund the amount of over-payment and it shall be lawful for the Employer to recover the same from him in the manner prescribed in clause 47 or in any other manner legally permissible and if it is found that the Contractor was paid less than what was due to him under the contract in respect of any work executed by him under it, the amount of such under payment shall be duly paid by the Employer to the without any interest thereon; Provided that the Contractor shall not be entitled to payment of any sum paid short where such payment has been agreed upon between the Employer on the one hand and the Contractor on the other under any term of the contract permitting payment for work after assessment by the Engineer-in-Charge.

#### 42. LIEN ::

(a) Whenever any claim or claims for payment of a sum of money arises out of or under the contract against the contractor, the Employer shall be entitled to withhold and also have a lien to retain such sum or sums in whole or in part from the security, if any deposited by the Contractor and for the purpose aforesaid, the Employer shall be entitled to withhold the security deposit, if any, furnished as the

case may be and also have a lien over the same pending finalization or adjudication of any such claim. In the event of the security being insufficient to cover the claimed amount or amounts or if no security has been taken from the contractor, the Employer shall be entitled to withhold and have a lien to retain to the extent of such claimed amount or amounts referred to above, from any sum or sums found payable or which may at any time thereafter become payable to the contractor under the same contract or any other contract with the Employer pending finalization or adjudication of any such claim.

- (b) Any sum of money due and payable to the contractor (including the security deposit returnable to him) under the contract may be withhold or retained by way of lien by the Employer or any other contracting person or persons through Engineer-in-Charge against any claim of the Employer or such person or persons in respect of payment of a sum of money arising out of or under any other contract made by the contractor with the Employer or with such other person or persons.
- (c) It is an agreed term of the contract that the sum of money or moneys so withheld or retained under the lien referred to above by the Employer will be kept withheld or retained as such by the Employer till the claim arising out of or under the contract is determined by the arbitrator (if the contracts governed by the arbitration clause) or by the competent court, as the case may be and that the Contractor will have no claim for interest or damages whatsoever on any account in respect of such withholding or retention under the lien referred to above and duly notified as such to the Contractor. For the purpose of this clause, where the Contractor is a partnership firm or a limited company, the Employer shall be entitled to withhold and also have a lien to retain towards such claimed amount or amounts in whole or in part from any sum found payable to any partner/limited company as the case may be, whether in his individual capacity or otherwise.

#### 43. EXTERNAL INSPECTION & AUDIT :-

- (i) All works under or in course of execution or executed in pursuance of the Contract shall at all times be open and accessible to the inspection of the Quality Control Organization of the Employer or any designated auditor / officials of the Employer and of the Chief Technical Examiner's Office under Central Vigilance Commission.
- (ii) If it shall appear to the Engineer-in-Charge or to the Engineer in charge of Quality Control or any designated auditors / officials of the Employer or to the Chief Technical Examiner, that any work has been executed with unsound, imperfect, or unskillful workmanship, or with materials or articles provided by him for the execution of the work which are unsound or of a quality inferior to

that contracted or otherwise not in accordance with the contract, the contractor shall, on demand made in writing within the defect liability period from the Engineer-in-Charge specifying the work, materials or articles complained of notwithstanding that the same may have been passed, certified and paid for earlier, forthwith rectify, or remove and reconstruct the work so specified in whole or in part, as the case may require and provide other proper and suitable materials or articles at his own charge and cost.

- (iii) In the event of the contractor failing to do so within a period specified by the Engineer-in-Charge in his demand aforesaid, the contractor shall be liable to pay compensation at the same rate as under the clause of defects after completion for this default.
- (iv) In such case the Engineer-in-Charge may not accept the item of work at the rates applicable under the contract but may accept such items at reduced rates as the Employer or the competent authority may consider reasonable during the preparation of on account bills or final bill if the item is so acceptable without detriment to the safety and without substantially affecting the utility of the item and the structure or he may reject the work outright without any payment and/or get it and other connected and incidental items rectified, or removed and re-executed at the risk and cost of the contractor. Decision of the Engineer-in-Charge to be conveyed in writing in respect of the same shall be final and binding on the Contractor.

SIGNATURE OF CONTRACTOR WITH SEAL

#### **SAFETY CODE**

## Safety Norms to be followed by the Contractor

## 1. Safety Clause

- i) The contractor should take all precautionary measures in order to ensure the protection of his own personnel moving about or working on the bank premises, and should conform to the rules and regulations of the bank.
- ii) The Contractor should abide by all bank regulations in force from time to time and ensure that the same are followed by his representatives, agents or sub contractors or workmen.
- iii) The contractor should ensure that unauthorized, careless or inadvertent operation of installed equipment which may result in accident to staff and / or damage to equipment does not occur.
- iv) The Contractor should indemnify and keep the purchaser indemnified and harmless against all actions, suits, claims, demands costs charges or expenses arising in connection with any accident, death or injury, sustained by any person or persons within the bank premises and any loss or damage to bank property sustained due to the acts or omissions of the contractor irrespective of whether such liability arises under the workmen's compensation act or the fatal accidents act or any other statute in force from time to time.

## 2. EMS Requirements

- i) The contractor shall ensure industrial safety methods in executing his work at bank premises.
- ii) The contractor shall ensure that all wastes generated by his activities / work are moved to the respective dump sites or taken for re-cycling.
- iii) The contractor has to give prior information whether any hazardous chemical is used in his work and if so, the operational control to be exercised.
- iv) The contractor has to ensure that all his material handling equipments / transport vehicles are emission tested.
- v) The contractor has to ensure that his activities are in tune with the Canara Bank EMS Policy (to be incorporated as part of Contract)
- vi) The contractors' staff shall be competent to operate emergency appliances like fire extinguishers.
- vii) The contractors' staff shall be competent in the areas wherein the contract is awarded by evaluating through skill matrix by concerned official

#### 3. OTHER SAFETY MEASURES

- i) Adequate and appropriate tools shall be issued.
- ii) The instruments are used to be conformed to Indian Standards.
- iii) Suitable scaffolds shall be provided for workmen for all works that cannot safely be done from the ground, or from solid construction except in the case

of short duration work, which can be done safely from ladders. When a ladder is used, it shall be of rigid construction made either of good quality wood or steel. The steps shall have a minimum width of 450 mm and a maximum rise of 300 mm. Suitable hand holds of good quality wood or steel shall be provided and the ladder shall be given an inclination not steeper than ¼ to 1 (¼ horizontal and 1 vertical).

- iv) Ensure adequate lighting at work place.
- v) Contractor should follow the terms and conditions/instructions of bank from time to time.
- vi) Activities other than the specified activities as per the contract clauses, which are assigned to contractor, are not permitted at the premises.
- vii) Ensure the Suitable guards are provided to the hand operating machine.
- viii) Suitable lifting machineries and tackles are to be used to handle the materials.
- ix) Any loss incurred to bank because of Contractor's activities shall be charged to their account.
- x) The equipment's & materials stored at our premises are at Contractor's own risk
- xi) Before start of work, proper shut down (if necessary) is to be undertaken for safety
- xii) Before start of any work, appropriate Work Permits shall be obtained.
- xiii)Off cuts and wastes generated during the course of work, must be suitably disposed identified areas.
- xiv) The contractor shall engage qualified supervisors at the work site whenever men are engaged for work.
- xv) First aid box with adequate medicine are to be provided in the work area.
- xvi) Disobeying or not following the conditions / precautions / procedures shall result in penalty. In serious cases, stoppage of work or cancellation of permits may be done.
- xvii) The display board containing the details of nature of work, maximum number of staff working per shift, period of work, site in charge name and phone number and main office phone numbers is to be placed at prominent place.
- xviii) Staffs under your control are to be insured during the work period.
- xix) All personnel of the contractor working within the plant site shall be provided with safety helmets. All welders shall wear welding goggles while doing welding work and all metal workers shall be provided with safety gloves. Persons employed on metal cutting and grinding shall wear safety glasses.
- xx) Adequate precautions shall be taken to prevent danger from electrical equipment. No materials on any of the sites of work shall be so stacked or placed as to cause danger or inconvenience to any person or the public.

#### 4. Demolition

Before any demolition work is commenced and also during the process of the work.

- i) All open areas adjacent to the work site shall either be closed or protected.
- ii) No electric cable or apparatus, which is liable to be a source of danger over a cable or apparatus used by the operator, shall remain electrically charged.
- iii) All practical steps shall be taken to prevent danger to persons employed from the risk so over loaded with debris or materials as to render it unsafe.

## 5. Personal Safety Equipment's

All necessary personal safety equipment as considered adequate by the Engineer should be kept available for the use of the person employed on the site and maintained in a condition suitable for immediate use, and the contractor should take adequate steps to ensure proper use of equipment by those concerned.

- i) Those engaged in welding works shall be provided with welder's protective eyesight lids.
- ii) Stonebreakers shall be provided with protective goggles and protective clothing and seated at sufficiently safe intervals.
- iii) When workers are employed in sewers and manholes, which are in use, the contractor shall ensure that the manhole covers are opened and are ventilated at least for an hour before the workers are allowed to get into manholes and the manholes so opened shall be cordoned off with suitable railing and provided with warning signals or boards to prevent accident to the public.
- iv) The contractor shall not employ men below the age of 18 years. Women of any age shall not be engaged for the work of painting with products containing lead in any form. Whenever men above the age of 18 years are employed on the work of lead painting the following precautions should be taken.
- v) Suitable facemasks should be supplied for use by the workers when paint is applied in the form of spray or a surface having lead paint dry rubbed and scraped.
- vi) Overalls shall be supplied by the contractor to the workmen and adequate facilities shall be provided to enable the working painters to wash during the cessation of work.
- vii) When the work is done near any public place where there is risk of accidents all necessary equipments should be provided and kept ready for use and all necessary steps taken for prompt rescue of any person in danger and adequate provision should be made for prompt first aid treatment of all injuries likely to be sustained during the course of the work.

- **6.** All the Indian Electricity rules 1956 on Electrical Safety should be strictly followed while execution of the Electrical works
- **7.** These safety provisions should be brought to the notice of all concerned by display on a notice board at a prominent place at work spot. The person responsible for compliance of the safety code shall be named therein by the contractor.

To ensure effective enforcement of the rules and regulations relating to safety precautions the arrangements made by the contractor shall be open to inspection by the Labour Officer, Engineers of the Department or their representatives.

Notwithstanding the above clause from (1) to (7), there is nothing in these to attempt the contractor from the operation of any other Act or Rule in force in the Republic of India.

SIGNATURE OF THE CONTRACTOR WITH SEAL

### **FORM OF AGREEMENT**

This agreement made thedayear 2018 BETWEEN, Canara Bank a body Banking Companies (Acquisiti 1970, having its Head office, 112, J C Road, constituted attorney (hereinafter referred to a PART; and	y corporate const on and Transfer of , Bengaluru) repre	tituted under the fundertakings Act, sented by its duly
*Sri	S/D/o	
resident ofof M/s	the	sole proprietor
of M/s	having	office at the
following address		
* M/s the administrative/principal office at Managing/duly authorised partner.	partnership firr repre	n having an sented by its
* M/s comp	pany/body corpor	rate incorporated
under the provisions of the Companies Act		
the following address	_	_
duly represented by its co	onstituted and au	thorized Managing
Director, Shriand (he		
term shall also be called the Supplier or the		
WHEREAS THE Employer / Bank is desirous Testing, Commissioning & Maintenance of ON-	- Grid Rooftop Sola	ar Power System in
004/2022 dated:/04/2022 and has beer terms and conditions as set out therein and in	•	Employer on the

### NOW THIS AGREEMENT WITNESSETH as follows:

- 1. In this agreement words and expression shall have the same meaningsas are respectively assigned to them in the conditions of contract hereinafter referred to.
- The following documents not inconsistent with these presents shall be deemed to form and be read and construed as part of this agreement viz;
- a) Notice inviting Tender
- b) General Rules and Instructions for the guidance of Contractors.
- c) Tender offer, Form of Agreement, Indemnity Bond format & Bank Guarantee format, if any, leading to and prior to acceptance letter.
- d) General Conditions of contract along with Annexure thereto.

- e) Safety Code
- f) Schedules A to C consisting of Technical Specifications, Special Conditions, Questionnaire, tender drawings if any, etc.
- g) Scope of Comprehensive AMC
- h) Schedule of quantities including Prices and tendered amount known as Price Bid.
- i) The details submitted in technical bid, design, technical brouchers, drawings and such other details etc.

[ Note : \* Strike off whichever is not applicable ]

Contractor, the carry out the On-Grid	ne Contractor Supply, Ins Rooftop	hereby of the stallation, Sol	Testing, Cor ar Po	d agrees v nmissionin ower	with the E g & Maint System	mployer to enance of in
respects and General Condi agreement.	subject to tions as also	all terms in the afor	and conditions resaid docume	ons/rules ents which	as mention shall from	ned in the part of this
In witness w					set their	respective
hands and sea	als the day an	d year firs	t above writte	en.		
Signed, Contractor,			delivered	•		said
		to the	e Employer_			in the
presence of:		to th	c Employer_			
			-			, III IS
			Sig	nature of	Contractor	(with seal)
			_		-	resentative Authority.
				, . ,		,
Witness (Sigr	nature, Name	& Address	s ):			
1).						
2)						

# FORMAT OF INDEMNITY BOND (TO BE SUBMITTED BY THE SUCCESSFUL CONTRACTOR IN STAMP PAPER)

THIS DEED OF INDEMNITY BOND is made on this day of month of year two thousand Twenty two(2022) By M/s duly represented by one of its partners, aged years, son of Sri, residing at
* M/sthe partnership firm having an administrative/principal office at represented by its Managing/duly authorised partner.
* M/s company/body corporate incorporated under the provisions of the Companies Act 1956 having its registered office at the following address, duly represented at duly represented by its constituted and authorised Managing Director, Shri and (hereinafter called the Contractor which term shall also be called the Supplier or the Contractor ) on the other part
Whereas My Firm/ Company was short listed for issue of tenders and my company became successful in securing the subject work through competitive tendering and the work of Supply, Installation, Testing, Commissioning & Maintenance of On-Grid Rooftop Solar Power System in has been awarded in favour of my Firm/ company by Canara Bank, Premises & Estate Section, Circle Office, Karnal.
And whereas for undertaking the furnishing work, my company has entered into contract agreement on 2022.
Now this Deed Witnessed that in pursuance of the aforesaid contract agreement dt2022 and in consideration of Canara Bank having agreed to make payments on the running bills claimed by my company based on the works completed by my company in respect of Supply, Installation, Testing, Commissioning & Maintenance of On-Grid Rooftop Solar Power System in
, and referred to above, I hereby undertake to indemnify and keep harmless the Canara Bank and its officials from any damages, prosecution, other legal suits and claims arising out of any mishaps occurring at the site due to faulty

work, faulty construction and for violating rules and regulations for which I shall be solely responsible.

[ Note : \* Strike off whichever is not applicable ]

### SIGNATURE OF CONTRACTOR WITH SEAL

## **BANK GUARANTEE FORMAT FOR EARNEST MONEY DEPOSIT**

To

WHEREAS	(Nar	me	of	Contrac	ctor)
(hereinafter called "the Contractor" has subr					
(Date) for t	he exec	ution	of (N	lame	of
Contract) (hereinafte	r called "t	he Ten	der")	in favou	r of
Canara Bank hereinafter called the "Employer"	;				
KNOW ALL MEN by these presents that we,		Bank,	a boc	dy corpo	rate
constituted under the Banking Compani	es (Acqu	uisition	& 7	Γransfer	of
Undertakings) Act, 1970 having its Head Office	e at				
amongst others a branch at	(herei	inafter	called	"the Ba	nk"
are bound unto the employer for the	sum o	f Rs_			
(Rupees		or	ıly)	for w	hich
payment well and truly to be made to the said	Employer	, the Ba	ınk bir	nds itself	, its
successors and assigns by these presents;					
THE CONDITIONS of this obligation are:					
(a) If the Contractor withdraws its Tender d	uring the	period	of Te	nder val	lidity
specified in the Tender; or	J	•			,
(b) If the Contractor having been notified of t	he accept	ance of	his Te	ender by	/ the
Employer during the period of Tender validity;	·			ĺ	
(i) Fails or refuses to execute the Agreeme	ent, if requ	uired; o	r		
(ii) Fails or refuses to furnish the performa	•	•		y Depos	it, in
accordance with clause					

We undertake to pay to the Employer up to the above amount upon receipt of his first written demand without the Employer having to substantiate his demand, provided that in his demand the Employer will note that the amount claimed by him is due to him owing to the occurrence of one or both of the two conditions,

specifying the occurred condition or conditions.

No	twiths	tanding ar	ything co	ntained	l herein,				
1)		liability				guarantee	shall	not	exceed
2)	The b	ank Guara	ntee is va	ılid up t	.0	and			
3)	guara before	ntee only	and only	if you s menti	serve upo on perio	unt or any pa on us a writte d of the Gu	n claim c	r dema	and on or
Da	ted		(	day of_			2	022	

**SIGNATURE OF THE BANK** 

## **BANK GUARANTEE FORMAT FOR SECURITY DEPOSIT**

Guarantee No Amount of Guarantee Rs Guarantee cover from Dated:
To Dated:
Last Date for Lodgement of claim:
To:
In consideration of
agreement dated (hereinafter called the "said Agreement") for the due fulfillment by the said obligator of the terms and conditions contained in the said agreement, on production of the Bank Guarantee for Rs (Rupees only), at the request of the obligator Bank, a body
corporate constituted under the Banking Companies (Acquisition & Transfer of undertakings) Act, 1970 having its Head Office at amongst others a branch at (hereinafter referred to as "the Bank") has agreed to give following guarantee in favour of the beneficiary for an amount not exceeding Rs
We, the Bank to hereby undertake to pay the amount payable under this guarantee without any demur merely on a demand from the beneficiary stating that the amount claimed is due by way of loss or damage caused to or would be caused to or suffered by reason or any breach of the terms and conditions contained in the said agreement or by reason of the obligator's failure to perform the said agreement. Any such demand in writing made on the Bank shall be conclusive as regards the amount due and payable by the Bank under the guarantee. However, our liability under this guarantee shall be restricted to an

We, the Bank further agree that the guarantee herein contained shall remain in full force and effect during the period that would be taken for the performance of

amount not exceeding Rs.....

the said agreement and that it shall continue to be enforceable till all the dues of the beneficiary under or by virtue of the said agreement have been fully paid and its claims satisfied or till the beneficiary certifies that the terms and conditions of the said agreement have been fully discharged this guarantee. Unless a demand for claim under this guarantee is made on us in writing on or before ................................... we shall be discharged from all liabilities under this guarantee thereafter.

We, the Bank further agree that the beneficiary shall have the fullest liberty, without consent and without effecting in any manner or obligations hereunder, to extend time of performance the said obligator(s) from time to time or to postpone for any time any of the powers exercisable by the beneficiary against the said obligator(s) and to forbear or enforce any of the terms and conditions relating to the said agreement and we shall not be relieved of our liability by reason of any extension being granted to the said obligator(s) for any forbearance, act or omission on the part of the beneficiary or any indulgence by the beneficiary to the said obligator(s) or by any such matter or thing whatsoever which under the law relating to sureties would not for this provision have effect of so relieving us.

We, the Bank lastly undertake not to revoke this guarantee during its currency except with the previous consent of the beneficiary in writing.

(i) Our liability under this Bank Guarantee shall not exceed Rs. ........

Notwithstanding anything contained herein:

DATE:

(Rup	pees	only)
(ii)	) This Bank Guarantee is valid upto	and
Bank Gu or before	e are liable to pay the guaranteed amount of a are liable to pay the guaranteed amount of a constant and a serve upon us ore (mention period of the guarant plus claim period)	a written claim or demand on
PLACE:		

**SIGNATURE** 

## Schedule- A SPECIAL INFORMATION TO THE CONTRACTORS

**1.** The Work has to be carried out at the following sites:

Place	Capacity	Contact Detail
Canara Bank, Circle Office Karnal, Bay Site	35kWp	P&E Section, Circle Office
17-18, Sector 12, Karnal – 132001,		Karnal, Bay Site 17-18, Sector 12,
Haryana		Karnal – 132001, Haryana
		Tel: 0184-4063657, 8572800777
Canara Bank Regional Office Panchkula,	25kWp	GA Section, Regional Office
SCO 904, NAC, Manimajra, Chandigarh-	-	Panchkula, SCO 904, NAC,
160101		Manimajra, Chandigarh- 160101
		Tel: 0172- 4730174, 9530903378

Contractors are advised to visit the sites, at their own expense and familiarize with site conditions before quoting.

Contractors are advised to go through the specifications and the schedule of work and clarify doubts if any, with the Bank's Engineer before quoting.

- 2. The contractor shall furnish full details of the materials he intends to use on the work like make, model no., printed literature/ catalogue showing all details, reference to any national/ international approvals etc. In case of any deviations from the specifications/ stipulations contained in the tender, the same shall be separately listed out by the contractor and enclosed with the tender (in technical bid). Failure to furnish the above details may result in rejection of tender summarily.
- 3. Warranty: The offer must include comprehensive on-site warranty (DLP) for a period of 1 year with free maintenance from the date of handing over of the solar power plant system. The offer must also include comprehensive AMC of 4 years from the date of completion of defect liability period. The firm shall be fully responsible for the warranty in respect of proper design, quality and workmanship of all equipments, accessories like covered by the offer. However the failure of the components due to other electrical faults will not be covered by the offer. The firm must warrant all equipments, accessories, spare parts etc., against any manufacturing defects during the warranty period. During the warranty period the firm shall maintain the equipment and repair/ replace all the defective components at the installed site at no additional charge of whatsoever nature to the Bank.

4. Relevant type/factory test certificates, data sheets shall be furnished in respect of Modules, Inverters, Cables and other related accessories etc.

SIGNATURE OF THE CONTRACTOR WITH SEAL

## Schedule B SPECIAL INSTRUCTIONS TO THE CONTRACTOR

- 1) This specification shall be read in conjunction with General conditions of contract as applicable for this project.
- 2) The Contractor shall design the equipment considering the site conditions. After award of contract no claim for extra payment will be entertained.
- 3) All Civil alteration works shall be provided by the Contractor. The equipment shall be designed keeping in view the provisions of the statutory regulations and safety codes in force in the locality of installation. All such minor civil works like chipping, grouting, drilling, etc for fixing mounting structure and other accessories are to be executed by the supplier.
- 4) The work should complete including testing & commissioning of solar power system within 60 days from the acceptance of work order by the Contractor including mobilization.
- 5) The following drawing/ documents shall be submitted for approval before commencement of work.
  - 1. Module test certificate from ETDC/any other Government test centers have to be produced on sample basis.
  - Contractor will submit his layout design for SPV module including its structural details to Engineer in Charge for approval prior to start of work.
  - 3. Design/Drawings of the mounting structure, the design for the mounting structure shall have the certification from a recognized Lab/Institution for the purpose.
  - 4. GA of ACDB, DCDB, Array Junction Box, Main Junction Box, Overall layout, cable routing layout, Module interconnection drawings, bill of materials etc., for approval.
- 6) The following drawings/ documents shall be submitted for records before handing over.
  - 1. As built drawings.
  - 2. A screen printed/laminated circuit and cabling diagram. The sameshould also be provided in the manual.
  - 3. Interconnection diagram of the modules of the panels on SPV 'module/panels shall also be provided for ready reference of the maintenance staff.
  - 4. Installation, Operation and Maintenance Manual. Regarding number of copies etc., refer to relevant articles.
- 7) In the Price Bid, the Contractor shall indicate Price for supply, Installation, testing, erection and commissioning of the SPV System. GST shall be paid extra by Bank. The quoted Price shall include charges on account of all taxes, duties, packing, forwarding, transport, insurance etc. The quoted Price shall

- remain firm and binding and shall not be subjected to any escalation whatsoever on any account during entire period of supply, installation, testing & commissioning.
- 7) SPV System shall be guaranteed for a period of 1 year of trouble free operation after commencement of regular operation and shall include free servicing, repair and replacement of parts by the Contractor.
- 8) Workmanship and performance warranty:
  - 1. The materials used shall be new and best of its kind available and shall conform to standards as mentioned in the technical specification.
  - 2. The supplier shall guarantee satisfactory performance of system as per relevant guidelines.
  - 3. The guarantee shall also cover faulty design/ materials/ workmanship. All rectification or replacement under guarantee shall be done by the supplier free of cost.
  - 4. The conditions regarding guarantee of equipment shall also be governed by the relevant clauses of general PRICE conditions.
- 9) The Contractor shall fill up the Price data sheet and submit in a separate cover along with the tender.
- 10) The Contractor shall furnish a Time Bar Chart showing breakup of time required for various activities viz., submission and approval of drawings, raw material procurement, engineering, various shop activities, order placement for bought out items and their delivery to shop, assembly, testing, inspection, dispatch, erection and commissioning.
- 11) The Contractor shall furnish the procedure proposed for conducting performance guarantee test; for review by Employer.
- 12) The Contractor shall ensure installation of all electrical equipment by approved licensed electrical Contractors and subsequent approval by electrical inspectorate and other competent authority, if necessary.
- 13) Packing: Packing and transportation of solar panels, Charge Controller, and Mounting Structure shall be made such that the equipment is not damaged, while transporting, loading and unloading.
- 14) Quality and Workmanship: All the units of the system shall be manufactured in accordance with international quality management systems ISO 9001-2000(or latest ISO), for which the manufacturer shall be duly accredited. A quality plan describing the quality assurance system followed by the manufacturer would be required to be submitted. The manufacturer shall

also be accredited for the compliance of ISO 14001 (latest issue) pertaining to environmental requirements. All wiring shall be neatly secured in position and adequately supported Metal panel or cover holes through which the wires or cables pass shall be bushed. All materials and workmanship shall be of professional quality to ensure the requirements.

#### SIGNATURE OF THE CONTRACTOR WITH SEAL

## Schedule C Technical Specifications of SPV Power Plant

#### TECHNICAL SPECIFICATIONS

#### SCOPE OF WORK:

The extent of the work shown and specified hereunder is defined to include all labour, materials, equipment, and supervision required for the design, fabrication, supply, installation, testing and commissioning of the complete solar power generation system, and subsequent upkeep and maintenance as defined.

Design, Supply, Installation, Testing & Commissioning and Maintenance for 4 years after completion of defect liability period of 1 year for ON- Grid Rooftop Solar Power System at

Place	Capacity
Canara Bank, Circle Office Karnal, Bay Site	35kWp
17-18, Sector 12, Karnal – 132001,	
Haryana	
Canara Bank Regional Office Panchkula, SCO 904, NAC, Manimajra, Chandigarh-	25kWp
160101	

including the following:

- 1. The solar power generated shall be utilized for consumer load and the surplus power to be fed into the grid.
- 2. Net- Metering and Grid connectivity of the roof top solar PV system under this scheme shall be in accordance with the prevailing guidelines of UHBVN /HAREDA etc. Obtaining permission from local authority, liaison and approval vests with the Contractor only. Any charges in this matter shall be borne by the Contractor. Application Charges, Statutory Charges against receipts shall be borne by the Bank.
- 3. In case of grid failure, the standby inverter shall create a captive grid and SPV power keeps feeding to this captive grid.
- 4. In case of low solar irradiation or cloudy weather, the deficit power is taken from the grid or DG.
- 5. System configuration must conform to Indian grid system (tt-n; 3-phase, neutral & earth).

The important Technical specification to be taken care during various stages like design, construction, commissioning and maintenance have been enumerated below.

#### 1. Solar Photo Voltaic Modules

- Solar photo voltaic module array shall consist of high efficiency Solar Modules utilizing Mono / Multi Crystalline high power Silicon Terrestrial Solar Photovoltaic cells.
- ii. Solar photovoltaic module capacity shall not be less than **400 Wp** at STC.

- iii. Solar module shall be laminated using lamination technology using established polymer (EVA) and Tedlar / Polyester laminate. Anti-reflection coating to be applied on cells to improve light absorption and to increase cell performance.
- iv. The modules shall be connected in suitable series / parallel combination to meet the voltage / current requirements of the Inverter units.
- v. Solar Photovoltaic module efficiency shall be minimum 15% and power tolerance shall be in the range of 0 to +3%. The temperature co-efficient of power for PV modules should be less than or equal to -0.45% per deg C.
- vi. The rated output power of any supplied module shall not have negative tolerance.
- vii. Module shall be made of high transmissivity glass front surface giving high encapsulation gain and hot butyl rubber edge sealant for module protection and mechanical support.
- viii. All materials used must have a proven history of reliable and stable operation in external outdoor applications.
- ix. Solar modules shall be designed to operate and perform in relative humidity up to 90% with temperatures between **-40 Deg C and +85 Deg C** and with stand gusts up to 200 km/h from back side of the panel.
- x. The Solar PV modules and production processes employed in the manufacture of the offered module shall be in accordance with the requirements of IEC 61215 Ed 2, IEC 61730 Part 1(Requirements for Construction) & Part 2(Requirements for Testing), IEC 61701 for operation in corrosive atmosphere.
- xi. SPV Modules shall be tested and approved by any one of the IEC authorized test centers. Test certificates can be issued by any of the NABL/BIS Accredited Testing/ Calibration Laboratories. Copy of the above Certifications along with I-V characteristics of all suitable modules as per specifications proposed to be used in the system must be provided along with offer. Undertaking from manufacturer / supplier that the modules being supplied are as per above shall also accompany the offer.
- xii. The module frame must be made of corrosion resistant materials, which is electrolytically compatible with the structural material used for mounting the module.
- xiii. Structure shall be designed to allow easy replacement of any module and in accordance with site conditions.
- xiv. Module Junction box shall of Flame proof / Explosion proof type be designed for long life outdoor operation in harsh environment and shall be IP 65 or better.
- xv. Degradation of power generated should not be exceeding 20% of the min. rated power over a 25 year period.
- xvi. Efficiency of solar PV system shall be guaranteed to 90% for up to 10 years & 80% for up to 25 years.

- xvii. The PV modules shall be equipped with bypass diode to minimize power drop caused by shades.
- xviii. The solar modules shall have suitable encapsulation and sealing arrangements to protect the silicon cells from the environment. The arrangement and the material of encapsulation shall be compatible with the thermal expansion properties of the Silicon cells and the module framing arrangement / material. The encapsulation arrangement ensures complete moisture proofing during life of the solar modules.
- xix. Each module must have low iron tempered glass front for strength and superior light transmission. It also must have tough multilayered back sheet for environment protection against moisture and high voltage electrical insulation.
- xx. The fill factor of modules shall not be less than 0.70.
- xxi. The Max. System Voltage of the modules used shall be 1000-V DC.
- xxii. Each PV module shall have an RF identification tag (RFID) fixed inside the module laminate, but able to withstand harsh environmental conditions, containing following information.
  - Name of manufacturer of PV Module
  - Name of manufacturer of Solar cells
  - Month & Year of manufacture (separately for Solar cells & module)
  - Country of origin (separately for Solar cells & module)
  - I-V Curve for the module
  - Peak wattage Im, Vm and FF for the module
  - Unique serial no. and model of the module
  - Date and year of obtaining IEC PV module qualification certificate
  - Name of the test lab issuing IEC certificate
  - Any other relevant information on traceability of solar cells and module as per ISO 9000 series.
- xxiii. Modules shall be North-South oriented.
- xxiv. MCB of suitable rating to be provided for connecting / disconnecting Solar array and PCU for maintenance purposes.
- xxv. The Solar PV Modules shall meet all the requirements of latest MNRE guidelines.

#### **Mechanical Features**

- Solar Photovoltaic Module shall be made of toughened, low iron content, high transmissivity front glass.
- Anodized Aluminum Frame shall be provided around the module.
- The module shall be encapsulated with Ethyl Vinyl Acetate (EVA).
- Silicon edge sealant shall be provided around laminate.
- The back surface shall be Tedlar /Polyester trilaminate.
- Weather proof (IP 65) terminal box shall be provided for the module output terminations.
- The module shall be Resistant to water, abrasion, hail impact, humidity & other

environmental factors for the worst situation at site.

- Bypass diode arrangement shall be provided.
- All nuts and bolts shall be made of very good quality stainless steel (SS 304 minimum)

## Marking

Each module shall carry the following clear indelible markings as minimum:

- Name, monogram of manufacturer
- Type or module number
- Module serial number
- Polarity of terminals
- Maximum system voltage for which module is designed
- Date and place of manufacture

## 2. Module Mounting Structure

- i. Module Mounting Structure should be as per MNRE specifications and supply & installation shall be in scope of contractor.
- ii. The structure shall be designed in accordance with the latitude of the place of installation. The array mounting structure shall be designed to allow easy replacement of any module and shall be in line with site requirement. Structure shall be designed for simple mechanical and electrical installation. It shall support SPV modules at a given orientation, absorb and transfer the mechanical loads to the ground properly.
- iii. The array structure shall have tilt arrangement to adjust the plane of the solar array for optimum tilt.
- iv. The array structure shall be made of hot dip galvanized MS angles/anodized aluminum of size not less than 50 mm x 50 mm x 6 mm size. The minimum thickness of galvanization shall be at least **120 microns.** All nuts & bolts shall be made of very good quality stainless steel. The minimum clearance of the lowest part of the module structure and the developed ground level shall not be less than 500 mm.
- v. Leg assembly of module mounting structure made of different diameter galvanized tubes are accepted. The work should be completed with supply, fitting fixing of clamps, saddles, nut & bolts etc. While quoting the rate, the contractor may mention the design & type of structure offered. All nuts & bolts shall be made of very good quality stainless steel.
- vi. The array structure shall be so designed that it will occupy minimum space without sacrificing the output from SPV panels at the same time it will withstand wind speed up to maximum of 200 km/hr.
- vii. The contractor shall specify installation details of the PV modules and the support structures with appropriate diagrams and drawings after receiving the offer.
- viii. The structure layout drawings along with shading calculation and detailed design shall be submitted to banker for approval after receiving the offer.

- ix. PCC ARRAY FOUNDATION BASE: The legs of the structures made with GI angles will be fixed and grouted in the PCC foundation columns made with 1:2:4cement concrete. The minimum clearance of the lowest part of any module structure shall not be less than 500 mm from ground level. While making foundation design, due consideration shall be given to weight of module assembly, maximum wind speed of 200 km/hr and seismic factors for the site.
- x. The contractor can visit the site before quoting the rate for civil works. After taking in to consideration all aspects of the site, condition of roof etc., the contractor shall quote for civil works. No extra claim shall be entertained at post project stage.
- xi. The foundation design of module structure design shall be submitted to banker for approval. The work will be carried out as per designs approved by bank. The contractor shall specify installation details of the PV modules and the support structures with appropriate diagrams and drawings. Such details shall include, but not limited to, the following;
  - 1. Determination of true south at the site;
  - 2. Array tilt angle to the horizontal, with permitted tolerance;
  - 3. Details with drawings for fixing the modules;
  - 4. Details with drawings of fixing the junction/terminal boxes;
  - 5. Interconnection details inside the junction/terminal boxes;
  - 6. Structure installation details and drawings;
  - 7. Electrical grounding (earthing);
  - 8. Inter-panel/Inter-row distances with allowed tolerances; and
  - 9. Safety precautions to be taken.
- xii. The array structure shall support SPV modules at a given orientation and absorb and transfer the mechanical loads to the rooftop columns properly. All nuts and bolts shall be of very good quality stainless /galvanized steel.
- xiii. Incase of any defects arising in the building during guarantee period of Five year, the contractor shall rectify the same at their own cost.

### 3. DC Combiner Box/Array Junction Box

The junction boxes shall be dust proof, vermin and waterproof and made of FRP/powder coated Aluminum.

The terminals shall be connected to copper bus bar arrangement of proper sizes. The junction boxes shall have suitable cable entry points fitted with cable glands of appropriate sizes for both incoming and outgoing cables and earthing provision shall be available. Suitable markings shall be provided on the bus bar for easy identification and cable ferrules shall be fitted at the cable termination points for identification. Each main junction box shall be fitted with appropriate rating blocking diode. The junction boxes shall be of reputed make and conform to IP65 standards and IEC 62208. Door shall be of hinged door with EPDM rubber gasket to prevent water entry.

The junction boxes shall have suitable arrangement for the Following:

- Combine groups of modules into independent charging sub-arrays that shall be wired to the controller.
- Provide arrangement for disconnection for each of the groups.
- Provide a test point for each sub-group for quick fault location.
- To provide group array isolation.
- The rating of the JB's shall be suitable with adequate safety factor to inter connect the Solar PV array.
- Suitable capacity MOVs shall be provided within the box to protect against lightning

**Fuse Protection on Strings:** DC fuses rated from 2A to 25A from leading manufacturers to be used in the combiner box to provide over-current protection. Fuses to be provided with indication.

**Surge Protection Device:** Surge Protection devices or SPD to be provided to protect the combiner/junction box from any power surge and voltage spike. SPD to be used should meet Type 2 regulations, and to be typically rated between 600 to 1000V.

**Input Glands/ Connectors:** The combiner/ array junction box offered is to be provided with IP 67 rated Cable Glands or MC 4 connectors at the input side to lead the array strings into the box.

## 4. Grid Interactive Inverter/PCU

- i. The Power Conditioning Unit comprises the Inverter(s) and associated MPPT, control, protection, data logging devices etc.
- ii. Solar array shall produce DC energy output which shall be supplied to the DC bus for inverting to AC voltage. Maximum Power Point Tracking (MPPT) system shall be an inherent feature of the system and shall be used to extract maximum energy from solar array to produce 415 VAC 3 ph 50 Hz output. The output shall be synchronized with the station's grid power.
- iii. The system shall generate power for use during the day-light hours directly by the captive load.
- iv. The peak efficiency of PCU shall not be less than 97% & shall be designed to meet the Solar PV Array capacity control which will extract maximum energy from solar array and provides 415V AC +/-10%, 50HZ, to synchronize (and not export) with local utility grid in Indian ambient conditions.
- v. The efficiency of PCUs used at Insolation levels of 10% to 90% shall not be less than 90%.
- vi. Output of Inverter shall be 3 phase, 415 v +/- 10%, 50 Hz sine wave with < 3% total harmonic distortion (THD). Additionally, it will provide protection features such as over current, short circuit, over temperature as a minimum.
- vii. PCU shall be of very high quality having high peak efficiency of 97% and above. The PCU should be completely compatible with the SPV array voltage and local grid / DG supply voltage.

- viii. Switching shall be MOSFET / IGBT based.
- ix. Idle current shall be less than 4% of rated capacity.
- x. The PCU shall be string type inverters to reduce the DC power losses & can have the flexibility to increase the capacity of the plant.
- xi. The PCU shall be designed for continuous, reliable power supply as per specifications.
- xii. The PCU shall be capable of complete automatic operation and shall be capable to synchronize independently & automatically with the grid supply and DG Supply. The idea for installing SPV unit is to be utilize whatever power is available and directly feed into the system irrespective of whether grid supply is 'ON' or DG is 'ON' on SOLAR FIRST basis.
- xiii. The PCU shall have a built-in data logging facility to remotely monitor and control plant performance through external PC.
- xiv. The PCU shall have internal protection arrangement against any sustained fault. The dimension, weight, foundation details etc. of the PCU shall be clearly indicated in the detailed technical specification provided by the contractor.
- xv. It has user friendly LED / LCD Graphical display for programming and viewing of the Solar system parameters and protection status.
- xvi. The operating temperature range shall be -20 to +50 deg C
- xvii. Housing cabinet IP-20(Minimum) for indoor, IP-65(Minimum) for outdoor
- xviii. Power factor shall be greater than 0.9
- xix. Cooling shall be forced air cooling through cooling fan.
- xx. The system shall be capable of automatic operation with automatic wake-up in the morning and providing supply to the load after synchronizing with Grid/DG supply.
- xxi. When the generated power is below a low, preset value or the solar insolation is below a set value for a pre-determined amount of time, the inverter shall be disconnected from the grid and shall be operated in a "sleep mode". In this mode, the inverter power stage components shall be switched off, thereby keeping the stand by losses to a bare minimum.
- xxii. Unique MPPT algorithm shall adjust the DC Link operating voltage to ensure that maximum power is extracted from the solar array in an efficient manner.
- xxiii. Automatic "Sleep Mode" shall be provided to reduce standby losses.
- xxiv. The system shall be designed to minimize both conducted and radiated RFI emissions.
- The capacity of the Inverter shall be chosen based on the PV system wattage. However, the total Peak output Power rating of all the PCU's at operating temperatures of 45 deg C shall not be less than 100 KW.
- xxvi. Overload protection shall be min. 150% for one minute.
- xxvii. The inverter must have a DC disconnect switch / device.
- xxviii. MCB of suitable rating to be provided for connecting / disconnecting Load and

PCU.

- xxix. The inverter must have an integrated MODBUS RS-485 interface for connectivity.
- xxx. Potential free contact shall be provided for the 'Solar system operation status' for remote monitoring.
- xxxi. The PCU shall meet all the requirements of latest MNRE guidelines.

#### 5. Indications

- Inverter on
- Grid on
- Inverter under voltage / over voltage
- Inverter over load
- Inverter over temperature

#### 6. Protections

- Over voltage at input
- Over current at output
- Over / under output voltage
- Over / under grid frequency
- Over temperature
- Short circuit
- DC reverse polarity
- Protection against lightning
- Surge voltage protection

#### 7. Remote Monitoring

- DC power input
- DC input voltage
- DC input current
- AC power output
- AC voltage
- AC current
- AC frequency
- Power factor
- Energy harvested daily / monthly / yearly
- Inverter status
- Total power generated/operation time

The PCU including MPPT and protection shall conform to IEC 61683 / IS 61683, IEC 60068 - 2 / equivalent BIS standards.

#### 8. Data Monitoring of Solar Power Plant

The system performance monitoring and solar generation data is recorded using a data logger. The Monitoring system shall comprise of the following main components:

 PCU logs the inverter performance data and transmits the same to the Data logger.

- Data monitoring system logs irradiance (solar insolation) and ambient temperature. Necessary sensors required for the same shall be provided by the Contractor and sensor outputs interfaced to the Solar monitoring system
- Data logger gathers information and monitors the performance of the inverter. It also supports measurements from the external sensors. The data can be acquired through Ethernet port (RJ45) and shall be available to connect to Bank network.
- The data acquisition system shall have a real-time clock and data storage capacity for recording data round the clock for min. one year.
- The monitoring of the Solar system and logging / viewing of system data shall be done through a PC with HMI software to be supplied by the Contractor.
- PC Data logging software enables automatic long-term storage of measured data from SPV Plant. It allows visualization, monitoring, commissioning and service of the installation.
- The software package shall be preferably windows based.
- The Solar system data shall be logged in chronological order, date wise. The periodicity of data logging shall be configurable.
- Event logging shall be adjustable repetition from 01 second to 600 Seconds,
   with storage capacity up to 03 Years with 10 minute logs.
- The system shall be capable of providing graphical trends for viewing the system parameters on real time as well as historic basis. It shall be possible to generate reports based on the logged historic data which shall be exportable in MS Excel / PDF formats.
- System shall have provision for remotely viewing the System status on local LAN /INTRANET of bank.

# 9. AC Distribution Board (ACDB)

An AC distribution box shall be provided between the Inverter and the existing LT Panel of bank. This panel shall have provision for protection, connection and disconnection of individual inverters from the AC system.

The AC Box will be used to combine AC power coming from the inverters.

- The AC Box shall be dust, vermin & water proof & made of FRP / ABS plastic.
- The junction boxes shall have suitable cable entry points fitted with cable glands of appropriate sizes for both incoming and outgoing cables.
- Suitable markings shall be provided on the bus bar for easy identification and cable ferrules shall be fitted at the cable termination points for identification.
- It should have the facility to protect from over currents & isolate the AC box from the main AC line.
- The AC Box should have surge protection devices, to protect inverters from surges in the AC line.
- For service & emergency safety requirements, the circuit breakers / loadbreak switches must have facility for remote operation.

 The Solar Power should be exported to the LT Panel bus bar through a Energy Meter. The Energy meter should have Modbus RS- 485 communication interface.

## 10. DC Distribution Board (DCDB)

DC Distribution panel board shall be provided to receive the DC output from the array field, with analog measurement panel for voltage, current and power from different MJBs so as to check any failure in the array field. DCDB shall have enclosure of dust & vermin proof. The bus bars shall be made of copper of desired size. Suitable capacity MCBs along with necessary surge arrestors shall be provided for controlling the DC power output to the PCU/Inverter. DCDB shall be fabricated by CRC Sheet/ FRP / ABS plastic to comply with IP 65 protection.

# 11. Cables and Accessories

Cables should be FRLS PVC insulated Copper Conductor armoured Cables of  $1100\ V$ 

Grade and shall conform to IS: 1554 / IEC 60502 AND IS 694 / IEC 60227.

Cable should be Bright Annealed 99% pure Copper Conductor. Conductor shall be of electrolytic copper confirming to IS: 8130

Cables shall be UV and weathering resistant.

Voltage drop & losses to be kept to minimum. On DC side voltage drop to be max 1%.

Cables shall be laid on prefabricated GI cable trays and through suitable HDPE pipes.

All interfaces between panel integral cable and extension cable must be done using MC4 equivalent connectors only.

# 12. Earthing and Lightning Protection

#### **Earthing Protection**

Each array structure of the PV yard should be grounded/ earthed properly as per IS:3043 -1987. In addition the lighting arrester/masts should also be provided inside the array field. Provision should be kept for shorting and grounding of the PV array at the time of maintenance work. All metal casing/shielding of the plant should be thoroughly grounded in accordance with Indian Electricity Act/IE Rules. Earth Resistance shall be tested in presence of the representative of bank as and when required after earthing by calibrated earth tester. PCU, ACDB and DCDB should also be earthed properly. Earth resistance shall not be more than 5 ohms for individual pit and shall be less than 1.0 Ohms for Grid in line. It shall be ensured that all the earths are bonded together to make them at the same potential. The earthing conductor shall be rated for the maximum short circuit current, and shall be 1.56 times the short circuit current. The area of cross - section of conductor shall not be less than 1.6 sq mm in any case. The Earthing

pits shall be made at locations approved by bank.

#### Lightning protection

There shall be the required number of suitable lightning arrestors (ESE) installed in the array area. Lightning protection shall be provided by the use of metal oxide arrestors and suitable Earthing such that induced transients find an alternate route to earth. Protection shall meet the safety rules as per Indian Electricity Act2003/IE rules.

#### 13. FIRE EXTINGUISHERS

This control room shall be provided with Portable fire extinguisher for fire caused by electrical short circuits. Apart from this Sand buckets shall be placed in relevant areas mandated by BIS. The installation of Fire Extinguishers should confirm to TAC regulations and BIS standards. The fire extinguishers shall be provided in the control room housing the PCUs as well as on the roof top where the PV arrays have been installed.

#### 14. Finish & Painting

Corrosion Resistance: All surfaces of the equipment including frame modules, covers, chassis, brackets, etc., shall be treated to prevent corrosion.

The ACDB/DCDB shall be Galvanized iron / powdered coated/Weather proof paint.

Colour scheme shall be as follows: Siemens Gray

*Name Plate:* A name plate, anodized shall be suitably fixed to the modules of the glass, iron structure and charge controller with the following:

Name Plate for SPV Panel and Mounting Structure:

Name of the User

Manufacturer's name and identification mark

Name of the Item

Model No.

Serial No. of the unit

Year of manufacture

Name Plate for PCU:

Name of the user

Manufacturer's name and identification mark

Name of the Item

Model No.

Type of unit

Serial No. of the unit

Year of manufacture

Rating and voltage of the PCU/Inverter

Input voltage

Output Voltage and Current

On the front top of the PCU,ACDB/DCDB cabinet, an anodized, screen printed or

any other arrangement ensuring better life expectancy designation plate in "Bold" letters showing "35 kWp SPV POWER PLANT UNDER GREEN INITIATIVE SCHEME" or "25 kWp SPV POWER PLANT UNDER GREEN INITIATIVE SCHEME".

#### 15. TOOLS, SHACKLES

After completion of installation & commissioning of the power plant, necessary tools & shackles are to be provided free of cost by the supplier for maintenance purpose.

#### 16. Documentation

Supplier shall provide 02 sets of Operation & Maintenance Manual in English for the complete system with Block diagram, detailed description of all the system components, mounting of PV Module, electronics used, working, starting and shutdown procedures, maintenance and trouble-shooting instructions, DO's & DONT's, Name & address of contact person or Centre to be contacted in case of complaints/ failure. Warranty Card & Service entry card shall be provided with the SPV Power Plant systems.

Supplier shall provide 02 sets of the As-built Detailed Wiring diagrams, Array layout and termination schedules. Approval of Bank needs to be obtained on the content of Manual,

## 17. Installation of Components and Materials

Description:

- 1. Supply and installation of Module mounting structure/ super structure for mounting at roof top.
- 2. The PV modules shall be installed with necessary tilt with the most effective orientation. Tilt angle to be optimized to obtain maximum generation.
- 3. Supporting structure material shall be compatible with the PV panel mounting frame.
- 4. Each module can be mounted on a mounting structures fabricated from hot dip galvanized MS, using appropriate clamps and trapezoidal sheet holders, rail track connectors, screws and fixtures. The structure shall be non-corrosive and long lasting. Each structure will carry multiple modules to form a row. The structure shall be capable of withstanding a wind speed of 150Km/Hr. after grouting and installation and shall be designed to cater very rough climatic conditions. The contractor shall furnish design calculations to confirm the wind speed withstand capability of the structure. The same will be reviewed by the banker's engineer's and in case of any shortcomings in the design the contractor shall make suitable changes so as to make the entire structure capable to withstand against wind speed specified as above. The mounting structure shall be guaranteed for at least 5 years.
- 5. Supply and installation of power conditioning unit (PCU) consisting of Solar Charge Controller/ Inverter.

- 6. The installation shall include the electrical wiring, cabling, terminations, cable trays, micro/ string inverters, metering and hooking up the system to the including synchronization with plant main LT Panel grid / DG set.
- 7. Installation of inverter should be in a ventilated area and proper inter-spacing is to be provided.
- 8. Laying of power/ control copper cables from PV power to plant room, Main LT panel including within terraces.
- Supply and installation of cables on prefabricated GI cable trays and / or within suspended ceiling spaces including installation, cable trays, hangers, supports, cable terminations all fixing accessories (terrace to plant room inclusive of PVC sleeve/ other accessories etc. wherever required)
- 10. Supply and installation of earthing system with testing joint for every pit (grounding) system including cutting of roads / paved areas / PCC floor etc and making as good as in original shape. Prior to execution, design shall be submitted by contractor for approval by bank.
- 11. Supply and installation of lightening arrester, required as per statutory norms/guidelines as approved by bank.

#### 18. Testing and commissioning

Pre-commissioning tests of all electrical equipments. Specific points to be considered during commissioning are:

- 1. Continuity checking and insulation resistance measurement of cables.
- 2. Proper crimping, lugging and glanding of cables before final terminations.
- 3. Checking of all electrical terminations for any loose contacts.
- 4. Proper earthing of electric equipment & solar array to be ensured.
- 5. At junction box in solar array, voltage levels to be checked (between positive & negative terminal, positive to earth and negative to earth) in consultation with inverter OEM.
- 6. Inverter to be checked in testing mode and after No Fault indication is displayed on LCD it is to be connected to grid/battery.

#### 19. Annual Generation Guarantee

Contractor shall give minimum annual power generation guarantee of 47250 Units/ Kwh for system at Karnal and 33750 Units/ Kwh for system at Panchkula for first year (Calculated on the basis of average 4.5 KWH per KWp functioning for 300 days) and for subsequent years as per following –

2nd Year: 99.0% of 1st Year Generation 3rd Year: 98.5% of 1st Year Generation 4th Year: 98.0% of 1st Year Generation 5th Year: 97.5% of 1st Year Generation

In case of short fall, Contractor will compensate for the less power generated as per prevailing rate of State electricity board for first five

years. The powergeneration trend after first 5 years must be mentioned.

Contractor may monitor the performance of system installed. In case Contractor finds that installed system will not meet assigned minimum annual guarantee, it isup to Contractor to upgrade the system to meet the minimum requirement at his own cost.

#### 20. LT Panel & AC Distribution Box - Interconnection

The Inverter / Power conditioning unit converts DC energy produced by solar array to 3 phase AC power. The AC power output of the inverter shall be fed to the AC Distribution Box (metering panel & isolation panel) which also houses energy meter. The 415 V AC output from the AC distribution box is fed to the owner's LT panel for feeding the building load. The AC power from the Solar Inverter shall be synchronized with the station's supply grid and power is fed into the building load on continuous basis. The connectivity / interfacing of the AC power output from the Solar Inverter to the existing grid power shall be designed and carried out by the contractor. First preference for drawing power shall be from Solar Inverter, the balance power shall be automatically drawn from the grid supply. Contractor shall finalize the scheme of interconnection to LT Panel / load after discussion with bank.

## 21. Integration Of Solar Power With Grid

The output power from SPV would be fed to the inverters which converts DC produced by SPV array to AC and feeds it into the consumer load and the surplus power to be feed into the grid after synchronization. In case of grid failure, or low or high voltage, solar PV system shall be out of synchronization and shall be disconnected from the grid. Once the DG set comes into service PV system shall again be synchronized with DG supply and load requirement would be met to the extent of availability of power. 4 pole isolation of inverter output with respect to the grid/ DG power connection need to be provided.

#### 22. Grid Islanding

- i. In the event of a power failure on the electric grid, it is required that any independent power-producing inverters attached to the grid turn off in a short period of time. This prevents the DC-to-AC inverters from continuing to feed power into small sections of the grid, known as "islands." Powered islands present a risk to workers who may expect the area to be unpowered, and they may also damage grid-tied equipment. The Rooftop PV system shall be equipped with islanding protection. In addition to disconnection from the grid (due to islanding protection) disconnection due to under and over voltage conditions shall also be provided.
- ii. A manual disconnect 4pole isolation switch beside automatic disconnection to grid would have to be provided at utility end to isolate the grid connection by the utility personnel to carry out any maintenance. This switch shall be locked by the

utility personnel

#### 23. Acceptance Criteria

Final acceptance of the integrated system will be given only after validating the performance of the system as in Installation, Testing and Commissioning of clause above.

#### 24. Guaranty

All the components of the system shall be guaranteed for any manufacturing defect or inferior components for a period of **FIVE years** from the date of commissioning.

# 25. Training

The supplier shall provide training to at least 3 departmental operators on the O & M aspects of the system

#### **PROFILE OF THE BIDDER**

SNO	Particulars		dder
1	Name of the Company		
2	Year of incorporation		
3	Registered office		
	Address		
	Office Telephone Number		
	Fax Number		
4	Contact Person		
	Name		
	Personal Telephone Number		
	Mobile Number		
	Email Address		
5	Local office(s)in Haryana/Delhi /Chandigarh/Punjab		
	Address		
	Office Telephone Number		
	Fax Number		
6	Tender signing authority		
	Name		
	Address		
	Personal Telephone Number		
	Email Address		
	Please enclose Authorization or Power of Attorney to sign and submit the Tender		
7	Address for communication under the current tender		
8	Goods & Service Tax No		
9	Permanent Account Number		
EMD A	mount		
S.No.	Particulars	Please furnish details for Karnal	Please furnish details for Panchkula
1	Name of the Bank		
2	Demand Draft (DD) Number		
3	DD Date		
4	DD Amount		

Т	Technical Data Sheet to be compulsorily filled by contractor 35KWp Solar Photo			
Vo	Voltaic Power Plant, Roof top Grid Tie System for Canara Bank Circle Office, Karnal			
SN	Specification	Bank Requirement	Contractor Reply	
A.	SPV power plant			
1	Rated Output	To be mentioned by Contractor (To meet total 35KWp)		
2	No. of PV Modules	To be mentioned by Contractor		
3	No. of series module in one array	To be mentioned by Contractor		
4	No. of array in parallel combination	To be mentioned by Contractor		
B.	SPV Module			
1	PV Cell type	To be mentioned by Contractor		
2	Make of SPV Cell	To be mentioned by Contractor		
3	Make of SPV Module	To be mentioned by Contractor		
4	Maximum Power Rating ofone module(KWp)	Should not be lesser than 400Wp-To be mentioned by Contractor		
5	Rated Current of Module			
6	Rated Voltage of module	To be mentioned by Contractor		
7	Short Circuit Current of module	To be mentioned by Contractor		
8	Open Circuit Voltage of module	To be mentioned by Contractor		
9	Sample I-V Curve Submitted (Yes/ No)	To be mentioned by Contractor		
10	Photo Electrical Conversion Efficiency of SPV module Fill Factor of SPV	Not less than 15% - To be mentioned by the Contractor  Greater than 0.70- To be		
	Module	mentioned by the Contractor		

12	No. of modules T	o be mentioned by the	
		ontractor	
	provided to achieve		
	minimum DC power		
C.	Mounting Arrangement	I	
1	Mounting type	Roof-mounted	
2	Surface azimuth angle of	To be mentioned by	
	PV Module	Contractor	
3	Tilt angle (slope) of PV	To be mentioned by	
	Module	Contractor	
4	Confirmation that	Yes/No – To be mentioned	
	structure and module	by Contractor	
	frame shall be designed to		
	withstand wind speed of		
	200km/hr		
D	DC Combiner Box/ Array Ju	unction Box	
1	Enclosure	To be mentioned by	
		Contractor	
2	Necessary Fuse Protection	Yes	
	& Surge Protection		
3	Rated Insulated Voltage	DC 1000V	
Е	Power Conditioning Unit (Po	CU) / Inverter	
E 1	Power Conditioning Unit (Power Make of PCU/Inverter	CU) / Inverter Schneider/ABB or	
	Make of PCU/Inverter	Schneider/ABB or equivalent	
	Make of PCU/Inverter  Nominal Output array	Schneider/ABB or equivalent  To be mentioned by	
1	Make of PCU/Inverter  Nominal Output array voltage shall be suitable	Schneider/ABB or equivalent	
2	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU	Schneider/ABB or equivalent  To be mentioned by Contractor	
1	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC	
2	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage	
2	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge	
3	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage MPPT Based Solar Charge Controller	
1 2 3 4	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage MPPT Based Solar Charge Controller MOSFET/IGBT based	
3	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage MPPT Based Solar Charge Controller MOSFET/IGBT based To be mentioned by	
1 2 3 4 5 6	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA)	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage MPPT Based Solar Charge Controller MOSFET/IGBT based To be mentioned by Contractor	
1 2 3 4 5 6	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor  Pure Sine Wave Output	
1 2 3 4 5 6	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage MPPT Based Solar Charge Controller MOSFET/IGBT based To be mentioned by Contractor Pure Sine Wave Output < 3% @ nominal power	
1 2 3 4 5 6 7 8 9	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion Output Voltage	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor  Pure Sine Wave Output  < 3% @ nominal power  3 ph, 415± 10 %	
1 2 3 4 5 6 7 8 9 10	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion Output Voltage Output Frequency	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor Pure Sine Wave Output  < 3% @ nominal power  3 ph, 415± 10 %  50Hz ± 3%	
1 2 3 4 5 6 7 8 9 10 11	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion Output Voltage	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor Pure Sine Wave Output  < 3% @ nominal power  3 ph, 415± 10 %  50Hz ± 3%  > 0.9	
1 2 3 4 5 6 7 8 9 10	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion Output Voltage Output Frequency Power Factor	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor  Pure Sine Wave Output  < 3% @ nominal power  3 ph, 415± 10 %  50Hz ± 3%  > 0.9  > 90% at nominal voltage	
1 2 3 4 5 6 7 8 9 10 11	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion Output Voltage Output Frequency	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor Pure Sine Wave Output  < 3% @ nominal power  3 ph, 415± 10 %  50Hz ± 3%  > 0.9	

	No. of Taxontona with	To be provided by	
14	No. of Inverters with	To be provided by	
	Configuration	Contractor ( to meet	
		nominal output power)	
15	Inverter Type	To be mentioned by	
		Contractor	
16	Idle Current	< 4% of rated capacity	
17	Regulation	±2% for DC I/p variation &	
		o/p load variation	
18	Overload Features	150% for 1 minute	
19	Cooling	Forced Air cooling, with	
		temperature controlled	
		cooling fan	
20	Operating Temperature	0 to 50 °C	
21	Relative Humidity	95% Maximum	
22	LED/LCD Display:	Display shall indicate	
	Indications	system functional	
		parameters and protection	
		functional indicator	
23	Data monitor and display	RS485, Ethernet OR RS232	
	controls	connectivity	
24	Protections		
	a. Input over voltage	To be mentioned by	
	b. Low/high frequency	Contractor	
	c. Short circuit		
	d. Under/over output		
	voltage		
	e. Over Temperature		
	f. Grid Input under		
	voltage / over voltage		
	with auto recovery		
	g. DC disconnect device		
	h. DC reverse polarity		
	i. Anti-Islanding Protection		
	as per the standard		
25	Enclosure Protection	IP 20(for indoor) IP 60 (for	
		outdoor)as per IEC 529	
26	Safety	1. IEC 62103	
	•	2. IEC 62109 Part 1 & 2	
		3. Galvanic Isolation at	
		input &	
		output through transformer	
27	Audible Noise	< 45dB at 1 Meter	
			<u> </u>

Power Control   MPPT suitable for hybrid operation.		ICHKULA RESPECTIVELY		
F DC/AC Distribution  1 DC Side Quantity & To be mentioned by Ratings of MCBs  2 AC Side Quantity & Contractor  MCBs  3 Details of measuring  To be mentioned by Contractor  4 Other Details  To be mentioned by Contractor  4 Other Details  To be mentioned by Contractor  G Cables  1 Make  To be mentioned by Contractor  2 Size  To be mentioned by Contractor  3 Other Details  To be mentioned by Contractor  H Earthing  1 Details of points earthed  To be mentioned by Contractor  I Lightning Arrestor  1 Make & To be mentioned by Contractor  I Lightning Arrestor  1 Area covered per Lightning Arrestor  J Datasheet for Modules,  To be submitted along with	28	Power Control	·	
1 DC Side Quantity & To be mentioned by Contractor 2 AC Side Quantity & Capacity of Quantity & Capacity of MCBs 3 Details of measuring To be mentioned by Contractor 4 Other Details To be mentioned by Contractor  4 Other Details To be mentioned by Contractor  5 Cables To be mentioned by Contractor  Contractor Size To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing To be mentioned by Contractor  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  I Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with			operation.	
1 DC Side Quantity & To be mentioned by Contractor 2 AC Side Quantity & Capacity of Quantity & Capacity of MCBs 3 Details of measuring To be mentioned by Contractor 4 Other Details To be mentioned by Contractor  4 Other Details To be mentioned by Contractor  5 Cables To be mentioned by Contractor  Contractor Size To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing To be mentioned by Contractor  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  I Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with				
Ratings of MCBs  2		<u> </u>	,	
2 AC Side Quantity & Capacity of MCBs  3 Details of measuring  To be mentioned by Contractor  4 Other Details  To be mentioned by Contractor  6 Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  Details of points earthed To be mentioned by Contractor  I Lightning Arrestor  Area covered per Lightning Arrestor  Number of Lightning Arrestors  J Datasheet for Modules, To be submitted along with	1		1	
Quantity & Capacity of MCBs  3 Details of measuring To be mentioned by Contractor  4 Other Details To be mentioned by Contractor  G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per Lightning Arrestor To be mentioned by Contractor  3 Number of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with			Contractor	
MCBs  Details of measuring To be mentioned by Contractor  To be mentioned by Contractor  Gentractor  Make To be mentioned by Contractor  Size To be mentioned by Contractor  Size To be mentioned by Contractor  Make To be mentioned by Contractor  Lightning Arrestor  Make & Type To be mentioned by Contractor  To be mentioned by Contractor  Area covered per Contractor  Mumber of Lightning Arrestor  Mumber of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with	2	AC Side	To be mentioned by	
Contractor  4 Other Details To be mentioned by Contractor  G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  Details of points earthed To be mentioned by Contractor  Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  Make & Type To be mentioned by Contractor  1 Make & Type To be mentioned by Contractor  2 Area covered per Lightning Arrestor  Number of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with			Contractor	
4 Other Details To be mentioned by Contractor  G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  Make & Type To be mentioned by Contractor  2 Area covered per Lightning Arrestor  Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with	3	Details of measuring	To be mentioned by	
Contractor  G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with			Contractor	
Contractor  G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with				
G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with	4	Other Details	·	
1 Make Contractor 2 Size To be mentioned by Contractor 3 Other Details To be mentioned by Contractor H Earthing 1 Details of points earthed To be mentioned by Contractor 2 Earth Resistance To be mentioned by Contractor I Lightning Arrestor 1 Make & Type To be mentioned by Contractor 2 Area covered per Lightning Arrestor Contractor 3 Number of Lightning To be mentioned by Arrestors Contractor J Datasheet for Modules, To be submitted along with			Contractor	
Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  Make & Type To be mentioned by Contractor  2 Area covered per Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with				
2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per Lightning Arrestor Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	1	Make	·	
Contractor  Other Details  To be mentioned by Contractor  H Earthing  Details of points earthed  To be mentioned by Contractor  Earth Resistance  To be mentioned by Contractor  I Lightning Arrestor  Make & Type  To be mentioned by Contractor  Area covered per Lightning Arrestor  Number of Lightning  Arrestors  To be mentioned by Contractor  To be submitted along with				
3 Other Details  To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with	2	Size	·	
Contractor				
H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per Lightning Arrestor  3 Number of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with	3	Other Details	I -	
1 Details of points earthed To be mentioned by Contractor 2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with			Contractor	
Contractor  Earth Resistance  To be mentioned by Contractor  I Lightning Arrestor  Make & Type  To be mentioned by Contractor  Area covered per To be mentioned by Contractor  Area covered per Contractor  Number of Lightning To be mentioned by Arrestors  Datasheet for Modules,  To be submitted along with	Н	Earthing		
2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Lightning Arrestor Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	1	Details of points earthed	To be mentioned by	
Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Lightning Arrestor  3 Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with				
I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Lightning Arrestor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	2	Earth Resistance	To be mentioned by	
1 Make & Type To be mentioned by Contractor 2 Area covered per To be mentioned by Lightning Arrestor Contractor 3 Number of Lightning To be mentioned by Arrestors Contractor J Datasheet for Modules, To be submitted along with			Contractor	
Contractor  2 Area covered per To be mentioned by Lightning Arrestor Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	I	Lightning Arrestor		
2 Area covered per To be mentioned by Lightning Arrestor Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	1	Make & Type	To be mentioned by	
Lightning Arrestor Contractor  Number of Lightning Arrestors Contractor  Datasheet for Modules, To be mentioned by Contractor To be submitted along with			Contractor	
3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	2	Area covered per	To be mentioned by	
Arrestors Contractor  J Datasheet for Modules, To be submitted along with		Lightning Arrestor	Contractor	
J Datasheet for Modules, To be submitted along with	3	Number of Lightning	To be mentioned by	
3		Arrestors	Contractor	
Inverter, Cables etc the bid	J	Datasheet for Modules,	To be submitted along with	
		Inverter, Cables etc	the bid	

# Technical Data Sheet to be compulsorily filled by contractor 25KWp Solar Photo Voltaic Power Plant, Roof top Grid Tie System for Canara Bank Regional Office

	Panchkula Panchkula				
SN	Specification	Bank Requirement	Contractor Reply		
Α.	SPV power plant				
1	Rated Output	To be mentioned by Contractor (To meet total 25KWp)			
2	No. of PV Modules	To be mentioned by			
		Contractor			
3	No. of series module in	To be mentioned by			
	one array	Contractor			
4	No. of array in parallel	To be mentioned by			
	combination	Contractor			
B.	SPV Module				
1	PV Cell type	To be mentioned by			
		Contractor			
2	Make of SPV Cell	To be mentioned by			
		Contractor			
3	Make of SPV Module	To be mentioned by			
		Contractor			
4	Maximum Power	Should not be lesser than			
	Rating ofone	400Wp-To be mentioned by			
	module(KWp)	Contractor			
5	Rated Current of Module	To be mentioned by			
		Contractor			
6	Rated Voltage of	To be mentioned by			
	module	Contractor			
7	Short Circuit Current of	To be mentioned by			
	module	Contractor			
8	Open Circuit Voltage of	To be mentioned by			
	module	Contractor			
9	Sample I-V Curve	To be mentioned by			
	Submitted (Yes/ No)	Contractor			
10	Photo Electrical	Not less than 15% - To be			
	Conversion	mentioned by the			
	Efficiency ofSPV	Contractor			
4.4	module	Constanthan 0.70 To be			
11	Fill Factor of SPV Module	Greater than 0.70- To be			
	Module	mentioned by the			
		Contractor			

12	No. of modules T	o be mentioned by the	
		ontractor	
	provided to achieve		
	minimum DC power		
C.	Mounting Arrangement	I	
1	Mounting type	Roof-mounted	
2	Surface azimuth angle of	To be mentioned by	
	PV Module	Contractor	
3	Tilt angle (slope) of PV	To be mentioned by	
	Module	Contractor	
4	Confirmation that	Yes/No – To be mentioned	
	structure and module	by Contractor	
	frame shall be designed to		
	withstand wind speed of		
	200km/hr		
D	DC Combiner Box/ Array Ju	unction Box	
1	Enclosure	To be mentioned by	
		Contractor	
2	Necessary Fuse Protection	Yes	
	& Surge Protection		
3	Rated Insulated Voltage	DC 1000V	
Е	Power Conditioning Unit (Po	CU) / Inverter	
E 1	Power Conditioning Unit (Power Make of PCU/Inverter	CU) / Inverter Schneider/ABB or	
	Make of PCU/Inverter	Schneider/ABB or equivalent	
	Make of PCU/Inverter  Nominal Output array	Schneider/ABB or equivalent  To be mentioned by	
1	Make of PCU/Inverter  Nominal Output array voltage shall be suitable	Schneider/ABB or equivalent	
2	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU	Schneider/ABB or equivalent  To be mentioned by Contractor	
1	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC	
2	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage	
2	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge	
3	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage MPPT Based Solar Charge Controller	
1 2 3 4	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage MPPT Based Solar Charge Controller MOSFET/IGBT based	
3	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage MPPT Based Solar Charge Controller MOSFET/IGBT based To be mentioned by	
1 2 3 4 5 6	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA)	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage MPPT Based Solar Charge Controller MOSFET/IGBT based To be mentioned by Contractor	
1 2 3 4 5 6	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor  Pure Sine Wave Output	
1 2 3 4 5 6	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion	Schneider/ABB or equivalent To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage MPPT Based Solar Charge Controller MOSFET/IGBT based To be mentioned by Contractor Pure Sine Wave Output < 3% @ nominal power	
1 2 3 4 5 6 7 8 9	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion Output Voltage	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor  Pure Sine Wave Output  < 3% @ nominal power  3 ph, 415± 10 %	
1 2 3 4 5 6 7 8 9 10	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion Output Voltage Output Frequency	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor Pure Sine Wave Output  < 3% @ nominal power  3 ph, 415± 10 %  50Hz ± 3%	
1 2 3 4 5 6 7 8 9 10 11	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion Output Voltage	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor Pure Sine Wave Output  < 3% @ nominal power  3 ph, 415± 10 %  50Hz ± 3%  > 0.9	
1 2 3 4 5 6 7 8 9 10	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion Output Voltage Output Frequency Power Factor	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor  Pure Sine Wave Output  < 3% @ nominal power  3 ph, 415± 10 %  50Hz ± 3%  > 0.9  > 90% at nominal voltage	
1 2 3 4 5 6 7 8 9 10 11	Make of PCU/Inverter  Nominal Output array voltage shall be suitable for the MPPT range of PCU DC Array Input Operating Voltage Type of solar charge controller Switching device Continuous inverter Output Rating (KVA) Output Wave Form Total Harmonic distortion Output Voltage Output Frequency	Schneider/ABB or equivalent  To be mentioned by Contractor  (-20% to +15%) of the DC Array input voltage  MPPT Based Solar Charge Controller  MOSFET/IGBT based  To be mentioned by Contractor Pure Sine Wave Output  < 3% @ nominal power  3 ph, 415± 10 %  50Hz ± 3%  > 0.9	

	ICHKULA RESPECTIVELY		
14	No. of Inverters with	To be provided by	
	Configuration	Contractor ( to meet	
		nominal output power)	
15	Inverter Type	To be mentioned by	
		Contractor	
16	Idle Current	< 4% of rated capacity	
17	Regulation	±2% for DC I/p variation &	
	_	o/p load variation	
18	Overload Features	150% for 1 minute	
19	Cooling	Forced Air cooling, with	
	_	temperature controlled	
		cooling fan	
20	Operating Temperature	0 to 50 °C	
21	Relative Humidity	95% Maximum	
22	LED/LCD Display :	Display shall indicate	
	Indications	system functional	
	maicacions	parameters and protection	
		functional indicator	
23	Data monitor and display		
23	Data monitor and display controls	RS485, Ethernet OR RS232	
24		connectivity	
24	Protections		
	a. Input over voltage	To be mentioned by	
	b. Low/high frequency	Contractor	
	c. Short circuit		
	d. Under/over output		
	voltage		
	e. Over Temperature		
	f. Grid Input under		
	voltage / over voltage		
	with auto recovery		
	g. DC disconnect device		
	h. DC reverse polarity		
	i. Anti-Islanding Protection		
	as per the standard		
25	Enclosure Protection	IP 20(for indoor) IP 60 (for	
		outdoor)as per IEC 529	
26	Safety	1. IEC 62103	
	-	2. IEC 62109 Part 1 & 2	
		3. Galvanic Isolation at	
		input &	
		output through transformer	
27	Audible Noise	< 45dB at 1 Meter	
		1000	

Power Control   MPPT suitable for hybrid operation.		ICHKULA RESPECTIVELY		
F DC/AC Distribution  1 DC Side Quantity & To be mentioned by Ratings of MCBs  2 AC Side Quantity & Contractor  MCBs  3 Details of measuring  To be mentioned by Contractor  4 Other Details  To be mentioned by Contractor  4 Other Details  To be mentioned by Contractor  G Cables  1 Make  To be mentioned by Contractor  2 Size  To be mentioned by Contractor  3 Other Details  To be mentioned by Contractor  H Earthing  1 Details of points earthed  To be mentioned by Contractor  I Lightning Arrestor  1 Make & To be mentioned by Contractor  I Lightning Arrestor  1 Area covered per Lightning Arrestor  J Datasheet for Modules,  To be submitted along with	28	Power Control	·	
1 DC Side Quantity & To be mentioned by Contractor 2 AC Side Quantity & Capacity of Quantity & Capacity of MCBs 3 Details of measuring To be mentioned by Contractor 4 Other Details To be mentioned by Contractor  4 Other Details To be mentioned by Contractor  5 Cables To be mentioned by Contractor  Contractor Size To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing To be mentioned by Contractor  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  I Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with			operation.	
1 DC Side Quantity & To be mentioned by Contractor 2 AC Side Quantity & Capacity of Quantity & Capacity of MCBs 3 Details of measuring To be mentioned by Contractor 4 Other Details To be mentioned by Contractor  4 Other Details To be mentioned by Contractor  5 Cables To be mentioned by Contractor  Contractor Size To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing To be mentioned by Contractor  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  I Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with				
Ratings of MCBs  2		<u> </u>	,	
2 AC Side Quantity & Capacity of MCBs  3 Details of measuring  To be mentioned by Contractor  4 Other Details  To be mentioned by Contractor  6 Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  Details of points earthed To be mentioned by Contractor  I Lightning Arrestor  Area covered per Lightning Arrestor  Number of Lightning Arrestors  J Datasheet for Modules, To be submitted along with	1		1	
Quantity & Capacity of MCBs  3 Details of measuring To be mentioned by Contractor  4 Other Details To be mentioned by Contractor  G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per Lightning Arrestor To be mentioned by Contractor  3 Number of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with			Contractor	
MCBs  Details of measuring To be mentioned by Contractor  To be mentioned by Contractor  Gentractor  Make To be mentioned by Contractor  Size To be mentioned by Contractor  Size To be mentioned by Contractor  Make To be mentioned by Contractor  Lightning Arrestor  Make & Type To be mentioned by Contractor  To be mentioned by Contractor  Area covered per Contractor  Mumber of Lightning Arrestor  Mumber of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with	2	AC Side	To be mentioned by	
Contractor  4 Other Details To be mentioned by Contractor  G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  Details of points earthed To be mentioned by Contractor  Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  Make & Type To be mentioned by Contractor  1 Make & Type To be mentioned by Contractor  2 Area covered per Lightning Arrestor  Number of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with			Contractor	
4 Other Details To be mentioned by Contractor  G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  Make & Type To be mentioned by Contractor  2 Area covered per Lightning Arrestor  Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with	3	Details of measuring	To be mentioned by	
Contractor  G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with			Contractor	
Contractor  G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with				
G Cables  1 Make To be mentioned by Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with	4	Other Details	·	
1 Make Contractor 2 Size To be mentioned by Contractor 3 Other Details To be mentioned by Contractor H Earthing 1 Details of points earthed To be mentioned by Contractor 2 Earth Resistance To be mentioned by Contractor I Lightning Arrestor 1 Make & Type To be mentioned by Contractor 2 Area covered per Lightning Arrestor Contractor 3 Number of Lightning To be mentioned by Arrestors Contractor J Datasheet for Modules, To be submitted along with			Contractor	
Contractor  2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  Make & Type To be mentioned by Contractor  2 Area covered per Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with				
2 Size To be mentioned by Contractor  3 Other Details To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per Lightning Arrestor Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	1	Make	·	
Contractor  Other Details  To be mentioned by Contractor  H Earthing  Details of points earthed  To be mentioned by Contractor  Earth Resistance  To be mentioned by Contractor  I Lightning Arrestor  Make & Type  To be mentioned by Contractor  Area covered per Lightning Arrestor  Number of Lightning  Arrestors  To be mentioned by Contractor  To be submitted along with				
3 Other Details  To be mentioned by Contractor  H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with	2	Size	·	
Contractor				
H Earthing  1 Details of points earthed To be mentioned by Contractor  2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per Lightning Arrestor  3 Number of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with	3	Other Details	I -	
1 Details of points earthed To be mentioned by Contractor 2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Contractor  3 Number of Lightning To be mentioned by Contractor  J Datasheet for Modules, To be submitted along with			Contractor	
Contractor  Earth Resistance  To be mentioned by Contractor  I Lightning Arrestor  Make & Type  To be mentioned by Contractor  Area covered per To be mentioned by Contractor  Area covered per Contractor  Number of Lightning To be mentioned by Arrestors  Datasheet for Modules,  To be submitted along with	Н	Earthing		
2 Earth Resistance To be mentioned by Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Lightning Arrestor Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	1	Details of points earthed	To be mentioned by	
Contractor  I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Lightning Arrestor  3 Number of Lightning To be mentioned by Arrestors  J Datasheet for Modules, To be submitted along with				
I Lightning Arrestor  1 Make & Type To be mentioned by Contractor  2 Area covered per To be mentioned by Lightning Arrestor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	2	Earth Resistance	To be mentioned by	
1 Make & Type To be mentioned by Contractor 2 Area covered per To be mentioned by Lightning Arrestor Contractor 3 Number of Lightning To be mentioned by Arrestors Contractor J Datasheet for Modules, To be submitted along with			Contractor	
Contractor  2 Area covered per To be mentioned by Lightning Arrestor Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	I	Lightning Arrestor		
2 Area covered per To be mentioned by Lightning Arrestor Contractor  3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	1	Make & Type	To be mentioned by	
Lightning Arrestor Contractor  Number of Lightning Arrestors Contractor  Datasheet for Modules, To be mentioned by Contractor To be submitted along with			Contractor	
3 Number of Lightning To be mentioned by Arrestors Contractor  J Datasheet for Modules, To be submitted along with	2	Area covered per	To be mentioned by	
Arrestors Contractor  J Datasheet for Modules, To be submitted along with		Lightning Arrestor	Contractor	
J Datasheet for Modules, To be submitted along with	3	Number of Lightning	To be mentioned by	
3		Arrestors	Contractor	
Inverter, Cables etc the bid	J	Datasheet for Modules,	To be submitted along with	
		Inverter, Cables etc	the bid	

# CHECKLIST FOR MEETING ELIGIBILITY CRITERIA This has to be mandatorily filled up and submitted with Technical Bid.

S.No	Criteria	•	Whether enclosed ( Page No.	Papers are Yes/No) with
1	SECIregistered vendor.  (MNRE registration prior to discontinuation of	Copy of the letter issued by MNRE / SECI regarding registration with them to confirm about the category of their registration.		Page No.
2	minimum 5 years experience in the field of solar power plants in Government / Semi Government / PSUs / office buildings / commercial	Valid certificates, Order copies and satisfactory completion certificates prior to 31.12.2021  (Need to submit all the above mentioned documents)		
3	Rs 20 Lakhs during last 3 financial years.	Certificate issued by Chartered Accountant indicating turnover for the last three years i.e. 2018-19,2019-20and 2020-21 along with audited financial statement for the sameperiods.		
4	At least two (2) completed similar works each of Capacity more than 25 KWp during the last 3 (Three) years ending with 31.12.2021. OR At least one (1) completed	order clearly indicating nature and scope and value of works. Completion certificate for the		

PANCE	IKULA RESPECTIVELY		
		can be contacted by the Bank if needed.	
	Service setup in Haryana/Delhi/Chandigarh	Address and contact details of the office and Service setup, in to be furnished. Copy of document proof of local address i.e lease agreement of the firm entered with landlord, tax paid receipt or GST registration has to be submitted. The same may be inspected by Bank officials.	
6	The firm must have Goods & Service tax registration number and PAN number.	Copies of the GST registration certificate and PAN card copy shall be enclosed.	

#### **SCOPE OF COMPREHENSIVE AMC**

## A) MAINTENANCE DURING DEFECT LIABILITY PERIOD OR WARRANTY PERIOD

- 1. The Contractor shall maintain the plant and associated equipment free of cost and ensure that it works as per tender parameters.
- 2. All spares required for normal operation as per tendered parameters shall be replaced at no extra cost.
- 3. The number of visits shall be same as stipulated in Comprehensive Annual Maintenance.

# B) COMPREHENSIVE ANNUAL MAINTENANCE (CAM) (after the defect liability period)

- 1. The Contractor shall maintain the plant and associated equipments for a period of Four years after the expiry of defect liability period and ensure that it works as per the tendered parameters.
- 2. The rate of annual maintenance charges shall be furnished for a period of 4 years after the expiry of warranty/defect liability period and the rates quoted shall be binding on the Contractor.
- 3. The cost of CAM furnished shall also be one of the criteria in evaluation of cost economics.
- 4. The Comprehensive Annual Maintenance Charges shall be paid once in three months in advance subject to satisfactory maintenance of previous quarter.

# SCOPE OF COMPREHENSIVE ANNUAL MAINTAINANCE CONTRACT FOR SOLAR ROOFTOP POWER SYSTEM (CAMC)

The Contractor shall offer the following at no extra cost to the bank. The rate quoted for CAMC should include the following.

- 1. The Contractor shall maintain the plant and ensure that it works as per the tendered parameters.
- 2. All the repairs and replacements of spares shall be carried out which are necessitated due to usage of system as per tender stipulations. However, the repairs and replacements necessitated by loss or damage due to misuse or accident, fire or natural calamities shall be out of the scope of CAMC.
- 3. The Contractor should visit every month for preventive maintenance of the system. If any breakdown calls for emergency service, the same shall be attended within 24 hrs. One of the scheduled preventive maintenance shall also be completed during such visits. Visits also shall be made for the upkeep of the system to ensure at no point of time the plant capacity is less than 90%.
- 4. During the Preventive Maintenance, the contract includes servicing including PV panel cleaning, repairing, maintenance and replacement of spare parts of

Solar Power System for the satisfactory running of the system. During each visit the supplier shall carry out Thermography checks during the CAMC period to identify hot spot of PV modules and take corrective action. The same shall be recorded in a log book which shall be verified and confirmed by bank's representative.

5. During the break down calls, the nature of repair carried out, parts replaced etc shall be recorded in the log book.

#### **OTHER TERMS WITH REGARD TO CAMC:**

- 1. The rate of annual maintenance charges shall be furnished for a period of 4 years after the warranty/Defect Liability Period and rates quoted shall be binding on the Contractor.
- 2. The scope and terms of Comprehensive Annual Maintenance Contract (CAMC) like number of monthly visits, items covering under CAMC, replacement of spares exclusions if any, down time for break down and service calls shall be as mentioned above.
- 3. The Bank reserves the right of discontinuing the CAMC from the contractor during the tenancy of the Maintenance Contract.
- 4. The cost of Comprehensive Annual Maintenance Charges shall also be one of the criteria in evaluation of cost economics of the tender. All the activities under this clause shall be completed within the stipulated time.

# PRICE BID TERMS OF PRICE BID

- 1. Prices quoted must be firm for the period /extended period of contract. No escalation shall be admissible in respect of any item of the contract, except in case of statutory variation in items like excise duty, works contract tax (if applicable), which shall be reimbursed subject to submission of necessary documents.
- 2. No escalation due to IEEMA clause shall be admissible.
- **3.** Price quoted must be inclusive of all items required for the entire job of design, manufacture, supply to site, erection, testing, commissioning, and handing over including ancillary items like minor civil works, all electrical items etc., and nothing extra shall be paid.
- **4.** All materials shall be insured against theft, damage, etc., from the time they are transported from the factory upto the time of handing over to the bank. No claim in respect of any damage/ loss shall be entertained.
- 6. Watch and ward responsibility at site shall be the responsibility of the contractor.
- 7. CAMC RATES: WITH REGARD TO CAMC, THE RATES SHOULD BE QUOTED EXCLUDING GOODS & SERVICE TAX (GST). APPLICABLE GST WILL BE PAID DURING THE COURSE OF AMC.
- 8. The value of items of Price bid & Present Value of the AMC amount for 4 years after completion of Defect liability period will be commuted for arriving lowest bidder (L1).

<u>Calculation of Present Value</u>: The Present value of AMC charges for 4 years after 1 year defect liability period will also be evaluated to arrive at Lowest Contractor (L-1). The present value of the AMC component per year will be calculated as per the following formula:

Present Value =  $c / (1+r)^n$ 

Where 'c' is the annual CSMC of each year

'r' is REPO LINKED LENDING RATE WHICH AT PRESENT IS 6.9%

'n' is number of years, ie., n is 1 for 1st year and 2 for 2nd year...

The above mentioned calculation is for Price comparison purpose only.

Therefore, the Contractors / contractors shall furnish the AMC charges in the Price bid for 4 years and the AMC shall be Comprehensive AMC (CAMC).

The Price quoted is subject to arithmetic errors i.e in case there is error, the individual sum total shall be considered.

9. THE CONTRACTOR HAS TO EXECUTE AGREEMENT WITH IN 7 DAYS FROM THE DATE OF ORDER ( AS PER THE FORMAT GIVEN BY THE BANK ), CONFIRMING THAT THE SOLAR POWER PLANT WILL BE MAINTAINED AT THE TENDERED RATE FOR FOUR YEARS AFTER WARRANTY PERIOD.

# PRICE BID FOR CIRCLE OFFICE KARNAL

S No	Description	Quantity	Rate per KWp in Rs	GST in Rs.	Total Amount Rs
1.			, <b>,</b>		
	Supply of materials -	Applic	able GST @_	%	
	Design, Manufacture,				
	Supply of complete				
	materials for generation				
	of Solar photovoltaic				
	(SPV) based Grid				
	interactive Solar Power				
	System of 35KWp of				
	operation including				
	required quantities of SPV				
	modules formed into				
	arrays their mounting				
	arrangement, On-Grid				
	power conditioning units,				
	required DC & AC				
	Distribution panels with				
	surge protection units,				
	copper cabling of required				
	rating from terrace to main distribution board at	35KWp			
	Electrical Room at Ground				
	Floor, require earthing,				
	Communication Interface				
	with data Logging along				
	with PC based				
	arrangement for system				
	performance monitoring				
	through licensed				
	software, solar energy				
	meter fixed at AC DB				
	near Grid Inverter, safety				
	arrangements etc. as				
	defined in the scope and				
	in accordance with laid				
	down functional				
	requirement and				
	specifications to provide a				

	composite operational system including liaisoning for all statutory approval etc. as details in the technical specification SPV module - (minimum 400 Wp Crystalline Silicon Terrestrial PV Modules)				
2	Installation, Testing & Com	missioning (1	ITC) - Applic	able GST @	<u> </u>
	Installation, testing and commissioning of the complete system including module mounting arrangement for SPV module/arrays, related civil works as required and as specified to provide a complete operational system including training etc.,  Total Amount = 1+2	35KWp			
	The rate exclusive of GST in	n words		only	,
3	only Comprehensive Annual Maintenance Charges for 4 years after defect liability period of 1 year – <b>The amount is exclusive of GST.</b>				
	Rate for all inclusive Upkeep & routine Maintenance of complete system as provided under the CAMC contract for periodic cleaning of PV cells, PCU/Solar Inverter etc. to ensure the committed minimum power generation including all spares, consumables for trouble shooting, routing, preventive and breakdown maintenance etc. as required as per	35KWp		NA	

	good engineering					
	practice,					
	recommendations in the					
	respective equipment					
	manufacturer and					
	instructions and					
	instructions of engineer in					
	charge form maintaining					
	the system inacceptable					
	functional and serviceable					
	state etc. as specified and					
	as per the scope of work					
	laid down.					
	1 <sup>st</sup> YEAR			NA		
	2 <sup>nd</sup> YEAR			NA		
	3 <sup>rd</sup> YEAR			NA		
	4 <sup>th</sup> YEAR			NA		
	Sub Total (1 to 4 years)					
	Total (1+2+3)					
Total Amount in words:						
		Only				
4.	Supply & Installation of Net	Metering: ( <b>Th</b>	e amount is	exclusive	of GST)	
	Supply, installation of Net					
	metering and HT cubical					
	meter with Load Breaker		Quote rate			
	Switch to meet the					
	requirements.					
	The Equipment shall meet					
	all the requirements of					
	latest MNRE / DISCOM					
	guidelines.					

#### **Important Notes:**

- 1. The above point no: 04 regarding supply & installation of net metering with panel. The rate quoted will not be considered for arriving at L1 Bidder.
- 2. The Present value of AMC charges for 4 years after 1 year defect liability period will be arrived at to decide the Lowest Contractor (L-1). The present value of the AMC component per year will be calculated as per the following formula:

Present Value =  $c / (1+r)^n$ 

Where 'c' is the annual CAMC of each year 'r' is REPO LINKED Lending Rate which is at present 6.9% 'n' is number of years, ie. n is 1 for 1st year and 2 for 2nd year...

The above mentioned calculation is for Price comparison purpose only.

3. Contractor has to note that the total capacity of the solar power plant should notbe less than 35 KWp (Karnal CO)

# PRICE BID FOR REGIONAL OFFICE PANCHKULA

S No	Description	Quantity	Rate per KWp in Rs	GST in Rs.	Total Amount Rs
1.			•		
	Supply of materials -	Applic	able GST @_	%	
	Design, Manufacture,				
	Supply of complete				
	materials for generation				
	of Solar photovoltaic				
	(SPV) based Grid				
	interactive Solar Power				
	System of 25KWp of				
	operation including				
	required quantities of SPV				
	modules formed into				
	arrays their mounting				
	arrangement, On-Grid				
	power conditioning units,				
	required DC & AC				
	Distribution panels with				
	surge protection units,				
	copper cabling of required				
	rating from terrace to	25KWp			
	main distribution board at				
	Electrical Room at Ground				
	Floor, require earthing,				
	Communication Interface				
	with data Logging along				
	with PC based				
	arrangement for system				
	performance monitoring				
	through licensed				
	software, solar energy				
	meter fixed at AC DB				
	near Grid Inverter, safety				
	arrangements etc. as				
	defined in the scope and				
	in accordance with laid				
	down functional				
	requirement and				
	specifications to provide a				Page 102 of 105

	composite operational system including liaisoning for all statutory approval etc. as details in the technical specification SPV module - (minimum 400 Wp Crystalline Silicon Terrestrial PV Modules)				
2	Installation, Testing & Com	missioning (1	TC) - Applic	able GST @	<u>a</u> %
	Installation, testing and commissioning of the complete system including module mounting arrangement for SPV module/arrays, related civil works as required and as specified to provide a complete operational system including training etc.,  Total Amount = 1+2	25KWp			
	The rate exclusive of GST in	n warda			
	The rate exclusive of GST in	n words		only	/
3	Comprehensive Annual Maintenance Charges for 4 years after defect liability period of 1 year – <b>The amount is exclusive of GST.</b>				
	Rate for all inclusive Upkeep & routine Maintenance of complete system as provided under the CAMC contract for periodic cleaning of PV cells, PCU/Solar Inverter etc. to ensure the committed minimum power generation including all spares, consumables for trouble shooting, routing, preventive and breakdown maintenance etc. as required as per	25KWp		NA	

	good engineering					
	practice,					
	recommendations in the					
	respective equipment					
	manufacturer and					
	instructions and					
	instructions of engineer in					
	charge form maintaining					
	the system inacceptable					
	functional and serviceable					
	state etc. as specified and					
	as per the scope of work					
	laid down.					
	1 <sup>st</sup> YEAR			NA		
	2 <sup>nd</sup> YEAR			NA		
	3 <sup>rd</sup> YEAR			NA		
	4 <sup>th</sup> YEAR			NA		
	Sub Total (1 to 4 years)					
	Total (1+2+3)					
Total Amount in words:						
		Only				
4.	Supply & Installation of Net	Metering: ( <b>Th</b>	e amount is	exclusive	of GST)	
	Supply, installation of Net					
	metering and HT cubical					
	meter with Load Breaker		Quote rate			
	Switch to meet the					
	requirements.					
	The Equipment shall meet					
	all the requirements of					
	latest MNRE / DISCOM					
	guidelines.					

#### **Important Notes:**

- 4. The above point no: 04 regarding supply & installation of net metering with panel. The rate quoted will not be considered for arriving at L1 Bidder.
- 5. The Present value of AMC charges for 4 years after 1 year defect liability period will be arrived at to decide the Lowest Contractor (L-1). The present value of the AMC component per year will be calculated as per the following formula:

Present Value =  $c / (1+r)^n$ 

Where 'c' is the annual CAMC of each year 'r' is REPO LINKED Lending Rate which is at present 6.9% 'n' is number of years, ie. n is 1 for 1st year and 2 for 2nd year...

The above mentioned calculation is for Price comparison purpose only.

6. Contractor has to note that the total capacity of the solar power plant should notbe less than 25 KWp (Panchkula RO)